

Costs of Mitigating CO₂ Emissions from Passenger Aircraft

Andreas W. Schäfer^{1,2,*}, Antony D. Evans³, Tom G. Reynolds⁴, Lynnette Dray¹

¹UCL Energy Institute, University College London, London, UK

²Precourt Energy Efficiency Center, Stanford University, Stanford, CA, USA

³University of California Santa Cruz, Moffett Field, CA, USA

⁴Lincoln Laboratory, Massachusetts Institute of Technology, Lexington, MA, USA

* Corresponding author

In response to strong growth in air transportation CO₂ emissions, governments and industry began to explore and implement mitigation measures and targets in the early 2000s. However, in the absence of rigorous analyses assessing the costs for mitigating CO₂ emissions, these policies could be economically wasteful. Here we identify the cost-effectiveness of CO₂ emission reductions from narrow body aircraft, the workhorse of passenger air transportation. We find that in the US, a combination of fuel burn reduction strategies could reduce the 2012 level of CO₂ emissions per passenger-km by around 2% per year through mid-century. These intensity reductions would occur at zero marginal costs for oil prices between \$50-100 per barrel. Even larger reductions are possible, but could impose extra costs and require the adoption of biomass-based synthetic fuels. The extent to which these intensity reductions will translate into absolute emissions reductions will depend on fleet growth.

Air transportation currently releases around 2.5% of global fuel combustion-related CO₂ emissions.^{1,2} In addition, since 1980, this sector's emissions have increased at a rate of 3.6% per year, i.e., twice the world total.² Non-CO₂ effects from aviation, which partly scale with CO₂ emissions, can also contribute to climate change.³ In response to this growth trend, the European Commission, two US Government agencies, the International Civil Aviation Organization, and the International Air Transport Association began to explore or implement CO₂ mitigation measures and targets. (Supplementary information: government and industry action). For these interventions to have an economic rationale, they need to rely on a solid understanding of the potential for and costs of mitigating CO₂ emissions. Yet, this need contrasts sharply with the current body of studies in this area.

Existing studies consist of consultancy reports with a global focus^{4,5,6} and a UK perspective⁷, two studies of the UK air transportation system^{8,9}, and one detailed technoeconomic study of three retrofit technologies.¹⁰ These analyses are valuable first steps towards a better understanding of the economic benefits and costs of CO₂ mitigation but possess limitations. For example, *refs 5, 6* do not report the underlying assumptions, methods, and data employed, which yields non-reproducible results; *refs 8, 9* do not consider the age composition of the aircraft fleet, which is a critical omission as fuel efficiency differs by age cohort thus affecting mitigation potentials and costs; *ref 7* omits important cost elements of key mitigation options; *refs 7, 10* consider only a narrow range of mitigation strategies, thus limiting our understanding of the overall mitigation potential. The shortage of carefully conducted studies may help explain the lack of comprehensive economic assessments of aviation emission reduction opportunities in the transport chapter of all IPCC Assessment Reports, and the

perception that reducing aircraft CO₂ emissions may be more difficult and more expensive compared to other sectors.¹¹

Here we present a techno-economic analysis of 21 CO₂ emission mitigation options for the domestic US aviation sector, the world's single largest air transportation system. We focus on narrow body aircraft with 100-189 seats, which generate 80% of revenue passenger-km (RPK), i.e., those passenger-km that generate airline revenue, burn nearly 75% of commercial passenger aircraft consumed jet fuels, and hence also release nearly 75% of CO₂ emissions (Supplementary information: Table S1). Our analysis is based on an aircraft fleet composition and CO₂ emissions model that allows (i) a realistic simulation of the introduction of improvements to existing aircraft (retrofits) and of new aircraft generations, (ii) a robust assessment of the CO₂ emissions mitigation potential and cost of all mitigation options related to the aircraft age cohort (those aircraft of a given vintage) that would be affected, and (iii) simulating the scheduling of aircraft retrofits in line with major maintenance checks to minimize the opportunity costs of non-available aircraft. (See Methods Section). In addition, we account for all relevant cost elements affecting airline operating costs, using the most recent data available.

Fleet CO₂ Intensity

Figure 1 depicts the historical decline in lifecycle CO₂ intensity (lifecycle CO₂ emissions per RPK) of the US commercial passenger aircraft fleet and of the narrow body passenger fleet.^{12,13} Also shown is the estimated historical development of the CO₂ intensity of *new* narrow body aircraft, which, after around 15 years, translates into that of the aircraft fleet.

The decline in fleet CO₂ intensity was particularly strong (at a rate of nearly 5% per year) between 1970 and 1980, mainly due to increases in the efficiency of aircraft engines. Thereafter, CO₂ intensity continued to decline at a lower rate of 2% per year due to mainly continuous improvements in engine efficiency, aerodynamics, and utilization of aircraft capacity.¹² Because commercial air transportation nearly exclusively burns petroleum-derived jet fuel, the historical decline was entirely a result of fuel efficiency improvements. Despite the past achievements, there continue to exist opportunities for further strong reductions, as shown by the projected future developments in Figure 1 and discussed below.

Opportunities for Mitigation

The opportunities for reducing aircraft CO₂ intensity can be illustrated by the Breguet range equation, modified such that CO₂ intensity represents the left-hand-side variable (equation 1). Although this equation only applies to cruise flight, the vast majority of fuel is burnt in the cruise phase and hence it offers intuition to understand the determinants of CO₂ emissions.

$$\frac{CO_2}{RPK} = CO_2EF \frac{Q \cdot SFC}{PAX \cdot V \cdot L/D} \frac{W_F}{\ln(W_0/(W_0 - W_F))} \quad (1)$$

In equation 1, CO₂EF is the CO₂ emissions factor (87.6 gCO₂/MJ for Jet A-1 fuel on a lifecycle basis, that is, after accounting for upstream emissions with respect to crude oil extraction, transportation, refining, jet fuel distribution and storage, which represent around 21% of the fuel carbon-related CO₂ emissions¹⁴), Q the fuel's lower heating value (42.8 MJ/kg for jet

fuel), SFC the engine specific fuel consumption (fuel burn per unit thrust), PAX the number of passengers, V the aircraft speed, L/D the lift-to-drag ratio, W_F the fuel weight before takeoff, and W_0 the aircraft weight at takeoff. Hence, aircraft CO₂ intensity can be reduced through fuels containing lower carbon on a lifecycle basis, higher engine efficiency, a larger number of passengers, higher aerodynamic efficiency, and a lower structural weight (a smaller $W_0 - W_F$). Note that the variables in equation 1 are interrelated. Thus, changing one variable will lead to changes in others, typically offsetting part of the impact on CO₂/RPK.

Each of the 21 mitigation options examined in this study influences at least one determinant of the CO₂ intensity in equation 1. We derive these options' CO₂ emissions reduction potential and costs from academic studies, industry sources, and our own calculations. (Supplementary information: Measures for Reducing Narrow Body Aircraft CO₂ Emissions). The measures, which are listed with the main techno-economic characteristics in Tables 1-3, can be grouped into four families:

- Technology options (Table 1): five retrofit options, one Intermediate Generation Aircraft type and two Next Generation Aircraft types aiming to reduce SFC, structural weight, or increase L/D
- Synthetic fuels (Table 1): cellulosic biomass-based fuels (biomass-to-liquids [BTL]) aiming to reduce CO₂EF
- Air traffic management measures (Table 2): five strategies that consist of bundles of measures, aiming to reduce SFC and the excess distance an aircraft flies
- Airline operational strategies (Table 3): nine measures aiming to increase the number of PAX and L/D, or to reduce SFC along with the fuel weight.

Other studies (e.g., *ref 8*) evaluated the CO₂ mitigation characteristics of engine upgrade kits, auxiliary power units, etc. We deliberately exclude these options from our analysis, as they seem too speculative in the absence of reliable data. We also exclude secondary mitigation opportunities that arise from some of the above options, such as increased seat density due to lighter and thinner aircraft seats and subsequent cabin re-optimization, as their degree of exploitation is uncertain.

Mitigation Potentials and Costs

To estimate the CO₂ abatement potentials and costs for the US narrow body aircraft fleet, we introduce the mitigation options summarized above and described in Tables 1-3 into our Fleet Composition and CO₂ Emissions Model. (Our model and choice of parameters are designed to minimize possible interactions of mitigation measures). As a reference vehicle we use the average fuel burn and operational characteristics of the US narrow body aircraft fleet. (Table S1 in supplementary information). We assume that aircraft utilization remains unchanged relative to the 2012 level, i.e., an average of 268 million RPK per narrow body aircraft per year.

The baseline development, which incorporates only the introduction of 2012 technology through natural fleet turnover, would lead to a 22% decline in the lifecycle CO₂ intensity of the narrow body fleet from 125 gCO₂/RPK in 2012 to 98 gCO₂/RPK in 2050, as depicted by curve (1) in Figure 1. If also taking into account the planned adoption of more fuel-efficient Intermediate Generation Aircraft starting in 2016, the 2050 fleet CO₂ intensity would be 15% below the baseline development or 34% below the 2012 intensity as shown by curve (2) in Figure 1. The related annual average decline corresponds to 1% per year.

We now explore the implications of introducing the maximum feasible combination of retrofit options, air traffic management measures and airline operational strategies which already exist or are currently under development. In addition, we simulate the introduction of a Next Generation Aircraft starting in 2035, which could offer a roughly 30% fuel burn and CO₂ emissions reduction over the Intermediate Generation Aircraft. This drastic decline is enabled by mainly open rotor engines, an all-carbon fiber airframe, and the structural advantage resulting from non-swept wings, which are made possible by a slight reduction of cruise speed.^{15,16} As a result of introducing this portfolio of mitigation strategies, the 2050 fleet CO₂ intensity could decline by an additional 25% relative to the baseline development plus Intermediate Generation Aircraft technology, as shown by curve (3) in Figure 1. Further reductions could be realized through cellulosic biomass-based synthetic fuels. A 15% (or 30%) BTL share of jet fuels consumed in 2050 could lead to a further 13% (or 26%) decline in the 2050 CO₂ intensity of the narrow body fleet, as depicted by curves (4) and (5) in Figure 1. Thereby, the 30% BTL share would lead to an average decline in CO₂ intensity by 2.6% per year. If taking into account only the CO₂ emission reduction options with negative or zero marginal costs identified in Figure 2 below, the projected 2050 fleet CO₂ emissions intensity would decline by 50% compared to the 2012 level; see dotted curve (CE) in Figure 1. The associated annual decline by nearly 2% of the cost-effective intensity trajectory essentially continues the more recent (1980-2012) development.

A detailed account of the cost-effectiveness of the various mitigation options is shown in Figure 2 for a jet fuel price of \$3.1 per gallon, which corresponds to an oil price of about \$100 per barrel. In addition, the shape of the curve for an oil price of \$50 per barrel is shown as a thin dashed line. Underlying this figure is a 1.5% annual growth rate of the narrow body fleet. This

rate is slightly lower than industry projections over the shorter 2014-2033 period^{17,18}, to account for the continuous maturation of the domestic US market. Combining the growth in the narrow body fleet with the baseline CO₂ intensity described above leads to cumulative (2012-2050) lifecycle CO₂ emissions of 4.0 billion tonnes. As can be seen from the horizontal axis of Figure 2, these projected cumulative emissions could be reduced by about 1 billion tonnes for a 15% adoption of synthetic fuels from biomass in 2050 (or by 1.1 billion tonnes for a BTL share of 30% in 2050, which is not shown here).

Clearly, a combination of strategies would be required for a meaningful mitigation impact. Yet, the mitigation potential is distributed unevenly across the measures. Overall, one-third of the 21 measures could exploit around 80% of the cumulative mitigation potential. Aircraft technology options provide around half of the entire cumulative CO₂ emissions mitigation potential. The second largest potential is offered by air traffic management measures and airline operational strategies with around 20% each. Synthetic fuels from cellulosic biomass would then account for the remaining roughly 10% under the assumed penetration rates.

As a mitigation cost metric, we employ the cumulative (2012-2050) marginal abatement costs, discounted to 2012 at a rate of 5%. This metric captures *all* mitigation opportunities over time, as otherwise especially the retrofit options would emerge and vanish due to the evolving age structure of the fleet. The cumulative nature of the mitigation costs also accounts for fuel burn reductions beyond the period of economic accounting (20 years for new aircraft and 5 years for retrofits according to industry practice), provided they are introduced sufficiently long before 2050. (Partly as a consequence, the mitigation costs in Figure 2 are lower than those in Tables 1-3). In addition, our specification of mitigation costs accounts for the stock properties of CO₂ that result from its long atmospheric lifetime. Because the exact mitigation potential and costs depend

on the year of introduction of each measure (as different age cohorts with different fuel burn characteristics would be affected) and the extent to which each measure is introduced, the figure legend specifies the introduction characteristics in more detail. As can be seen, at least 75% of the CO₂ emissions mitigation potential comes at negative or zero marginal costs. In particular, some airline operational strategies, nearly all technology options, and the entire range of air traffic management measures turn out to be cost-effective. If the lower end of the projected range of BTL supply costs of \$3.0-3.6 per gallon can be realized, synthetic fuels could just become cost-effective at a jet fuel price of \$3.1 per gallon.

The identified negative and zero marginal cost measures represent the economically attractive mitigation opportunities from an industry viewpoint (at the chosen discount rate and economic lifetime). Even larger reductions could be justified from a societal perspective, as long as the mitigation costs do not exceed the marginal damages of CO₂. Estimates of the social cost of carbon (SCC) are highly uncertain, but likely above the upper end of the projected cost range of up to \$34 per tonne of CO₂ (oil price of \$50 per barrel) for BTL.¹⁹

Figure 3 shows the associated wedge diagram of annual CO₂ emissions, where some of the families of measures are further broken down and ranked broadly according to their cost-effectiveness. The introduction of new, highly fuel-efficient aircraft technologies in 2035 is of paramount importance to outpace the anticipated growth in air transportation demand. Additional significant emission reductions could be achieved from synthetic cellulosic biomass-based fuels. The same figure also shows the emission mitigation benefit of retrofits and early aircraft replacements is only short-term; by 2050, their effect over time has virtually evaporated, as by then nearly all of the retrofitted and the early-replaced aircraft would have been substituted. Yet, due to the long atmospheric lifetime of CO₂, the cumulative emission reductions remain

beneficial. If only introducing cost-effective options at a fuel price of \$2.0-3.1 per gallon from Figure 2, the 2050 narrow body aircraft CO₂ emissions could decline to a level of 77 million tonnes, a roughly 10% decline relative to the 2012 level (dotted line).

Future Developments

Natural fleet turnover, the scheduled introduction of Intermediate Generation Aircraft, the eventual adoption of Next Generation Aircraft, improvements in air traffic management and slightly more efficient airline operations could reduce the average CO₂ intensity of the US narrow body fleet by about 2%/yr at zero marginal costs for oil prices between \$50-100 per barrel. Further reductions could be achieved through cellulosic biomass-based synthetic fuels.

In addition to CO₂ intensity, the amount of CO₂ emissions will depend on fleet growth. While a fleet growth rate below 2% per year could result in lower 2050 emissions relative to the 2012 level, growth rates higher than 2.6% per year would outpace the CO₂ emission reduction potential of the entire portfolio of measures and adoption rates examined here.

Consistent with our findings, the air transportation industry has already started to pursue all options we identified as being cost-effective. Some of these measures, such as blended winglets, are already being adopted. Many others will likely also be introduced into existing and future models once they become available, thus assuring a continuous decline in operating costs (all other factors equal) and increase in industrial competitiveness.

The limited number of data points underlying many mitigation options does not allow for an uncertainty analysis to be performed without expert elicitation. Clearly, better understanding

the uncertainties underlying this study is an important next step. Nonetheless, because we omitted several mitigation options due to a lack of data and did not explore the optimized timing of their introduction, our key finding that a 2% CO₂ fleet intensity reduction could be achieved at zero marginal costs is likely conservative.

FIGURES

Figure 1 Lifecycle CO₂ emissions intensity of the US commercial passenger aircraft fleet operating in domestic service (black) and of the narrow body fleet (gray), historical development (1970-2012) and projections (2013-2050). Due to increases in aircraft fuel efficiency improvements, the CO₂ intensity of the US aircraft fleet declined by nearly 5% per year between 1970 and 1980, and by 2% per year thereafter. Despite the past achievements, there continue to exist opportunities for further strong reductions at least through 2050. Data sources for historical trends: *refs. 12, 13*

Figure 2 Discounted marginal abatement costs for cumulative (2012-2050) lifecycle CO₂ emissions from narrow body aircraft in US domestic passenger service. Mitigation options are ranked in sequence of declining cost-effectiveness. Around one-quarter of the cumulative CO₂ emissions of 4.0 billion tonnes that are based on fleet turnover and growth (1.5% per year) could be mitigated if employing all options. At least 75% of that potential could be reduced at zero marginal costs.

Figure 3 Lifecycle CO₂ emissions, historical trend (1991-2012) and future projections (2013-2050) of the mitigation potential by category of measures. In light of the anticipated

fleet growth rate of 1.5% per year, lifecycle CO₂ emissions from the US narrow body aircraft fleet could be reduced by about 10% between 2012 and 2050, even without the introduction of synthetic fuels from cellulosic biomass.

Table 1 Techno-economic characteristics of CO₂ mitigation technologies and synthetic fuels at a fuel price of \$3.1 per gallon (crude oil price of \$100/bbl)

	Year of Introduction	Application Potential ¹ %Fleet	Lifecycle CO ₂ Emissions Reduction %/Aircraft	Payback Period ² Years	Mitigation Costs ² \$/tonne(CO ₂)
Retrofits					
Blended winglets	2015	25	3.0 (2-4)	3.3	-80
Carbon brakes	2015	13	0.35 (> 0)	1.0	-10
Re-engining	2016	70	12.5 (1-12)	15	830
Cabin weight reduction					
Mild	2015	0	1.2	2.9	-110
Aggressive	2015	50	2.1 (0.6-1.6)	5.3	70
Electric taxiing	2018	50	2.8 (1.5-4)	2.1	-170
Intermediate Generation Aircraft					
A320NEO/B737MAX/CSeries	2016	100	15	2.9	-250
Next Generation Aircraft					
Evolutionary	2035	0	30	6.2	-160
Open rotor	2035	100	40	9.7	-70
Synthetic Fuels					
Biomass-to-Liquids (BTL)	2020	15-30 ³	13-26 ⁴	0-∞ ⁵	-10 to 70

Table Notes:

All monetary units are in 2010 US dollars. ¹Numbers underlying our analysis represent upper limit as retrofits are only implemented if investments are fully recuperated by the time the respective age cohort reaches the mean aircraft lifetime of 29 years. ²At year of introduction; economic lifetime: 20 years for new aircraft, 5 years for retrofits; discount rate 5%. ³In 2050. ⁴For BTL share of 15-30%. ⁵The projected lower end fuel price of \$3.0 per gallon results in immediate benefits, whereas the projected higher end fuel price of \$3.6 per gallon will never result in cost-effectiveness at identical fuel burn at a jet fuel price of \$3.1 per gallon. For details see supplementary information.

References for estimates and/or literature ranges (in parenthesis):

Winglets: 4,7,8, 20,21,22. **Carbon brakes:** 23,24. **Re-engining:** 4,8,10,25. **Cabin weight reduction:** 8,26,27. **Electric taxiing:** 28,29,30,31. **Synthetic Fuels:** 32,33,34.

Table 2 Techno-economic characteristics of air traffic management measures at a fuel price of \$3.1 per gallon (crude oil price of \$100/bbl)

	Full Deploy- ment Year	Application Potential %	Lifecycle CO ₂ Emissions Reduction ¹ %/Aircraft	Payback Period ² Years	Mitigation Costs ² \$/tonne(CO ₂)
Surface congestion management	2020	100	0.8	0.5	-310
Single engine taxi	2015	50	2.0	0.1	-320
Optimized departures procedures	2020	75	1.6	3.3	-240
Lateral/vertical/speed inefficiency reduction during cruise	2020	75	4.6	0.2	-320
Optimized approach procedures	2020	75	1.6	3.3	-240

Table Notes:

All monetary units are in 2010 US dollars. ¹Assuming gate-to-gate (block) fuel burn is divided into taxi, departure, cruise, and arrival on a 5%, 8%, 83%, and 4% basis according to BTS Form 41 block hour analysis. ²At year of introduction. For details see supplementary information.

References for estimates:

Surface congestion management: benefits: 35. **Single engine taxiing:** benefits: 36. **Optimized departures procedures:** benefits: 37, costs: 38,39. **Lateral / Vertical / Speed Inefficiency Reduction during Cruise:** benefits: lateral: 40, vertical: 41, speed: 42. **Optimized approach procedures:** benefits: RNAV/RNP: 37, CDAs: 43, DDAs: 44; costs: 38,39.

Table 3 Techno-economic characteristics of airline operational strategies at a fuel price of \$3.1 per gallon (crude oil price of \$100/bbl).

	Application Potential %Fleet	Lifecycle CO ₂ Emissions Reduction %Aircraft	%Fleet	Payback Period Years	Mitigation Costs \$/tonne(CO ₂)
Reducing contingency fuel by 300kg	100	0.38 (0.38)	0.38	0	-330
Early replacements by Intermediate Generation Aircraft					
≥ 25 years of age, in 2016	10 ¹	55	8.7	11	100
≥ 30 years of age, in 2016	1 ¹	65	1.0	7	-50
≥ 25 years of age, in 2020	11 ¹	52	8.7	12	160
≥ 30 years of age, in 2020	4 ¹	57 (5-20) ²	3.9	10	80
Increased PAX load factor through					
2% reduction of flight frequency	100	-0.3	3.1 ³	0.5	-200
enhanced use of Regional Jets	0.4 ⁴	33	0.3	23	7,500
enhanced use of Turboprops	0.3 ⁴	57	0.3	96	32,000
Reduced fuel tankering	15	0.26	0.04 (0.2)	> 1	4,100
Additional engine wash	50	0.25 (0.5-1.2)	0.13	0.4	-190
Surface polish and reduced decorative paint	10	0.1 (0.1-1.5)	0.01	> 1	4,500

Table Notes:

All monetary units are in 2010 US dollars. ¹Based upon 1.5% fleet growth per year. ²Replacing 5-20 year old aircraft: *ref* 4,8. ³A large part is related to the retirement of the oldest 2% of the aircraft in the fleet, which are not required anymore. ⁴%RPK. For details see supplementary information.

Key references for estimates and/or literature ranges (in parenthesis):

Reducing contingency fuel: 8. **Early aircraft replacements:** 4,8. **Reduced fuel tankering:** 4,8,9.

Additional engine wash: 8,45. **Surface Polish:** 4,8,46

References

¹ International Energy Agency (IEA). CO₂ emissions from fuel combustion: detailed estimates (2014).

² Energy Information Administration (EIA). International Energy Statistics. www.eia.gov (accessed 2015).

³ Lee, D. S. *et al.* Aviation and global climate change in the 21st century. *Atmospheric Environment*, 43(22), 3520-3537 (2009).

⁴ Henderson, J. Controlling Carbon Dioxide Emissions from the Aviation Sector. Stratus Consulting Inc., Boulder CO (2005).

⁵ McKinsey&Company. Pathways to a Low-Carbon Economy, Version 2 of the Global Greenhouse Gas Abatement Cost Curve (2009).

⁶ Pearce, B. Commercial Airline CO₂ and Mitigation Potential. International Air Transport Association (2009).

⁷ Holland, M. *et al.* A Marginal Abatement Cost Curve Model for the UK Aviation Sector Department for Transport, London (2011).

⁸ Morris, J., Rowbotham, A., Angus, A., Mann, M., Poll, I. A Framework for Estimating the Marginal Costs of Environmental Abatement for the Aviation Sector, Omega Report, Cranfield University (2009).

⁹ Raper, D. *et al.* UK Aviation: Carbon Reduction Futures, Department for Transport, London (2009).

¹⁰ Jesse, E., van Aart, P., Kos, J. Cost-benefit studies of possible future retrofit programmes. WP/Task No. D4.2. EC-FP7 RETROFIT Project (2012).

¹¹ European Commission (EC). Reducing the Impact of Aviation on Climate Change, Economic aspects of inclusion of the aviation sector in the EU Emissions Trading Scheme, Briefing Note IP/A/ENVI/FWC/2005-35 (2006).

¹² Lee, J.J., Lukachko, S.P., Waitz, I.A., Schäfer A. Historical and Future Trends in Aircraft Performance, Cost, and Emissions, *Annual Review of Energy and the Environment* 26, 167-200 (2001).

¹³ Department of Transportation. Air Carrier Statistics and Financial Reports (Form 41). Washington, DC (2014).

¹⁴ Stratton, R.W., Min Wong, H., Hileman, J. Quantifying Variability in Life Cycle Greenhouse Gas Inventories of Alternative Middle Distillate Transportation Fuels. *Env. Science & Techn.* 45, 4637-4644 (2011).

¹⁵ Graham, W.R., Hall, C.A., Vera Morales, M. The potential of future aircraft technology for noise and pollutant emissions reduction, *Transport Policy* 34, 36-51 (2014).

¹⁶ Vera Morales, M., Graham, W.R., Hall, C.A., Schäfer A. Techno-Economic Analysis of Aircraft, Deliverable D5 (WP 2 report), Technology Opportunities and Strategies towards Climate friendly transport (EC-FP7 TOSCA) project (University of Cambridge 2011).

¹⁷ Airbus. Global Market Forecast 2014-2033 (2014). [ww.airbus.com/company/market/forecast/](http://www.airbus.com/company/market/forecast/)

¹⁸ Boeing. Current Market Outlook 2014-2033 (2014). ww.boeing.com/boeing/commercial/cmo/

¹⁹ Moore, F.C, Diaz, D.B. Temperature impacts on economic growth warrant stringent mitigation policy, *Nature Clim. Change* 5, 127-131 (2015).

²⁰ Aviation Partners Boeing. <http://www.aviationpartnersboeing.com/index.php>

-
- ²¹ Airbus. Airbus launches Sharklet retrofit for in-service A320 Family aircraft. Press Release, October 29 (2013). <http://www.airbus.com/presscentre/pressreleases/press-release-detail/detail/airbus-launches-sharklet-retrofit-for-in-service-a320-family-aircraft/>
- ²² Freitag, W., Schulze, E.T. Blended Winglets Improve Performance. AERO Magazine, Boeing, Quarter 3, 9-12 (2009).
- ²³ Avitrader MRO. The Price of a Smooth Landing, September (2011).
- ²⁴ Allen, T., Miller, T., Preston, E. Operational Advantages of Carbon Brakes. AERO Magazine, Boeing. Quarter 3, 16-18 (2009).
- ²⁵ Chicago Tribune. Jet engine makers battle over performance. June 16 (2013). http://articles.chicagotribune.com/2013-06-16/business/sns-rt-us-air-show-enginesbre95f0f2-20130616_1_pratt-engine-cfm-international-leap-engine
- ²⁶ Flightglobal. How Airlines are losing weight in the cabin. 31 March (2014). <http://www.flightglobal.com/news/articles/analysis-how-airlines-are-losing-weight-in-the-cabin-397193/>
- ²⁷ Berglund, T. Evaluation of fuel saving for an airline. Bachelor Thesis in Aeronautical Engineering. (Mälardalen University, Sweden, 2008).
- ²⁸ Dzikus, N., Fuchte, J., Lau, A., Gollnick, V. Potential for Fuel Reduction through Electric Taxiing. 11th AIAA Aviation Technology, Integration, and Operations (ATIO) Conference, Virginia Beach, VA, 20-22 Sep. 2011.
- ²⁹ Hospodka, J. Cost-benefit analysis of electric taxi systems for aircraft, Journal of Air Transport Management 39, 81-88 (2014).
- ³⁰ Airbus. eTaxi—taxiing Aircraft with engines stopped. FAST Airbus Technical Magazine, 51, 2-10, January (2013).

³¹ Safran/Honeywell. EGTS (Electric Green Taxiing System), on the web:

<http://www.safranmbd.com/systems-equipment-178/electric-green-taxiing-system/>

³² Department of Energy (DOE). US Billion-Ton Update: Biomass Supply for a Bioenergy and Bioproducts Industry. R.D. Perlack and B.J. Stokes (Leads), ORNL/TM-2011/224. Oak Ridge National Laboratory (2011).

³³ Malina, R. *et al.* HEFA and F-T jet fuel cost analyses. MIT Laboratory for Aviation and the Environment. (Massachusetts Institute of Technology, 2012).

³⁴ Hileman, J. *et al.* Near-Term Feasibility of Alternative Jet Fuels (RAND and MIT, 2009).

<http://web.mit.edu/aeroastro/partner/reports/proj17/altfuelfeasrpt.pdf>

³⁵ Nakahara, A., Reynolds, T.G. Estimating Current & Future System-Wide Benefits of Airport Surface Congestion Management. 10th USA/Europe Air Traffic Management Research and Development Seminar, Chicago, IL (2013).

³⁶ Clewlow, R., Balakrishnan, H., Reynolds, T.G., Hansman, R. J. A Survey of Airline Pilots Regarding Fuel Conservation Procedures for Taxi Operations, International Airport Review, Issue 3 (2010).

³⁷ Muller, D., Uday, P., Marais, K.B. Evaluation of Trends and Potential Environmental Benefits of RNAV/RNP Arrival and Departure Procedures. 11th AIAA Aviation Technology, Integration, and Operations (ATIO) Conference, Virginia Beach, VA, 21-22 Sep. (2011).

³⁸ Reason. Reason Foundation ATC Reform Newsletter, Oct. (2011).

<http://reason.org/news/printer/air-traffic-control-reform-news-87>

³⁹ Federal Aviation Administration (FAA). The Business Case for the NextGen Air Transportation System, Aug. (2012).

[http://www.faa.gov/nextgen/media/NextGen%20Bus%20Case%202012%20\(2012-10-05\).pdf](http://www.faa.gov/nextgen/media/NextGen%20Bus%20Case%202012%20(2012-10-05).pdf)

⁴⁰ Reynolds, T.G., 2008. Analysis of Lateral Flight Inefficiency in Global Air Traffic Management. 26th Congress of International Council of the Aeronautical Sciences/8th AIAA Aviation Technology, Integration and Operations Conference, Anchorage, AK, Sep. (2008).

⁴¹ Lovegren, J., Hansman, R. J. Estimation of Potential Aircraft Fuel Burn Reduction in Cruise via Speed and Altitude Optimization Strategies, SM Thesis, Department of Aeronautics and Astronautics, Massachusetts Institute of Technology, Feb. (2011).
<http://hdl.handle.net/1721.1/62196>.

⁴² Jensen, L., Hansman, R. J., Venuti, J., Reynolds, T.G. Commercial Airline Speed Optimization Strategies for Reduced Cruise Fuel Consumption. AIAA Aviation 2013 Conference, Los Angeles, CA (2013).

⁴³ Reynolds, T. G., Ren, L., Clarke, J.-P. B. Advanced Noise Abatement Approach Activities at a Regional UK Airport. Air Traffic Control Quarterly, 15(4), 275-298 (2007).

⁴⁴ Dumont, J.-M., Reynolds, T. G., Hansman, R. J. Fuel Burn and Emissions Reduction Potential of Low Power/Low Drag Approaches, 11th AIAA Aviation Technology, Integration, and Operations (ATIO) Conference, Virginia Beach, VA, Sep. (2011).

⁴⁵ Lufthansa Technik. Price List Line Maintenance Services for German Stations only (2014).
<http://www.lufthansa-technik.com/documents/100446/101431/Pricelist+German+Stations+2014.pdf>

⁴⁶ Hansen, D. Painting versus Polishing of Airplane Exterior Surfaces, AERO Magazine, Boeing. Quarter 1 (1999).

Author to whom correspondence and requests for materials should be addressed

Andreas W. Schäfer, UCL Energy Institute, University College London, Central House, 14 Upper Woburn Place, London WC1H 0NN, Tel 020 3108 5925, Email a.schafer@ucl.ac.uk

Acknowledgements

AWS gratefully acknowledges the funding provided by Stanford University's Precourt Energy Efficiency Center. TGR's contributions are based on work sponsored by the Federal Aviation Administration (FAA) under Air Force Contract FA8721-05-C-0002. Opinions, interpretations, conclusions, and recommendations are those of the authors and are not necessarily endorsed by the United States Government. TGR gratefully acknowledges support from the FAA Office of Environment and Energy.

Author Contributions

AWS led the specification of aircraft technologies and synthetic fuels, the development of the model, the analysis of the results, and the preparation of the manuscript. ADE led the specification of the airline operational strategies, developed elements of the model, and contributed to the analysis of the results and preparation of the manuscript. TGR developed the techno-economic characteristics of air traffic management systems, contributed to those of aircraft technologies and airline operational strategies, and contributed to the analysis of the results and preparation of the manuscript. LD developed elements of the model, including underlying fleet databases, and contributed to the analysis of the results and preparation of the manuscript.

Methods: Fleet Composition and CO₂ Emissions Model

The narrow body aircraft fleet composition model generates the fleet age distribution, energy use, and CO₂ emissions in absolute terms and per revenue passenger-km. It takes as inputs the projected narrow body aircraft fleet size at any year along with the energy intensity level of new narrow body aircraft. The number of new narrow body aircraft introduced in each year then results from the difference between the projected total fleet and those aircraft remaining, while the number of aircraft retirements is estimated with a generic retirement curve. The effect of international sales (to and from the US) is included where data is available; however, the impact on the overall totals is small.

We employ a retirement curve from those globally operating narrow body aircraft that were produced between 1965 and 2007.⁴⁷ During that period, these curves' characteristics were stable across aircraft from different manufacture years and world regions. The mean aircraft age at retirement of the cohorts forming the narrow body fleet was 28.6 years; that is, after that period, half of the aircraft fleet has been retired. Due to the characteristics of the data, the retirement curves were estimated with a logistic function. This symmetric S-curve is based on the BACK Aviation Fleet Database, which describes key attributes of the world aircraft fleet, such as the number of aircraft types by country, their entry into the fleet, sales of second-hand aircraft, and the year of their retirement between 1960 and 2007.⁴⁸ More recent (2007-2012) data describing the age composition of the US narrow body aircraft fleet are derived from Form 41 Schedule B43 data.¹³ The Form 41 data implies a mean age of 12.1 years for the 2012 US narrow body aircraft fleet used for domestic passenger transport.

Another key determinant of fleet energy use and CO₂ emissions is the energy intensity of new aircraft. There is a 10-15 years lag between the energy intensity level of an age cohort and that of the fleet.¹² We estimated a second order polynomial function describing the decline in new narrow body energy intensity over time, such that the resulting fleet energy intensity, after applying the aircraft stock model to each age cohort, best approximates the observed narrow body fleet energy intensity development from 1991 to 2012 (the derived relationship is: $E/RPK(\text{year}) = 0.00147839 \times \text{year}^2 - 5.949046 \times \text{year} + 5985.82037$; R^2 between observed and estimated narrow body aircraft fleet energy intensity for the 22 year period = 0.95). Other

functional forms were also tested, including exponential and hyperbolic, but the polynomial function was found to be most plausible and to correspond best to the ranges in energy intensity from new narrow body aircraft presented by *ref 12*. For all age cohorts forming the 2012 narrow body fleet, we assume an annual fuel burn deterioration of 0.2% due to wear and tear, compounded over the respective aircraft age.⁴⁹

References

⁴⁷ Dray, L. An analysis of the impact of aircraft lifecycles on aviation emissions mitigation policies, *Journal of Air Transport Management* 28, 62-69 (2013).

⁴⁸ BACK Aviation Solutions. *Global Fleet Database*. New Haven, CT (2008).

⁴⁹ Morrell, P., Dray, L. *Environmental Aspects of Fleet Turnover, Retirement, and Life-Cycle*, Final Report, Omega, Cranfield University (2009).





