

1 **A compact skeletal mechanism for *n*-dodecane with optimized semi-global low-temperature**
2 **chemistry for diesel engine simulations**

3
4 Tong Yao^{1, 2, 3*}, Yuanjiang Pei⁴, Bei-Jing Zhong^{2*}, Sibendu Som⁴, Tianfeng Lu³, Kai Hong
5 Luo^{1,5}
6

7 ¹*Center for Combustion Energy, Key Laboratory for Thermal Science and Power Engineering of Ministry*
8 *of Education, Department of Thermal Engineering, Tsinghua University, Beijing 100084, China*

9 ²*School of Aerospace Engineering, Tsinghua University, Beijing 100084, China*

10 ³*Department of Mechanical Engineering, University of Connecticut, Storrs, CT 06269-3139, USA*

11 ⁴*Energy System Division, Argonne National Laboratory, Argonne, IL-60439, USA*

12 ⁵*Department of Mechanical Engineering, University College London, Torrington Place, London WC1E*

13 *7JE, UK*

14 **Corresponding Authors: dy-369@163.com; zhongbj@tsinghua.edu.cn*
15

16 **Abstract:** A skeletal mechanism with 54 species and 269 reactions was developed to predict
17 pyrolysis and oxidation of *n*-dodecane as a diesel fuel surrogate involving both high-temperature
18 (high-T) and low-temperature (low-T) conditions. The skeletal mechanism was developed from a
19 semi-detailed mechanism developed at the University of Southern California (USC). Species and
20 reactions for high-T pyrolysis and oxidation of C₅-C₁₂ were reduced by using reaction flow analysis,
21 isomer lumping, and then merged into a skeletal C₀-C₄ core to form a high-T sub-mechanism.
22 Species and lumped semi-global reactions for low-T chemistry were then added to the high-T sub-
23 mechanism and a 54-species skeletal mechanism is obtained. The rate parameters of the low-T
24 reactions were tuned against a detailed mechanism by the Lawrence Livermore National Laboratory
25 (LLNL), as well as the Spray A flame experimental data, to improve the prediction of ignition delay
26 at low-T conditions, while the high-T chemistry remains unchanged. The skeletal mechanism was

1 validated for auto-ignition, perfect stirred reactors (PSR), flow reactors and laminar premixed
2 flames over a wide range of flame conditions. The skeletal mechanism was then employed to
3 simulate three-dimensional turbulent spray flames at compression ignition engine conditions and
4 validated against experimental data from the Engine Combustion Network (ECN).

5 **Keywords:** *n*-dodecane; surrogate; spray flames; ignition delay; skeletal mechanism

7 **1. Introduction**

8 Accurate prediction of diesel engine combustion requires realistic chemical kinetics. However, diesel
9 fuels consist of a large number of components and involve an even larger number of intermediate species
10 and reactions during the combustion process, and thus it is difficult to employ fully detailed mechanisms
11 in practical engine simulations as the computational cost would be intractable. As a simplification, surrogate
12 mixtures with one or a few components have been developed to mimic the physicochemical behaviors of
13 the real diesel fuels [1]. For instance, *n*-dodecane features a molecular size close to that of average diesel
14 components, and has been employed recently as a surrogate fuel to model diesel fuel combustion [2-12].
15 Detailed mechanisms for large hydrocarbons, e.g. *n*-dodecane, can consist of thousands of species and
16 reactions when low temperature (low-T) chemistry is involved [13-17]. For instance, the detailed
17 mechanism developed by Westbrook et al. [14] for *n*-alkanes from *n*-octane to *n*-hexadecane consists of
18 2775 species and 11,173 reactions. Such large mechanisms need to be reduced for computationally tractable
19 three-dimensional (3-D) simulations.

20 Mechanism reduction has been extensively studied in the last few decades and a number of reduction
21 methodologies have been brought up [18]. Reduced mechanisms can be obtained by removing unimportant
22 species and reactions from the detailed mechanisms and lumping of similar species and reactions, using
23 such methods as reaction flow analysis (RFA) [19], sensitivity analysis [20-22], principal component
24 analysis (PCA) [23], detailed reduction [24], directed relation graph (DRG) [25-28] and variants[29-31],
25 path flux analysis (PFA) [32] and isomer-lumping [33,34]. However, reduced mechanisms for practical
26 engine fuels with low-T chemistry obtained by such methods may still be large [2,35]. For example, a

1 skeletal mechanism for *n*-dodecane developed by Luo *et al.* [2] consists of 106 species and 420 reactions.
2 The mechanism was developed using DRG with expert knowledge (DRGX) [36] and DRGASA [30] based
3 on a detailed LLNL mechanism [13]. This mechanism and its variants [7, 8] have been coupled to different
4 turbulent combustion models in Spray A flame simulations [5,7-11] and compared with the experimental
5 data from the Engine Combustion Network (ECN). Narayanaswamy *et al.* [37] reduced the detailed LLNL
6 mechanism to a skeletal *n*-dodecane mechanism with 255 species and 2289 reactions through multi-stage
7 reduction strategy involving DRGEP [29] and chemical lumping [33]. The reduced mechanism was
8 implemented in a tabulated-chemistry combustion model by Ayyapureddi *et al.* [38] to simulate the Spray
9 A flames. D’Errico *et al.* [39] developed a reduced mechanism of *n*-dodecane using a reduction algorithm
10 combining sensitivity and flux analysis starting from a much smaller detailed mechanism that consists of
11 435 species and 13,532 reactions. This mechanism was also used to simulate the Spray A flames for
12 validation under engine-relevant conditions. These mechanisms are still relatively large and can be
13 expensive for engine simulations, especially when the mechanisms are coupled to advanced combustion
14 models [5, 7, 9,10], or high-fidelity LES studies [11]. More importantly, all of these reduced mechanisms
15 show increased errors in low ambient temperature conditions for Spray A flames, and thus a compact and
16 more accurate mechanism is needed for engine simulations.

17 In the present work, multiple reduction methods, including RFA and isomer-lumping, will be employed
18 to obtain a skeletal mechanism for *n*-dodecane based on a semi-detailed mechanism developed by You *et*
19 *al.* [40]. The semi-detailed mechanism consists of 171 species and 1306 reactions and has been widely
20 validated, which is a good candidate to start with. Semi-global reactions for low-T chemistry are merged to
21 the skeletal mechanism and subsequently optimized to better predict the negative temperature coefficient
22 (NTC) behavior. The final mechanism consists of 54 species and 269 reactions in the skeletal form and is
23 validated against detailed mechanisms and available experimental data. The mechanism is further tuned for
24 and applied in 3-D lifted diesel spray flame simulations.

1 **2. Mechanism development**

2 *2.1 Skeletal mechanism development*

3 For a range of conditions in ignition and combustion, the kinetics of fuel decomposition to smaller
4 fragments, which is described by C₅-C₁₂ sub-mechanism, is always fast and can be decoupled from the
5 oxidation kinetics of the H₂ and C₁-C₄ fragments [40]. In the development of the skeletal mechanism, the
6 C₅-C₁₂ sub-mechanism from a detailed mechanism is firstly simplified by eliminating unimportant species
7 and reactions, and isomer lumping is also employed. The simplified C₅-C₁₂ sub-mechanism is then merged
8 into the simplified H₂/CO/C₁-C₄ base mechanism. Lumped low-T reactions are then added and tuned,
9 resulting in an optimized skeletal mechanism with 54 species and 269 reactions. The reduction and tuning
10 procedure is further discussed in the following.

11 The detailed C₅-C₁₂ mechanism developed by You *et al.* [40] consists of 60 species and 522 reactions.
12 In the present study, reduction is based on data sampled from homogeneous, adiabatic, isobaric reactors.
13 The parameter range covers pressure of 1–80 bar, equivalence ratio of 0.5–2.0, and initial temperature of
14 800–1600 K. RFA is first employed to quantify the contribution of each reaction to the generation and
15 consumption of each species. Analysis is conducted from the reactant n-dodecane as the starting point.
16 Reaction pathways that are not important to the consumption of n-dodecane are removed along with the
17 species that the path leads to. Species associated with reaction pathways contributing e.g. 95% of the total
18 consumption of n-dodecane are retained. This reduction is performed successively until all the retaining
19 C₅-C₁₂ species find their main pathways to translate into C₁-C₄ fragments. By further applying radical
20 isomers equilibrium assumptions [34], isomers of n-dodecyl and other alkyls are lumped to three and one
21 representatives, respectively. The reduced C₅-C₁₂ sub-mechanism obtained after performing species and
22 reactions elimination and isomer lumping consists of 18 species and 60 reactions. It is worth noting that
23 fuel cracking process goes fast during the oxidation of n-dodecane and many intermediates are in steady
24 state, only the main reaction pathways that are important for the decomposition of n-dodecane to fragments
25 are needed to reproduce this process.

1 In order to obtain a compact C₀-C₄ sub-mechanism, the C₀-C₄ core in a reduced high-T mechanism for
2 *n*-dodecane oxidation in Vie *et al.* [41] is adopted. This core is reduced from USC-MECH II (111 species
3 and 784 reactions) [42] for high temperature oxidation (high-T). Two species, namely C₄H₇ and pC₄H₉, and
4 the involved reactions are added to accommodate the C₅-C₁₂ sub-mechanism and more accurately predict
5 the C₄ species concentrations in pyrolysis, which was not considered by Vie *et al.* [41], resulting in a new
6 C₀-C₄ core with 32 species and 191 reactions.

7 In the end, a semi-global scheme involving 4 species and 18 reactions for low-T chemistry of *n*-decane
8 developed by Bikas and Peters [43] is modified to be suitable for *n*-dodecane and appended to the skeletal
9 mechanism to capture the NTC behavior. Transition between low and high temperatures showing the
10 negative temperature dependence can be well reproduced by applying the Low-T sub-mechanism with
11 lumped reaction steps, which is rather efficient for practical engine simulations [43] and has been fully
12 investigated for *n*-heptane in [44, 45]. A 54-species skeletal mechanism (SK54a) is thereby obtained, which
13 can be found in the supplementary material.

14 2.2 Need for further tuning

15 The ignition delay time of SK54a is compared with experimental measurement by Vasu *et al.* [46] and
16 detailed mechanisms [13, 40] in Fig. 1. Simulations were performed under constant-pressure, adiabatic
17 conditions by the Senkin program package [47]. It is seen that the ignition delay time at low-T (~700 K) is
18 significantly over-predicted by the You *et al.* mechanism [40] and SK54a while predictions by the LLNL
19 [13] show improved agreement with experimental data.

20 3-D simulations of Spray A flames are further performed by a three-dimensional computational fluid
21 dynamics code CONVERGE with the flame condition listed in Table 1. The simulation setup has been
22 reported in our previous studies [9, 48] and will be briefly described here. The Reynolds-averaged Navier-
23 Stokes (RANS) method is used along with the Re-normalization Group (RNG) k- ϵ turbulence model [49].
24 The traditional Lagrangian-Eulerian method is employed, where the liquid phase is treated as Lagrangian
25 discrete parcels and the gas-phase is solved on a Eulerian mesh. Source terms are used to exchange mass,
26 momentum, and energy between the two-phases. The “blob” injection method [50] is used with the Kelvin-

1 Helmholtz and Rayleigh-Taylor (KH-RT) model [51, 52] for primary and droplet secondary breakup. A
2 dynamic drag model [53] was used to account for the droplet drag. Droplet evaporation is modeled using
3 the Frossling correlation [54]. The gas phase reaction is modeled by a delta function combustion model
4 [55]. The computational region is a cube with dimension of 108 mm in each direction. Adaptive mesh
5 refinement (AMR) is employed to refine the mesh. The minimum cell size is 0.25 mm with peak cell counts
6 in the order of one million. Based on a previous study, this resolution is deemed to be grid convergent for
7 RANS calculations [56]. Lift-off length (LOL) and ignition delay data measured under a wide range of
8 ambient conditions are used for validation of the developed n-dodecane skeletal mechanism. The conditions
9 involve ambient gas temperature of 800-1100 K, fuel injection pressure of 150 MPa, ambient oxygen
10 concentration of (X_{O_2}) 15%, ambient gas density of 22.8 Kg/m³. Ignition delay obtained using SK54a and
11 the previous 106-species mechanism (SK106) [2] are compared with the ECN data [57-59] in Fig. 2 for
12 different ambient temperatures. It is seen that the predictions at 1100 K and 1000 K are better for the SK54a
13 mechanism, showing an advantage of SK54a at high temperatures. At 800 K, SK54a however significantly
14 over-predicts the ignition delay (which is longer than 6 ms and not shown here), showing the need for
15 further tuning of the semi-global low-T reactions.

16 *2.3 Mechanism Tuning*

17 Mechanism tuning is conducted against the detailed LLNL mechanism in auto-ignition. Although there
18 are uncertainties in the detailed mechanism as well but at least with this approach the tuned mechanism will
19 match a published detailed one, wherever experimental data is rare and more scattered. Simulations are
20 performed under representative conditions of pressure $p = 20$ bar, initial temperature $T_0 = 800$ K and various
21 equivalence ratios as shown in Fig. 3. It is seen that the ignition delay time is over-predicted by SK54a at
22 lean conditions, while better agreement is observed for rich mixtures. As a result, ignition delay in Spray A
23 flames predicted using SK54a at $T = 800$ K is expected to be longer than that of SK106 which is reduced
24 from LLNL.

25 Sensitivity analysis is then performed using SK54a at $p = 20$ bar, $\phi = 0.5, 1.0, 2.0$, and $T_0 = 800$ K in
26 the NTC regime to identify the reactions important for low-T ignition. Sensitivity Coefficients (SC) are

1 defined as the resulting percentage change in the ignition delay time (τ) by doubling the rate constant of the
2 i th reaction, k_i [60].

$$3 \quad SC_i = \frac{\tau(2k_i) - \tau(k_i)}{\tau(k_i)}$$

4 Eight reactions with the largest SC are selected and summarized in Fig. 4. Reactions with positive SC
5 decelerate ignition and make ignition delays longer, and those with negative SC accelerate ignition and
6 result in shorter ignition delays. Sensitivity analysis is also performed under other engine relevant
7 conditions, for example $p = 50$ bar and 80 bar, which shows the same tendency as in $p = 20$ bar and is not
8 showing here.

9 It can be seen from Fig. 4 that ignition delay times under fuel rich conditions ($\phi = 2.0$) have larger
10 sensitivity to Low-T reactions (R3, R4, R5) than lean conditions ($\phi = 0.5$), which makes it impossible to
11 change ignition delay time at lean conditions without affecting rich conditions by tuning these reactions.
12 R1, R2, R6, R7 and R8 are involved in the high-T sub-mechanism and cannot be changed. Then we
13 observed that R1 is more sensitive for lean conditions, for the formation of vinoxy radical (CH_2CHO)
14 facilitates the chain branching of the overall reactivity and the facilitation is more inclined in lean conditions
15 than rich conditions [60]. Although R1 cannot be tuned for its significant influence to high temperature
16 oxidation, decomposition reaction of ketohydroperoxide $\text{OC}_{12}\text{H}_{23}\text{OOH}$ (R9) can be tuned to accelerate
17 CH_2CHO formation which leads to small species through one step reaction ($\text{OC}_{12}\text{H}_{23}\text{OOH} \rightarrow$
18 $\text{CH}_2\text{O} + 3\text{C}_2\text{H}_4 + \text{C}_2\text{H}_5 + \text{C}_2\text{H}_3\text{CHO} + \text{OH}$). As the products of R9 are appointed arbitrarily with reference to
19 Bikas and Peters [43], the $\text{OC}_{12}\text{H}_{23}\text{OOH}$ decomposition reaction is changed to the following formation:
20 $\text{OC}_{12}\text{H}_{23}\text{OOH} \rightarrow 3\text{C}_2\text{H}_4 + \text{C}_2\text{H}_5 + 2\text{CH}_2\text{CHO} + \text{OH}$, to produce vinoxy radicals (CH_2CHO) that can facilitate
21 the chain branching of low temperature reactivity. And the rate constant of this reaction is tuned down by
22 a factor of two to accommodate the new mechanism, resulting in SK54b mechanism, which can be found
23 in the supplementary material. Performance of SK54b can be seen in Fig. 3, which shows improvement
24 after the above tuning.

1 The tuned mechanism (SK54b) was then employed in 3-D Spray A flame simulations, and predictions
2 of ignition delay time are shown in Fig. 5. Over-prediction of ignition delay by ~25% is still observed at
3 the 800 K ambient temperature, which is also observed with SK106 in Fig.2. Since the first stage ignition
4 was found to occur in the lean mixtures and the main ignition in rich mixture [11], ignition delay of rich
5 cases (e.g., $\phi = 2.0$) at 800 K is further tuned down by ~25% using another round of reaction tuning based
6 on sensitivity analysis, resulting in a final mechanism (SK54).

7 The second round of sensitivity analysis is performed using SK54b to identify important low-T
8 reactions that are sensitive to ignition delay times at $p = 20$ bar, $\phi = 0.5, 1.0, 2.0$ and $T_0 = 800$ K, 900 K.
9 Selected reactions with high sensitivities are shown in Fig. 6. It can be seen that R2 mostly facilitates
10 ignition in all investigated cases with negative sensitivity coefficient. And R6 accelerates ignition of fuel
11 rich condition and decelerates ignition of fuel lean condition at $T_0 = 800$ K, which however has little
12 influence on ignition delay time at $T_0 = 900$ K. Therefore, tuning up rate constants of R2 and R6 will result
13 in a further decrease of ignition delay time at $\phi = 2.0, T_0 = 800$ K and ignition delay times at $T_0 = 900$ K and
14 $\phi = 0.5, T = 800$ K nearly unaffected. The tuning of these two reactions (R2 and R6) is conducted through
15 careful trial and error, leading to the final mechanism (SK54), which can be found in the supplementary
16 material. Performance of SK54 after this round of tuning can be found in Fig. 5. Improvement achieved can
17 be seen here that ignition delay time at $T_0 = 800$ K can be better reproduced by SK54.

18 **3. Mechanism Validation**

19 *3.1 Validation for elementary reactors and flames*

20 The mechanism is first validated for shock tube ignition delay data [46,61] at various pressures and
21 equivalence ratios. Fig. 7 shows comparison between experimental data and predicted ignition delay for
22 pressure of 20 bar and 50 bar, and various equivalence ratios. It is seen that the present mechanism agrees
23 well with the experimental data, and the overall discrepancy is smaller than that using the detailed LLNL
24 mechanism due to the tuning of low-T chemistry. It is therefore expected that the auto-ignition delay of

1 homogeneous mixtures can be more accurately captured for flames that fall within the above parameter
2 range, which is relevant to the Spray A flame conditions.

3 To further verify the performance of the mechanisms, especially the simplified C₅-C₁₂ fuel cracking
4 sub-mechanism, pyrolysis of *n*-dodecane in stirred reactors [62] and flow reactors [63] was simulated with
5 the present mechanism and compared with the experimental data by Herbinet *et al.* [64] and Dahm *et al.*
6 [65]. Fig. 8 shows the comparison of the *n*-dodecane conversion rate calculated with different mechanisms
7 [13, 40] in comparison with experimental data. Species profiles during the pyrolysis processes are further
8 compared in Figs. 9-10. It is seen that the reduced mechanism shows overall similar accuracy in the different
9 pyrolysis cases to that of the more detailed You *et al.* mechanism, for these two mechanisms share the high
10 temperature chemistry, while the LLNL mechanism shows overall larger discrepancies.

11 Figure 11 shows extended validations of the laminar flame speed of *n*-dodecane/air mixtures during
12 one-dimensional (1-D) flame simulations [66] evaluated using SK54 and You *et al.* mechanism [40], in
13 comparison with experimental data in literature [67-69]. Agreement between SK54 and You *et al.*
14 mechanism is of the order of the scatter of the experimental data at various conditions of pressures, inlet
15 temperatures and equivalence ratios. This is expected since the flame speed is primarily controlled by high
16 temperature chemistry, while You *et al.* mechanism and SK54 share the high temperature C₀-C₄ core, which
17 has been extensively validated against flame speed data, although some discrepancy exists for the
18 simplification. Also, the present skeletal mechanism is primarily developed for simulations of diesel engine
19 relevant conditions for which absolutely accurate prediction of laminar flame speed is not so necessary [2].

20 3.2 Validation for 3-D spray flame simulations

21 The newly developed skeletal mechanism SK54 is further applied to simulate spray flames. The
22 simulation results are compared with experimental data performed under compression-ignition (CI) engine
23 conditions from the ECN [57,70-72]. The experimental and computational configurations are shown in
24 Table 1. Details of the 3D simulations are described in section 2.2.

1 Figure 12 shows the comparison of experimental data and predicted ignition delay and LOL at fuel
2 injection pressure of 150 MPa, ambient oxygen concentration of (X_{O_2}) 15%, ambient gas density of 22.8
3 Kg/m^3 and various ambient temperatures. It is seen from Fig. 12a that the ignition delays are well
4 reproduced at high temperatures ($T > 1000$ K), indicating the high fidelity of the high-T sub-mechanism in
5 the skeletal mechanism. Some discrepancies are observed at low-T conditions wherein ignition delays are
6 under-predicted at ambient temperatures of 900 K and 850 K, and slightly over-predicted at 800 K. The
7 differences may be due to the simplification of the lumped low-T oxidation sub-mechanism. It is noted that
8 the prediction at 800 K is within the experimental uncertainty range. The LOL comparison is reported in
9 Fig. 12b. It is seen that the present mechanism accurately reproduces the experimental LOL data at both
10 low and high temperature conditions. Overall, the predictions of the present mechanism are reasonably
11 good compared to the measurements for the wide range of ambient temperatures investigated.

12 Figures 13 and 14 show the comparisons of ignition delay and LOL between the experimental data and
13 predictions at ambient gas temperature of 900 K, ambient gas density of 22.8 Kg/m^3 , different fuel injection
14 pressures and ambient oxygen concentrations. Overall, the simulations capture the experimental trends well.
15 As the present mechanism under-predicts ignition delay at the condition $T=900$ K, all cases in Fig. 13a
16 show about 10-20% shorter ignition delay time compared to the experimental data. Similar observation is
17 made in Fig. 14a also at different oxygen concentrations. However, the predictions of LOL presented in
18 Figs. 13b and 14b are in good agreement with experiments.

19 Comparisons of ignition delay and LOL at ambient gas temperature of 900 K, fuel injection pressure
20 of 150 MPa, ambient oxygen concentration of (X_{O_2}) 15% and different ambient densities are shown in Fig.
21 15. Again, the ignition delay is under-predicted with larger discrepancies at lower ambient densities.
22 Overall, the ignition delay and LOL at these ambient densities are reasonably reproduced by the skeletal
23 kinetic mechanism.

24 **4. Conclusions**

1 A compact skeletal mechanism with 54 species and 269 reactions was developed for *n*-dodecane using
2 a hybrid and decoupling approach. The high temperature C₅-C₁₂ mechanism module is firstly simplified
3 from the detailed mechanism of You *et al.* [40] by eliminating unimportant species and reactions and isomer
4 lumping, guided by RFA. The C₅-C₁₂ sub-mechanism is then merged to a reduced C₀-C₄ core based on the
5 USC-Mech II [42]. Semi-global reactions for NTC chemistry are added and tuned against the detailed
6 LLNL mechanism and experimental data to eventually obtain a 54-species skeletal mechanism.

7 The tuned mechanism was validated against experimental data for shock tubes, stirred reactors, flow
8 reactors, and laminar flame speed, and compared with other mechanisms. It is shown that the skeletal
9 mechanism performs well over a wide range of parameters in elementary flame experiments. Furthermore,
10 the skeletal mechanism was applied for 3-D Spray A flame simulations. Comparison with experimental
11 data obtained from the ECN shows that the ignition delay and flame LOL are reasonably well reproduced
12 by the tuned skeletal mechanism under various conditions, thus providing a valid option for efficient and
13 accurate multi-dimensional engine combustion simulations.

14 **5. Acknowledgements**

15 This work was supported by the National Science Foundation and the Department of Energy through
16 the NSF-DOE Partnership on Advanced Combustion Engines Program under Grant CBET-1258646. The
17 work at Tsinghua was supported by the Natural Science Foundation of China under Contracts No. 91441113
18 and No. 91441120.

19 The submitted manuscript has been created by UChicago Argonne, LLC, Operator of Argonne National
20 Laboratory (“Argonne”). Argonne, a U.S. Department of Energy Office of Science laboratory, is operated
21 under Contract No. DE-AC02-06CH11357. This research was funded by DOE’s Office of Vehicle
22 Technologies, Office of Energy Efficiency and Renewable Energy under Contract No. DE-AC02-
23 06CH11357. The authors wish to thank Gurpreet Singh and Leo Breton, program managers at DOE, for
24 their support.

1 We gratefully acknowledge the computing resources provided on "Fusion," a 320-node computing
2 cluster operated by the Laboratory Computing Resource Center at Argonne National Laboratory. We also
3 acknowledge Convergent Sciences Inc. for providing us with the CONVERGE software and related
4 support.

5 **6. Supplementary material**

6 Supplementary data including newly developed mechanisms (SK54a, SK54b, SK54) associated with
7 this article can be accessed online.

8 **7. References**

- 9 [1] Pitz WJ, Mueller CJ. Recent progress in the development of diesel surrogate fuels. *Prog Energy Combust Sci*
10 2011;37(3):330–50.
- 11 [2] Luo Z, Som S, Sarathy SM, Plomer M, Pitz WJ, Longman DE, et al. Development and validation of an *n*-
12 dodecane skeletal mechanism for spray combustion applications. *Combust Theory Model* 2014;18(2):187–203.
- 13 [3] Wang H, Ra Y, Jia M, Reitz RD. Development of a reduced *n*-dodecane-PAH mechanism and its application for
14 *n*-dodecane soot predictions. *Fuel* 2014;136(10):25–36.
- 15 [4] Gong C, Jangi M, Bai XS. Large eddy simulation of *n*-dodecane spray combustion in a high pressure combustion
16 vessel. *Appl Energy* 2014; 136:373–81.
- 17 [5] Bhattacharjee S, Haworth DC. Simulations of transient *n*-heptane and *n*-dodecane spray flames under engine-
18 relevant conditions using a transported PDF method. *Combust Flame* 2013;160(10):2083–102.
- 19 [6] Manin J, Bardi M, Pickett LM, Dahms RN, Oefelein JC. Microscopic investigation of the atomization and
20 mixing processes of diesel sprays injected into high pressure and temperature environments. *Fuel* 2014;134(9):531–
21 43.
- 22 [7] Pei Y, Hawkes ER, Kook S, Goldin GM, Lu T. Modeling *n*-dodecane spray and combustion with the transported
23 probability density function method. *Combust Flame* 2015;162(5):2006–19.
- 24 [8] Som S, Longman DE, Luo Z, Plomer M, Lu T. Three dimensional simulations of diesel sprays using *n*-dodecane
25 as a surrogate. In: Fall Technical Meeting of Eastern States Section of the Combustion Institute, USA; 2011.
- 26 [9] Kundu P, Pei Y, Wang M, Mandhapaty R, Som S. Evaluation of turbulence-chemistry interaction under diesel
27 engine conditions with multi-flamelet RIF model. *Atomization and Sprays* 2014;24(9):779–800.

- 1 [10] D'Errico G, Lucchini T, Contino F, Jangi M, Bai X-S. Comparison of well-mixed and multiple representative
2 interactive flamelet approaches for diesel spray combustion modelling. *Combust Theory Model* 2014;18(1):65–88.
- 3 [11] Pei Y, Kundu P, Goldin GM, Som S. Large eddy simulation of a reacting spray flame under diesel engine
4 conditions. *SAE Paper* 2015: 2015-01-1844.
- 5 [12] Pei Y, Davis MJ, Pickett LM, Som S. Engine Combustion Network (ECN): Global sensitivity analysis of Spray
6 A for different combustion vessels. *Combust Flame* 2015;162(6):2337–47.
- 7 [13] Sarathy SM, Westbrook CK, Mehl M, Pitz WJ, Togbe C, Dagaut P, et al. Comprehensive chemical kinetic
8 modeling of the oxidation of 2-methylalkanes from C₇ to C₂₀. *Combust Flame* 2011;158(12):2338–57.
- 9 [14] Westbrook CK, Pitz WJ, Herbinet O, Curran HJ, Silke EJ. A comprehensive detailed chemical kinetic reaction
10 mechanism for combustion of n-alkane hydrocarbons from n-octane to n-hexadecane. *Combust Flame*
11 2009;156(1):181–99.
- 12 [15] Mzéhmed A, Hadjali K, Dagaut P, Dayma G. Experimental and modeling study of the oxidation kinetics of *n*-
13 undecane and *n*-dodecane in a Jet-Stirred Reactor. *Energy Fuels* 2012; 26(7):4253-68.
- 14 [16] Biet J, Hakka MH, Warth V, Glaude P-A, Battin-Leclerc F. Experimental and modeling study of the low-
15 temperature oxidation of large alkanes. *Energy Fuels* 2008;22(4):2258–69.
- 16 [17] Battin-Leclerc F. Detailed chemical kinetic models for the low-temperature combustion of hydrocarbons with
17 application to gasoline and diesel fuel surrogates. *Prog Energy Combust Sci* 2008;34(4):440–98.
- 18 [18] Lu T, Law CK. Toward accommodating realistic fuel chemistry in large-scale computations. *Prog Energy*
19 *Combust Sci* 2009;35(2):192–215.
- 20 [19] Warnatz J, Maas U, Dibble RW. *Combustion: physical and chemical fundamentals, modeling and simulation,*
21 *experiments, pollutant formation.* Springer; 2006.
- 22 [20] Rabitz H, Kramer M, Dacol D. Sensitivity analysis in chemical kinetics. *Annu Rev Phys Chem*
23 1983;34(1):419–61.
- 24 [21] Tomlin AS, Pilling MJ, Turányi T, Merkin JH, Brindley J. Mechanism reduction for the oscillatory oxidation of
25 hydrogen: sensitivity and quasi-steady-state analyses. *Combust Flame* 1992;91(2):107–30.
- 26 [22] Turányi T. Sensitivity analysis of complex kinetic systems. Tools and applications. *J Math Chem*
27 1990;5(3):203–48.

- 1 [23] Vajda S, Valko P, Turanyi T. Principal component analysis of kinetic models. *Int J Chem Kinet* 1985;17(1):55–
2 81.
- 3 [24] Wang H, Frenklach M. Detailed reduction of reaction mechanisms for flame modeling. *Combust Flame*
4 1991;87(3):365–70.
- 5 [25] Lu T, Law CK. A directed relation graph method for mechanism reduction. *Proc Combust Inst*
6 2005;30(1):1333–41.
- 7 [26] Lu T, Law CK. Linear time reduction of large kinetic mechanisms with directed relation graph: *n*-Heptane and
8 *iso*-octane. *Combust Flame* 2006;144(1):24–36.
- 9 [27] Lu T, Law CK. On the applicability of directed relation graphs to the reduction of reaction mechanisms.
10 *Combust Flame* 2006;146(3):472–83.
- 11 [28] Luo Z, Lu T, Maciaszek MJ, Som S, Longman DE. A reduced mechanism for high-temperature oxidation of
12 biodiesel surrogates. *Energy Fuels* 2010;24(12):6283–93.
- 13 [29] Pepiot-Desjardins P, Pitsch H. An efficient error-propagation-based reduction method for large chemical kinetic
14 mechanisms. *Combust Flame* 2008;154(1):67–81.
- 15 [30] Zheng XL, Lu T, Law CK. Experimental counterflow ignition temperatures and reaction mechanisms of 1, 3-
16 butadiene. *Proc Combust Inst* 2007;31(1):367–75.
- 17 [31] Lu T, Law CK. Strategies for mechanism reduction for large hydrocarbons: *n*-heptane. *Combust Flame*
18 2008;154(1):153–63.
- 19 [32] Sun W, Chen Z, Gou X, Ju Y. A path flux analysis method for the reduction of detailed chemical kinetic
20 mechanisms. *Combust Flame* 2010;157(7):1298–307.
- 21 [33] Pepiot-Desjardins P, Pitsch H. An automatic chemical lumping method for the reduction of large chemical
22 kinetic mechanisms. *Combust Theory Model* 2008;12(6):1089–108.
- 23 [34] Zeppieri SP, Klotz SD, Dryer FL. Modeling concepts for larger carbon number alkanes: a partially reduced
24 skeletal mechanism for *n*-decane oxidation and pyrolysis. *Proc Combust Inst* 2000;28(2):1587–95.
- 25 [35] Saylam A, Ribaucour M, Pitz WJ, Minetti R. Reduction of large detailed chemical kinetic mechanisms for
26 autoignition using joint analyses of reaction rates and sensitivities. *Int J Chem Kinet* 2007;39(4):181–96.
- 27 [36] Lu T, Plomer M, Luo Z, Sarathy SM, Pitz WJ, Som S, et al. Directed relation graph with expert knowledge for
28 skeletal mechanism reduction. in: 7th US National Combustion Meeting, 2011.

- 1 [37] Narayanaswamy K, Pepiot P, Pitsch H. A chemical mechanism for low to high temperature oxidation of *n*-
2 dodecane as a component of transportation fuel surrogates. *Combust Flame* 2014;161(4):866–84.
- 3 [38] Ayyapureddi S, Egüz U, Bekdemir C, Somers LMT, De Goey LPH. Application of the FGM method to spray
4 conditions of the ECN database. in: *The 12th Triennial International Conference on Liquid Atomization and Spray*
5 *Systems*, Heidelberg, Germany: 2012.
- 6 [39] D’Errico G, Lucchini T, Stagni A, Frassoldati A, Faravelli T, Ranzi E. Reduced kinetic mechanisms for diesel
7 spray combustion simulations. *SAE Technical Paper* 2013.
- 8 [40] You X, Egolfopoulos FN, Wang H. Detailed and simplified kinetic models of *n*-dodecane oxidation: The role
9 of fuel cracking in aliphatic hydrocarbon combustion. *Proc Combust Inst* 2009;32(1):403–10.
- 10 [41] Vié A, Franzelli B, Gao Y, Lu T, Wang H, Ihme M. Analysis of segregation and bifurcation in turbulent spray
11 flames: A 3D counterflow configuration. *Proc Combust Inst* 2015;35(2):1675–83.
- 12 [42] Wang H, You X, Joshi AV, Davis SG, Laskin A, Egolfopoulos F, et al. USC MECH Version II High-temperature
13 combustion reaction model of H₂/CO/C₁-C₄ compounds, 2007. <http://ignis.usc.edu/USC_Mech_II.htm>.
- 14 [43] Bikas G, Peters N. Kinetic modelling of *n*-decane combustion and autoignition. *Combust Flame*
15 2001;126(1):1456–75.
- 16 [44] Peters N, Paczko G, Seiser R, Seshadri K. Temperature cross-over and non-thermal runaway at two-stage ignition
17 of *n*-heptane. *Combust Flame* 2002;128(1-2):38–59.
- 18 [45] Kazakov A, Chaos M, Zhao Z, Dryer FL. Computational singular perturbation analysis of two-stage ignition of
19 large hydrocarbons. *J Phys Chem A* 2006;110(21):7003–9.
- 20 [46] Vasu SS, Davidson DF, Hong Z, Vasudevan V, *n*-Dodecane oxidation at high-pressures: Measurements of
21 ignition delay times and OH concentration time-histories. *Proc Combust Inst* 2009;32(1):173–80.
- 22 [47] Lutz AE, Kee RJ, Miller JA. SENKIN: A FORTRAN program for predicting homogeneous gas phase chemical
23 kinetics with sensitivity analysis. Sandia National Laboratories: Livermore, CA, 1988; Sandia National Laboratories
24 Report SAND-87-8248.
- 25 [48] Pei Y, Mehl M, Liu W, Lu T, Pitz WJ, Som S. A multicomponent blend as a diesel fuel surrogate for
26 compression ignition engine applications. *ASME. J. Eng. Gas Turbines Power*. 2015;137(11):111502-111502-9.
- 27 [49] Han Z, Reitz RD. Turbulence modeling of internal combustion engines using RNG κ - ϵ models. *Combust Sci*
28 *Technol* 1995;106(4-6):267–95.

- 1 [50] Reitz RD, Diwakar R. Structure of high-pressure fuel sprays. SAE Technical Paper, 870598; 1987.
- 2 [51] Reitz RD. Modeling atomization processes in high-pressure vaporizing sprays. *Atomisation and Spray Technol*
3 1987;3:309–37.
- 4 [52] Patterson MA, Reitz RD. Modeling the effects of fuel spray characteristics on diesel engine combustion and
5 emission. In: International congress and exposition, Detroit, MI; 1998.
- 6 [53] Liu AB, Mather DK, Reitz RD. Modeling the effects of drop drag and breakup on fuel sprays. In: Proceedings
7 of the international SAE congress and exposition, Detroit, MI; 1993.
- 8 [54] Frossling N. Evaporation, heat transfer, and velocity distribution in two dimensional and rotationally symmetrical
9 laminar boundary-layer flow. N.A.C.A. 1956; 168: AD-B189
- 10 [55] Senecal PK, Pomraning E, Richards KJ, Briggs TE, Choi CY, McDavid RM, et al. Multi-dimensional modeling
11 of direct-injection diesel spray liquid length and flame lift-off length using CFD and parallel detailed chemistry. SAE
12 Technical Paper, 2003-01-1043; 2003.
- 13 [56] Senecal PK, Pomraning E, Richards KJ, Som S. Grid-convergent spray models for internal combustion engine
14 CFD simulations. *J Energy Res Technol* 2013;136(1):12204.
- 15 [57] Sahetchian K, Champoussin JC, Brun M, Levy N, Blin-Simiand N, Aligrot C, et al. Experimental study and
16 modeling of dodecane ignition in a Diesel engine. *Combust Flame* 1995;103(3):207–20.
- 17 [58] Pickett LM, Genzale CL, Bruneaux G, Malbec L-M, Hermant L, Christiansen CA, et al. Comparison of diesel
18 spray combustion in different high-temperature, high-pressure facilities. *SAE Int J Engines* 2010;3(2):156–81.
- 19 [59] Pickett L, Bruneaux G, Payri R. Engine combustion network. Sandia National Laboratories, Livermore, CA,
20 2014. <<http://www.ca.sandia.gov/ecn>>.
- 21 [60] Kumar K, Mittal G, Sung C-J, Law CK. An experimental investigation of ethylene/O₂/diluent mixtures:
22 Laminar flame speeds with preheat and ignition delays at high pressures. *Combust Flame* 2008;153(3):343–54.
- 23 [61] Pfahl U, Fieweger K, Adomeit G. Self-ignition of diesel-relevant hydrocarbon-air mixtures under engine
24 conditions. in: Symposium (International) on Combustion, 1996; Elsevier: pp 781-789.
- 25 [62] Glarborg P, Kee RJ, Grcar JF, Miller JA. PSE: A Fortran program for modeling well-stirred reactors; Sandia
26 National Laboratories: Livermore, CA, 1986; Sandia National Laboratories Report SAND-86-8209.

- 1 [63] Larson RS. PLUG: A Fortran program for the analysis of plug flow reactors with gas-phase and surface
2 chemistry. Sandia National Laboratories: Livermore, CA, 1986; Sandia National Laboratories Report SAND-96-
3 8211.
- 4 [64] Herbinet O, Marquaire P-M, Battin-Leclerc F, Fournet R. Thermal decomposition of *n*-dodecane: Experiments
5 and kinetic modeling. *J Anal Appl Pyrolysis* 2007;78(2):419–29.
- 6 [65] Dahm KD, Virk PS, Bounaceur R, Battin-Leclerc F, Marquaire PM, Fournet R, et al. Experimental and
7 modelling investigation of the thermal decomposition of *n*-dodecane. *J Anal Appl Pyrolysis* 2004;71(2):865–81.
- 8 [66] Kee RJ, Grcar JF; Smooke MD, Miller JA. A Fortran program for modeling steady laminar one-dimensional
9 premixed flames; Sandia National Laboratories: Livermore, CA, 1985; Sandia National Laboratories Report SAND-
10 85-8240.
- 11 [67] Ji C, Dames E, Wang YL, Wang H, Egolfopoulos FN. Propagation and extinction of premixed C₅–C₁₂ *n*-alkane
12 flames. *Combust Flame* 2010;157(2):277–87.
- 13 [68] Kumar K, Sung C-J. Laminar flame speeds and extinction limits of preheated *n*-decane/O₂/N₂ and *n*-
14 dodecane/O₂/N₂ mixtures. *Combust Flame* 2007;151(1):209–24.
- 15 [69] Hui X, Sung C-J. Laminar flame speeds of transportation-relevant hydrocarbons and jet fuels at elevated
16 temperatures and pressures. *Fuel* 2013;109:191–200.
- 17 [70] Pickett LM, Manin J, Genzale CL, Siebers DL, Musculus MP, Idicheria CA. Relationship between diesel fuel
18 spray vapor penetration/dispersion and local fuel mixture fraction. *SAE Int J Engines* 2011;4(1):764–99.
- 19 [71] Payri R, García-Oliver JM, Bardi M, Manin J. Fuel temperature influence on diesel sprays in inert and reacting
20 conditions. *Appl Therm Eng* 2012;35:185–95.
- 21 [72] Benajes J, Payri R, Bardi M, Martí-Aldaraví P. Experimental characterization of diesel ignition and lift-off
22 length using a single-hole ECN injector. *Appl Therm Eng* 2013;58(1):554–63.

23