A New South Polar Digital Terrain Model of Mars from the High Resolution Stereo Camera (HRSC) onboard the ESA Mars Express

Alfiah Rizky Diana Putri^{a,*}, Panagiotis Sidiropoulos^a, Jan-Peter Muller^a,
Sebastian H. G. Walter^b, Greg G. Michael^b

^a*Imaging Group, Mullard Space Science Laboratory, University College London, Holmbury
St. Mary, Dorking, Surrey, RH5 6NT, UK*

^b*Freie Universität Berlin, Department of Geosciences, Institute for Geological Sciences,
Planetary Sciences and Remote Sensing, Malteserstr. 74-100, 12249 Berlin, Germany*

Abstract

The first high-resolution Digital Terrain Model (DTM) of the entire South Pole of Mars has been produced. A modified version (Kim and Muller, 2009) of a NASA-VICAR-based pipeline developed by DLR (German Aerospace Centre) and JPL (Jet Propulsion Laboratory) has been employed with image matching based on the Gotcha (Gruen-Otto-Chau) algorithm (Shin and Muller, 2012) with a specialised setup for the polar region. DTM products have been produced with more than twice the resolution (50m/pixel) of the gridded Mars Orbiter Laser Altimeter (MOLA) 512 pixels/degree (112 m/pixel) over the South Polar Residual Cap (SPRC) and the Mars South Polar region (82° - 90°S) in MOLA and areoid reference. The accuracy of the HRSC orbital DTMs are compared against a MOLA reference with good results. HRSC orthorectified strip images from 12.5-50m have also been produced from the base DTMs and these have been processed into a 12.5m mosaic. HRSC strip products are currently being assessed as base images for automatic co-registration of thousands of high-resolution images, making them geometrically consistent with the surface conditions imaged by HRSC. In some cases, CTX DTMs have been automatically produced and co-registered to the HRSC image strips and these, in turn, are being employed for automated co-registration of higher-resolution images.

Keywords: Mars; SPRC; DTM; Mars South Pole; HRSC

*Corresponding author

Email addresses: alfiah.putri.15@ucl.ac.uk (Alfiah Rizky Diana Putri),
p.sidiropoulos@ucl.ac.uk (Panagiotis Sidiropoulos), j.muller@ucl.ac.uk (Jan-Peter Muller),
sebastian.walter@fu-berlin.de (Sebastian H. G. Walter),
gregory.michael@fu-berlin.de (Greg G. Michael)

1. Introduction

The Mars south polar region has generated research interest because of its rapidly changing appearance. Telescopic observations of Mars on Earth dates back to Huygens (1672) (see (Sheehan, 1996)), until the more recent James, et. al. James (1979) and from Hubble Space telescope (Cantor et al., 1998; James et al., 1979). Herschel Herschel (1784) (from (John Louis Emil, 2013), see also (Sheehan, 1996)) made notable early observations of the south polar cap. After the launch of the Viking and Mariner 9 spacecraft, the observations extended to quantifying the growth and recession of the ice caps (James, 1979; Piqueux et al., 2015; Calvin et al., 2017) and the dark ring shown around the South Pole (Geissler, 2005). With the launch of other spacecraft instruments, more information has been obtained about the SPRC (South Polar Residual Cap) (Thomas et al., 2000, 2005, 2009, 2016; Byrne and Ingersoll, 2003), finer features such as pits and troughs(Thomas et al., 2009) and araneiform (spider-like) terrain in the cryptic region (Piqueux et al., 2003; Kieffer, 2007) in MOC-NA images, down to meter-and sub-meter-scale pitting and cracking in the SPRC (Buhler et al., 2017) observed in HiRISE images.

A Digital Terrain Model (DTM) is a gridded elevation model of the terrain surface, where each point has a regular position in latitude and longitude as well as an associated elevation value. For this research, single-instrument and multi-instrument images are used, automatically co-registered to base images and orthorectified to the same base DTM to widen spatial and temporal coverage of high-resolution images over the South Pole in order to obtain the most accurate representation of the surface. The only currently available DTM for the South Pole is from the Mars Global Surveyor laser altimeter MOLA with a resolution of 463m/pixel on average globally and 512pixel/ degree over the polar region. MOLA produces pulse footprints diameter of 170m on the Martian surface (Smith et al., 2001a; Poole et al., 2014). Given the differences of resolution from MOLA to HiRISE, the finest resolution camera of Mars currently reaches 400 times the mean resolution of the MOLA DTM. The MOLA DTM is therefore not ideally suited for performing terrain correction of higher resolution images through orthorectification. Although 18m CTX DTMs are being produced(Tao and Muller, 2017), their coverage in polar regions is poor. Serendipitous HiRISE stereo-pairs for making DTMs are even sparser.

This research is motivated by the lack of such high-resolution DTMs and corresponding orthorectified images (ORIs), which hinders the scientific analysis of this area. Research on the South Pole so far has been done using images from MOC-NA, CTX, and HiRISE, but hardly at all with HRSC. Because of the lack of high-resolution DTMs, these high-resolution images have mostly been orthorectified using the MOLA DTM. Even the currently available HRSC images are ortho-rectified to a 5 km x 5 km MOLA DTM in most cases. For change detection, images are mostly co-registered to one another by hand (Buhler et al., 2017) so although the images may be properly co-registered between a subset of images, they are not all co-registered to a common baseline, which will present problems for further research.

Another motivation for the creation of high resolution DTMs, especially with regards to polar research, is to fill the gap in the MOLA data product between 87° - 90°S. This gap results from the non-polar orbit of MOLA's host spacecraft, the NASA Mars Global Surveyor. This gap is currently interpolated to produce a rasterised MOLA MEGDR South Polar DTM. The SPRC also lies within this gap, so it is critical for research over the SPRC to utilise a more complete DTM. One of the problems with the South Polar region is that the surface changes rapidly, resulting in problems in image matching. Another problem is the changeable weather conditions in certain seasons, which often reduce the input image quality due to dust storms, cloud and CO₂ frosts, resulting in poor visibility of the surface.

The objective of this paper is to describe the processes involved in the creation and application of high-resolution DTMs from HRSC over the South Polar region. These DTMs are subsequently shown to be useful as base DTMs for generating orthorectified HRSC images. The orthorectified images can be subsequently used to produce higher resolution co-registered DTMs from repeat-pass CTX images, which themselves can subsequently be used to co-register finer DTMs and ORIs from HiRISE stereo-pairs. This method increases the accuracy of the resulting CTX and HiRISE DTMs compared to using MOLA DTM as the base DTM using the USGS ISIS+SOCET stereo photogrametric methods (Kirk et al., 2008). Given the orthorectified HRSC images, other high-resolution images can be co-registered to the same global reference as well as orthorectified to a common DTM. This is not only helpful for research using single-instrument images, but also for research using multiple-instrument images. This technique has already been demonstrated in other areas of Mars where high-resolution DTMs derived from HRSC data have been produced (Sidiropoulos and Muller, 2018; Sidiropoulos et al., 2018).

This paper is structured as follows. In Section 2 the requirements for a Mars DTM are discussed as well as the selection criteria utilised for the data used to produce the high-resolution South Polar DTM. Section 3 discusses the DTM production methods for Mars, planetary, and earth data and the DTM processing chain used in this paper. Section 4 shows the results of our DTM production. Section 5 shows the validation and assessment using the MEGDR MOLA grid and nadir images orthorectified to MOLA DTM, how the DTM and ORI products can be used for estimating changes in the ice cap volume and observing surface changes, discussion of the produced DTMs as well as on-going coregistration work with the produced HRSC ORIs. The last section concludes and discusses future work.

2. Mars Images and Available Mars South Polar DTMs

Mars has been observed intensively, especially at visible wavelengths over the last 40 years. High-resolution observations of Mars (defined here as IFoV (Instantaneous Field of View) $\leq 100\text{m}$), were started by Viking Orbiter 1 and Viking Orbiter 2 with the Visual Imaging Subsystem (Soffen and Snyder, 1976), which were operational from 1976-1980. A global coverage of imagery finer than

90 1 km/pixel was obtained and the planet’s first global mosaic was produced by
 91 USGS at 231 m/pixel, comprising some 4600 images out of the total of 47,000
 92 images taken by both orbiters. Serendipitous stereo was acquired (Blasius et al.,
 93 1980) and automated stereo photogrammetric mapping has also been previously
 94 demonstrated (Thornhill et al., 1993).

95 The Mars Orbiter Camera-Narrow Angle (MOC-NA) on board the NASA
 96 Mars Global Surveyor (MGS) took pictures with resolutions ranging between
 97 1.5-12m/pixel. Operating between 1997-2006 (Mars Year (MY)23-MY28), it
 98 imaged 5.45% of the surface of Mars at 12 m/pixel, and began the acquisition
 99 of stereo coverage of Mars, resulting in a 0.32% stereo coverage (Malin et al.,
 100 2010).

101 Better surface coverage was obtained by the Thermal Emission Imaging Sys-
 102 tem (THEMIS-VIS) onboard the NASA Mars Odyssey at 18m/pixel (Chris-
 103 tensen et al., 2004). More than 82.01% of Mars surface has been covered by
 104 this instrument since 2001, and it is still in operation in early 2018. The High
 105 Resolution Stereo Camera (HRSC) onboard of the ESA Mars Express started
 106 its operation in 2003 (MY26) and is still working until the present-day (Gwin-
 107 ner et al., 2016). The NASA Mars Reconnaissance Orbiter was launched in 2006
 108 (MY28) with two visible instruments on board, the Context Camera (CTX)
 109 and the High Resolution Imaging Science Experiment (HiRISE). CTX has a
 110 nominal resolution of 6m/pixel and provides context to the instrument with the
 111 highest resolution so far, HiRISE with 0.25-0.5m/pixel. Both are still work-
 112 ing as this paper is written, covering more than 82% of Mars for CTX and
 113 2.40% of Mars for HiRISE, with 28.21% CTX DTM coverage(Tao et al., 2018)
 114 and 0.183% stereo HiRISE coverage ((Tao et al., 2018), also see (Becker et al.,
 115 2015; Mattson et al., 2011)). Recently the ExoMars Trace Gas Orbiter has been
 116 launched, with Colour and Stereo Surface Imaging System (CaSSIS) which is
 117 taking 2-4.5m/pixel stereo images of Mars since May 2018(Thomas et al., 2014).

118 2.1. MOLA

119 The Mars Orbital Laser Altimeter instrument is onboard the Mars Global
 120 Surveyor (MGS) launched on 7 November 1996 (MY23) and failed on 2 Novem-
 121 ber 2006. With an along-track sampling frequency of 10 Hz, this 1064nm laser
 122 altimeter, MOLA collected altimetry data of Mars with a pulse footprint diam-
 123 eter of 170m every 300m until 30 June 2001 (MY25) (Seidelmann et al., 2002).
 124 The MOLA Precision Experiment Data Records (PEDRs) are generated from
 125 raw altimetry profile data with precision orbit corrections applied.

126 From these "points", three sets of rasterised grids were produced by inter-
 127 polating the values obtained by MOLA, called the MOLA MEGDR (Mission
 128 Experiment Gridded Data Records). MOLA MEGDR consist of a global Mar-
 129 tian DTM, a South Polar DTM up to a latitude of -70°S and a North Polar
 130 DTM down to a latitude of 70°N. Global Martian DTMs are available with
 131 resolutions of 4,16,32, 64 and 128 pixels/ degree (which are about to 15, 3.7,
 132 1.85, 0.9, and 0.463 km/pixel respectively) for global data. Because of its global
 133 coverage, its consistency from crossover analysis and its accuracy, MOLA data

is treated as the principal areocentric reference body for Mars (Duxbury et al., 2002).

In regards to the South Polar DTMs, although the resolution of the global DTM is too coarse for our intended goal, because of its polar orbit, the MOLA point density is higher near the poles. A consequence of the near-polar orbit is that the resolution of the raster product can be increased up to 512 pixels/degree. However, this is at the expense of a large gap from $87^\circ - 90^\circ$ where no laser tracks are available. This is a problem for any research involving images for the production of higher resolution DTM over this area.

2.2. HRSC

The ESA-DLR High Resolution Stereo Camera (Neukum and Jaumann, 2004) has been active in orbit since January 2003 (MY27), and is still acquiring pictures of Mars whilst this paper is written. HRSC has reached global coverage of 97% for resolutions of 100m/pixel and higher and 70% at 10-20m/pixel (Gwinner et al., 2016). HRSC obtains images in resolution ranging between 200m/pixel at its coarsest up to 12.5m/pixel at its finest, although HRSC data at lower resolution are also acquired of limbs and the poles. This difference in resolution is due to its elliptical orbit due to the need to accommodate non planetary surface instruments as well as limited onboard storage for acquiring all views at full resolution for each data acquisition.

HRSC is a pushbroom camera with 9 different optical components at 9 different angles ranging up to $\pm 18.9^\circ$: one nadir channel, two stereo channel, four-band colour channels (Red, Green, Blue, and Near Infra-Red) and two photometry channels. Another (frame array) camera, the Super Resolution Camera (SRC) has 2-3 times the resolution of the nadir camera. With this setup, HRSC is currently the only stereo camera orbiting Mars (CaSSIS has yet to start obtaining stereo images at the time of writing). This uniqueness combined with its coverage ensures that close to 100% of the surface of Mars is available in stereo with temporal effects being almost negligible (≤ 120 s).

Although the coverage of HRSC images orthorectified to a MOLA DTM over the South Pole appears satisfactory, the polar gap and the large difference in resolution between HRSC images (up to 12.5m/pixel) and the MOLA MEGDR resolution of 112m/pixel results in poor orthorectification in this region. However, one of the major difficulties to ensure that HRSC strip products will lie on top of each other is that accurate spacecraft location and viewing orientation (which is referred as exterior orientation in this paper) is required for each strip, preferably from a bundle block adjustment, but in practice this is not feasible with the resources available. There were 14 DTMs over the area of interest available on the HRSC database at the ESA-PSA. However, their coverage is limited and their quality variable (see Figure 1). After searching through the metadata for HRSC south polar images for those acquired during a similar season (solar longitude, L_s), similar nadir resolution (12.5m, 25m, or 50m) strips, and examining each image for cloud or dust cloud coverage visually as well as by studying the MARCI image sequences kindly provided by Wendy Calvin (private communication, 2016) it was determined that there were sufficient numbers

Figure 1: Currently available DTMs over the SPRC and south polar region

179 of overlapping HRSC images which could be photogrammetrically processed to
 180 cover 100% over the area.

181 Based on the spatial coverage, it was decided that producing DTMs for the
 182 South Polar region was feasible at 50m, which is around twice the best MOLA
 183 DTM resolution. The HRSC DTMs also completely cover the gap below 87°
 184 S and allow the production of a set of base orthorectified images. The usual
 185 way to look for stereo pair images is to look for overlapping images with similar
 186 criteria such as incidence angle, solar azimuth, etc. (Becker et al., 2015), and
 187 not necessarily to give much attention to solar longitude values. These usual
 188 criteria to look for stereo pairs is not necessarily suited to the polar region,
 189 because of the existence of surface changes caused by seasonal processes causing
 190 different surface appearances for two stereo pairs. In this region, similarity
 191 in solar longitude increases the success rate for stereo matching. The changes
 192 signified by solar longitude values are obvious and cause a real problem for
 193 stereo matching if the features between two stereo images don't match because
 194 of the surface changes in the time interval between the dates they were captured.
 195 As all 9 HRSC CCD images are taken near-simultaneously (within 2 minutes),
 196 problems caused by these possible changes can be minimised. The last benefit
 197 of using HRSC and stereo imagery compared to using altimeters such as MOLA
 198 is that the CCD images are taken at almost exactly the same time and can be
 199 more readily used for matching. This brightness information can be used to

improve point sampling such as used in block adjustment to update exterior orientation.

A topographic datum of Mars has been defined based on a gravity model obtained by the Mars Global Surveyor (Lemoine et al., 2001). On Mars, there are several reference height frames for DTMs including: the MOLA Sphere defined by the MOLA mission as a sphere with 3396 km radius; an areoid surface, defined by the zero-elevation surface described previously. The Viking MDTM is available also on an older datum, but both MOLA MEGDR DTMs and HRSC DTMs are available in both reference systems. We also provide south polar DTMs in both reference systems.

3. Digital Terrain Model Production Pipeline

HRSC DTMs of the surface of Mars are produced exploiting its capabilities as a stereo photogrammetric camera system. The method used for producing HRSC DTMs by the DLR team is based on the recently published open-source NASA VICAR software, with specific proprietary executable software developed at DLR for producing DTMs from HRSC images (DLR-VICAR) (Scholten et al., 2005). Using MOLA data as control for HRSC exterior orientation, the DTMs produced can obtain vertical accuracies averaged at 12m (Gwinner et al., 2010, 2016). Other papers have also mentioned a method that has been previously discussed for HRSC by producing a DTM using the commercial SOCET-SET® which uses a generic camera model and combining this with ISIS (Integrated Software for Imagers and Spectrometers) (Kirk et al., 2002, 2008). Improvements were made based on the original VICAR-based DTM production pipeline such as Kim and Muller (Kim and Muller, 2009) who produced an in-house method by modifying the original DLR-VICAR based pipeline to use the Gotcha (Gruen-Otto-Chau) algorithm (Shin and Muller, 2012) for densifying the DTM up to 30m grid-spacing (Heipke et al., 2007). The NASA Ames Stereo pipeline can also be employed to generate HRSC DTMs if suitable bundle adjusted and updated SPICE kernels are available (R. Beyer, private communication, 2018).

The method that was employed to produce the HRSC DTMs is described in Kim and Muller (2009). It is based on a DLR-VICAR pipeline which was briefly discussed as one of the DTM Production Methods in the previous paragraph. This is part of a complex PERL script to allow fully automated DTM processing (Stephan van Gasselt, private communication, 2005). Inputs for this pipeline are three Level 2 HRSC images, which means images that have been radiometrically calibrated to radiance or reflectance but are still in the original instrument-based geometry. These three level 2 HRSC images are stereo triplet views from nadir, stereo angle 1, and stereo angle 2 ($\pm 18.9^\circ$). Other information needed to produce HRSC DTMs with this method are: a base DTM, which in this work is the Mars South Polar MOLA MEGDR, updated exterior orientation files (A. Dumke, private communication, 2016) obtained by bundle adjusting multiple channels from each orbit with MOLA data (Bostelmann and Heipke, 2016; Heipke et al., 2007), and geometric calibration data.

Initially, images are orthorectified from Level 2 HRSC images (nadir, stereo angle 1, and stereo angle 2) using the DLR-VICAR orthorectification programme (Gwinner et al., 2009) and a gridded version of MOLA heights (see next paragraph). Area-based matching is then performed on image patches from image pairs extracted from the three stereo images. Instead of using the DLR-VICAR programme to match conjugate points to nadir iteratively, each bilinearly sampled image is matched from the lowest resolution up to the highest using discrete pixel position approximation by a cross-correlation algorithm. Area based matching in this modification is performed using a region-growing variant of the Gruen Adaptive Least Square Correlation (ALSC) matcher within the Gotcha (Gruen-Otto-Chau) algorithm (Gruen, 1985; Otto and Chau, 1989; Shin and Muller, 2012). For each match, a variance and co-variance matrix is defined and a maximum eigenvalue is calculated as a precision value. Iteration is performed to calculate the lowest possible maximum eigenvalue based on different matching window sizes, from larger to smaller. In this paper we use a threshold of 5 iterations to find the lowest possible maximum eigenvalue. Maximum grey level differences are also calculated as metrics (Kim et al., 2013). Pairwise matching results are merged and 3D points are computed using a least squares forward intersection. Blunders are reduced by assigning a threshold for intersection accuracy. More accurate subpixel retrievals are obtained by interpolation, and a final DTM is produced by kriging grid point interpolation. The overall production system is shown in Figure 2.

The processing is done in sections by dividing orbital strips (which can be up to 100,000 lines in length) into segments, each varying from 5,000-10,000 lines, and then merging them together afterwards using the DLR mosaicking software (Scholten et al., 2005) without grey-level adjustment and without elimination of duplicated values. Disparity between the images is set between the limits of ± 5 pixels, and for Gotcha the minimum correlation is set to 0.6 and maximum eigenvalue is set to 600. Artefacts caused by stereo matching over cliff edges (signified by very high difference to MOLA values compared to other data) are cropped afterwards and not used for calculation of the end products. To reduce the disparity range, MOLA DTMs are employed to orthorectify the imagery. Usually this is performed using a 5km/pixel DTM. Instead here the 512 pixels/degree (112m/pixel) MOLA DTM is employed.

DTMs are produced with a grid spacing of 50 m/pixel from the original image resolutions, which range between 12.5-50m/pixel. Orthorectified images are produced by orthorectifying Level 2 images used as inputs to the HRSC DTM produced at their original resolution of either 12.5, 25, or 50m/pixel using a polar stereographic projection with the same projection parameters of 90°S and 0°E as centres of projection. This global projection is chosen instead of maximising matching by projecting images into their central longitude and latitude to obtain a similar reference so that we can produce a global map and mosaics from the product. A significant improvement was obtained by exploiting the Mars MEGDR (available from 87°S down to approximately 75°S) in polar stereographic projection at the highest resolution (512 pixels/ degree) as the base DTM. This raster image has the advantage of obtaining higher accuracy

Figure 2: Schematic of modified DTM production algorithm based on DLR-VICAR (Kim and Muller, 2009)

in the polar region, instead of using a global DTM in Plate Carée cylindrical projection, where MOLA counts per pixel are high for the higher latitudes, both resulting in less accuracy and unavailability to process images with poles. The areoid version of products are also produced by differencing DTM products with the Mars geopotential surface. Striping effects sometimes occur in areoid products because of the limited values of areoid surface stretched to 50m/pixel and integration of values to 16bit integer. These have been fixed using the floating-points method discussed in Section 4.

4. Results

In this paper, we analyse the new high-resolution DTMs generated from HRSC images over the South Pole. We selected 33 polar orbits based on their MY and their coverage (see coverage map in Figure 1). Emphasis is given to images from Mars Year 27 (23 strips, 69.7%) with 8 other strips from MY28 (24.24%) and 2 strips from MY29 to fill gaps. The detailed data acquisition information is presented in Table 1.

The 33 DTMs cover almost the whole of the area between latitude of 82°S – 90°S. There was a bundle adjustment failure for orbit H2153_0000, which had no other HRSC images overlapping this area. A DTM has been produced over this area, but we expect the accuracy to be lower because of the use of the predicted exterior orientations used to produce this DTM instead of the bundle-adjusted exterior orientation data. The elevations of the DTMs produced in this paper are given with height referenced to the MOLA sphere (DT extension in HRSC definitions) as well as areoid products (DA in HRSC definitions) which have been produced by subtracting the height from the difference from the South Polar MOLA MEGDR radius and MOLA MEGDR areoid heights. The small range of the areoid heights resulting in stripe-like patterns when the resulting areoid products was interpolated to integer. This was solved by using floating-point values for intermediate steps and adding a filter for 87°S-90°S where the striping result could still be observed. The coverage of the resultant DTMs products is illustrated in Figure 3. This DTM could then be mosaiced with the existing MOLA 112m/pixel DTMs to fill any remaining few grid-points where there were gaps. The resolution of the MOLA DTM in the area without HRSC DTMs data gets upsampled to HRSC DTMs resolution (50m/pixel)

5. Discussion

5.1. DTM and Vertical Accuracy Analysis

An accuracy assessment was performed by comparing the HSRC height results for each HRSC image strip against the equivalent MOLA height by down-sampling the DTM products (50 m/pixel) to the MOLA South Polar MEGDR resolution and subtracting the values from the MOLA MEGDR. From the relative accuracy map, we can see that differences with MOLA DTM are generally positive in the north-west direction and negative in the south-east direction.

Table 1: Information for each HRSC DTM strip produced

Product ID	Nadir image Scale (m/pixel)	Solar Longitude	Mars Year	Date
H2153.0000	50	289.93	27	17-09-2005
H2155.0000	50	290.27	27	18-09-2005
H2160.0000	25	291.13	27	19-09-2005
H2162.0000	25	291.47	27	20-09-2005
H2163.0000	25	291.64	27	20-09-2005
H2165.0000	25	291.98	27	20-09-2005
H2167.0000	25	292.32	27	21-09-2005
H2179.0000	25	294.36	27	24-09-2005
H2181.0000	25	294.70	27	25-09-2005
H2183.0000	25	295.04	27	25-09-2005
H2189.0000	25	296.05	27	27-09-2005
H2197.0000	25	297.40	27	29-09-2005
H2286.0000	25	312.13	27	24-10-2005
H2287.0000	25	312.30	27	25-10-2005
H2288.0000	12.5	312.46	27	25-10-2005
H2318.0000	12.5	317.29	27	02-11-2005
H2340.0000	12.5	320.79	27	08-11-2005
H2348.0000	12.5	322.06	27	11-11-2005
H2362.0000	12.5	324.26	27	15-11-2005
H2372.0000	12.5	325.82	27	17-11-2005
H2428.0000	12.5	334.45	27	03-12-2005
H2454.0000	12.5	338.37	27	10-12-2005
H2498.0000	12.5	344.90	27	23-12-2005
H4144.0000	50	208.88	28	29-03-2007
H4162.0000	50	211.95	28	03-04-2007
H4369.0000	12.5	248.22	28	31-05-2007
H4574.0000	12.5	284.34	28	27-07-2007
H4685.0000	12.5	303.18	28	27-08-2007
H4696.0000	12.5	305.00	28	30-08-2007
H4837.0000	25	327.62	28	09-10-2007
H4917.0009	25	339.80	28	31-10-2007
H6794.0000	12.5	249.36	29	18-04-2009
H6908.0000	25	270.10	29	21-05-2009

Figure 3: HRSC DTMs produced for the SPRC. Height information is measured from MOLA DTM sphere.

Figure 4: Height accuracy assessment for HRSC DTM strips to MOLA MEGDR. The figure shows differences to MOLA MEGDR in metres.

Figure 5: Height accuracy assessment for HRSC DTM strips to MOLA PEDR points (the example is H2348.0000 (11-11-2005, MY27, L_s 322.06)). The figure shows differences to the MOLA PEDR points in metres.

330 An illustration of this difference can be seen in Figure 4) and the statistics for
 331 each strip is presented in Table 2, showing the mean of the differences between
 332 HRSC points to MOLA points, with σ as the standard deviation of the differ-
 333 ences, RMSE as the root mean square error of the differences, $|\text{Mean}|$ as the
 334 overall mean of the absolute values of the differences, max and min as maximum
 335 and minimum height difference excluding outliers with range as the difference
 336 between the two values, Med as the median value, and counts as the number
 337 of MOLA points for each strip. Using this method the overall mean differ-
 338 ence (bias) with MOLA MEGDR is 1.08m with a root mean square error of
 339 7.29m and a mean absolute difference of 3.21m. This value is comparable with
 340 the results calculated for the currently available HRSC DTMs overlapping the
 341 MOLA South Polar MEGDR. The new DTMs were compared with the currently
 342 available DTMs (H2364_0000, H4526_0000, H4547_0000). Three of these HRSC
 343 products are all located around a similar area (86°S–88.5°S, 291°W–24°E) with
 344 a mean difference to MOLA MEGDR more than 12m and a standard devia-
 345 tion higher than 40m. These DTMs are complemented by DTMs overlapping
 346 the same area produced in this paper (H2181_0000, H2189_0000, H4837_0000,
 347 H6908_0000), with a mean difference between 0.29m–4.37m and a standard de-
 348 viation of 3.07m–10.66m. The mean differences between overlapping DTMs are
 349 less than the RMS errors in the data products (Table 2), which indicates that
 350 there are no vertical changes detectable in the HRSC DTMs over this region
 351 between MY 27 and MY 29.

352 The method used in this paper also worked well in both rugged areas (sig-
 353 nified by high elevation deviations) and smoother plains (vice versa), and there
 354 are no significant differences between these values for the three most rugged
 355 strips (H2160_0000, H2318_0000, and H4369_0000) and the three smoothest
 356 strips (H2155_0000, H2340_0000, H6908_0000). A consistent grid spacing of
 357 50m/ pixel for all DTMs is used to prevent sacrificing information for higher
 358 resolution input images and for producing geospatial analysis product (mosaic).
 359 From the vertical accuracy assessment, we can also assert that producing 50
 360 m/pixel DTMs from 50 m/pixel nadir images is acceptable for the south polar
 361 region because of the resolution of the base DTM (112 m/pixel) which is about
 362 twice the resolution of the images and the sub-pixel Gotcha image matcher used
 363 to produce sub-pixel accuracy. The actual finest grid-spacing depends on many
 364 different factors, including the texture and the Signal to Noise Ratio. These
 365 fine details are not considered in this paper. Height assessment with MOLA
 366 MEGDR also gives satisfactory results for orbit H2153_0000 compared to other
 367 strips. Based on the resulting DTMs, the mean differences with MOLA MEGDR
 368 for each nadir resolution group are 0.89m (12.5 m/pixel), 1.98m (25 m/pixel),
 369 and -1.41m (50 m/pixel).

370 Analysis has also been performed for each strip using the original MOLA
 371 PEDR values (Smith et al., 1999). The MOLA PEDR points are extracted for
 372 each orbit and DTMs are discretely sampled to compare the height to MOLA
 373 PEDR points. Comparison has been done for HRSC DTM heights and MOLA
 374 heights. A mean difference is calculated for each orbit by subtracting sampled
 375 points from the MOLA PEDR points. Validation is done to assess DTM quality

Table 2: Vertical Difference Assessment of Processed Products to MOLA MEGDRs and PE-DRs

Product ID	Assessment to MOLA MEGDR								Assessment to MOLA PEDR Points				
	Mean	σ	RMSE	Mean	Max	Min	Range	Med	Mean	σ	RMSE	Mean	Counts
H2153_0000	-1.34	5.68	5.83	2.88	125	-360	485	-1	0.44	23.44	23.45	5.04	3610642
H2155_0000	-0.32	4.76	4.77	0.83	138	-364	502	0	1.01	15.22	15.26	5.22	919180
H2160_0000	4.81	3.84	6.18	5.11	102	-567	669	5	-5.46	17.44	18.27	6.46	1680046
H2162_0000	-0.32	4.76	4.77	0.83	138	-364	502	0	-2.50	11.02	11.03	2.91	2833013
H2163_0000	3.09	2.55	3.99	3.36	40	-209	249	3	-3.29	15.30	15.65	4.92	1983991
H2165_0000	0.84	0.35	0.91	0.84	188	-91	279	-2	6.26	31.00	31.62	8.81	1937000
H2167_0000	3.94	13.18	13.7	5.22	198	-232	430	0	-4.84	30.03	30.42	7.81	2849683
H2179_0000	-1.80	13.02	13.18	3.36	164	-1293	1457	0	0.74	20.66	20.67	4.98	4312909
H2181_0000	2.02	10.66	10.83	2.15	205	-281	486	0	-5.17	21.31	21.93	6.43	4230094
H2183_0000	-4.15	10.03	10.71	4.22	207	-448	655	-4	4.04	12.75	13.37	5.41	2317075
H2189_0000	1.72	7.09	7.27	2.45	213	-179	392	1	-3.73	25.34	25.61	5.86	6093104
H2197_0000	-1.6	3.93	4.19	2.87	43	-233	276	-1	1.08	14.14	14.18	4.20	759573
H2286_0000	7.49	32.54	33.88	13.04	169	-239	408	0	-0.72	10.75	10.77	3.04	701211
H2287_0000	-23.1	57.03	61.41	25.42	379	-525	904	-2	0.38	25.04	25.04	4.82	597345
H2288_0000	0.76	4.41	4.52	2.74	75	-616	691	1	-2.58	35.24	35.33	7.33	1029365
H2318_0000	-3.05	3.68	4.75	3.46	46	-133	179	-3	2.10	18.43	18.55	5.48	257335
H2340_0000	0.19	3.00	2.96	2.19	43	-49	92	0	0.41	24.93	24.93	4.86	428181
H2348_0000	-0.36	3.26	3.28	1.07	134	-130	264	0	0.04	13.52	13.52	3.07	679729
H2362_0000	-3.05	3.68	4.75	3.46	46	-133	179	3	-2.43	20.98	21.12	5.80	2167703
H2372_0000	3.78	24.42	24.78	4.93	270	-159	429	1	-3.55	33.89	34.08	7.33	913428
H2428_0000	2.14	7.37	7.69	3.81	24	-106	130	3	-2.45	20.01	20.16	5.61	405097
H2454_0000	0.00	1.63	1.63	1.14	36	-73	109	0	-0.91	15.50	15.52	2.58	72980
H2498_0000	0.03	2.70	2.64	0.33	124	-1365	1489	0	-2.18	25.77	25.86	4.25	654458
H4144_0000	-1.30	7.37	7.49	3.98	268	-930	1198	-1	0.82	14.74	14.76	5.24	2635904
H4162_0000	-2.43	6.26	6.78	3.19	77	-551	628	-2	1.99	14.90	15.04	4.72	3996424
H4369_0000	1.3	4.06	4.25	2.44	109	-75	184	1	-2.48	20.39	20.54	4.33	371309
H4574_0000	3.72	10.17	10.84	5.54	57	-175	232	4	-3.65	15.49	15.91	6.85	261659
H4685_0000	-0.42	10.89	10.89	2.78	251	-198	449	-1	-0.60	20.75	20.76	4.50	1137623
H4696_0000	0.53	6.52	6.53	2.32	209	-1431	1640	0	-2.34	22.65	22.78	4.74	1429417
H4837_0000	0.29	4.64	4.00	1.39	281	-356	637	0	-2.19	25.75	25.84	7.12	4022651
H4917_0009	5.90	7.66	9.61	7.27	154	-314	468	6	-7.72	18.34	19.00	10.25	6477732
H6794_0000	3.51	6.15	7.04	3.90	167	-270	437	3	-4.53	18.00	18.57	5.77	2183158
H6908_0000	4.37	3.07	5.34	4.54	51	-218	269	4	-5.27	21.87	22.50	6.36	3236488

t Difference is calculated in metres. Counts are number of MOLA points in an individual strip

Figure 6: Annual stability testing, analysed by differencing heights between MY27-MY28, not including H2287_0000, both tails not shown for clarity. The graph is presented in logarithmic scale because the percentage of height difference of $\leq 1\text{m}$ is far higher compared to other height differences

376 with MOLA PEDR results and results in a mean difference (bias) of 0.04 m
 377 difference and 13.53 m of root mean square error for DTMs with a resolution of
 378 50m/pixel. An example of the height difference map for these PEDR point is
 379 shown in Figure 5.

380 From this assessment against PEDR points by separate strips shown in Table
 381 2, we obtain a mean differences of -2.20m to PEDR points with -9.48m root
 382 mean square error and 6.12m mean absolute difference. This mean difference is
 383 larger than the differences assessed using the MOLA MEGDR because of the
 384 likelihood that in the DTM production we use MOLA MEGDR heights which
 385 are gridded values of PEDR data as the base DTM.

386 5.2. Annual and Seasonal Stability

387 Annual and seasonal stability assessments are necessary to be performed for
 388 the South Polar images considering the annual and seasonal changes caused by
 389 the recession and growth of the seasonal CO₂ ice cap (Smith et al., 2001b). To
 390 look at annual stability, we compare DTMs produced from overlapping strips
 391 from different years. As shown in Figure 6 is a histogram of height differences
 392 for DTM heights taken in PEDR point locations between MY27 and MY28 with
 393 both tails cropped and focused within -10m until 10m because the percentage of
 394 values outside those numbers is very low. In this calculation we do not include
 395 H2287_0000 as statistically based on 2, its difference with MOLA MEGDR and
 396 PEDR is higher than all other strips. We can see from the graph that the heights
 397 are similar between each year, with a height difference of $\leq 1\text{m}$ for 61.64% of the

398 overlapping points (2.18×10^7 points from the total of 3.54×10^7 points). Calculating the statistics without extreme values, we obtain a mean of differences of
 399 2.3525m, and a root mean square difference of 48.3844m. The mean differences
 400 between overlapping DTMs are generally in agreement with the RMS errors in
 401 the data products (Table 2), which indicates that the vertical changes differ-
 402 ences in the HRSC DTMs over this region between MY 27 and MY 28 is not an
 403 indication of annual changes, but an indication of bundle adjustment quality of
 404 individual HRSC image strips, as based on Smith, et. al. Smith et al. (2001b),
 405 the maximum yearly height differences over the south poles between two MYs
 406 are 1.5-2m.

408 Although seasonal changes are visible in the orthorectified images (such
 409 as shown in Figure 7 between H2183_0000 and H2372_0000 (top); as well as
 410 H4162_0000 and H4917_0009 (bottom)), this is unimportant for the DTM be-
 411 cause the thickness of the seasonal ice cap is less than 1 m (Phillips, 2006)),
 412 which is smaller than the vertical precision of the HRSC DTMs. This can be
 413 shown by comparing different DTMs in overlapping areas with DTMs produced
 414 from different years (annual stability) and produced from the same year but
 415 with different solar longitudes (seasonal stability).

416 We can see small differences in the height comparison between DTMs made
 417 from images taken in different seasons for both MY27 and MY28 (see 8). We
 418 check for seasonal stability by differencing image strips which have a distinctive
 419 gap between seasons to increase the extremity of surface differences. We use
 420 13 strips for MY27 (8 strips from spring/ earlier sets of L_s 5 from the end of
 421 summer/ later sets of L_s and for MY28, we used 4 image strips (2 strips from the
 422 start of spring / earlier sets of L_s and 2 strips from the end of summer/ autumn,
 423 the later sets of L_s . We did not include the strips with in-between- L_s value as we
 424 want to have the most surface changes from the HRSC image strips we used. We
 425 did not calculate seasonal stability for MY29 as there are only two image strips
 426 available in this research. The graph is presented in logarithmic scale because
 427 the percentage of height difference of $\leq 1m$ is far higher compared to other height
 428 differences. From the graph, we could see that the majority of the discrete height
 429 points have a difference of $\leq 1m$ (80.10% for MY27, corresponding to 1.23×10^7
 430 points from the total of 1.53×10^7 and 50.10% for MY28 0.85×10^6 from the total
 431 of 1.68×10^6 . Calculating the statistics, for MY27 we obtain a mean of difference
 432 of -0.412m, a root mean square difference of 7.988m, and standard deviation of
 433 7.978m. The mean differences between overlapping DTMs are generally agreeable
 434 with the RMS errors in the data products (Table 2). In the comparison of two
 435 DTMs from different seasons of MY28, a larger mean offset and root mean
 436 square error are observed compared to the values from MY27. However, this
 437 is likely due to changing surface properties (e.g. a dust storm (Piqueux et al.,
 438 2008)) that affect the feature-matching algorithm rather than an actual change
 439 in elevation. We obtain a 8.506m mean difference (without extremes) with a root
 440 mean square error of 221.730m and standard deviation of 221.561m. Further
 441 research on the seasonal differences effect on DTM production needs to be done
 442 with higher resolution DTMs such as CTX or HiRISE, but for these HRSC
 443 DTMs, the results are likely to be similar between different seasons.

Figure 7: Seasonal stability testing by comparing height difference between seasons (top) (MY27) H2181_0000 (17-09-2005 L_s 294.6) bottom H2372_0000 (17-11-2005, L_s 325.7) (bottom) (MY28) H4162_0000 (03-04-2007, L_s 211.9), bottom: H4917_0009, (31-10-2007, L_s 339.7)

Figure 8: Seasonal stability testing by comparing height difference between seasons (biggest range of available L_s) for MY27(19 strips) and MY28(4 strips), not including H2287.0000, both tail not shown for clarity.

Further calculations on stability between DTMs can be obtained by making histograms of the height differences from grid points in overlapping DTM strips. From the histogram in Figure 9, we can see that the difference peaks at -1 m then followed by 0 m, which is in agreement with the results obtained by comparing single profiles, concluding that the DTM result is stable between different strips. Based on research on height changes obtained from MOLA measurement (Smith et al., 2001b), the interannual and intraannual changes on the south poles are shown to be less than 0.4m. Based on the annual and seasonal stability test calculated in this research, most errors in HRSC DTM (reflected in the height differences) arise from (a) lower resolution in the HRSC nadir images; (b) quality of the exterior orientations which depend greatly on dense feature points, which are more difficult to obtain over snow and ice; (c) the lack of any bundle block adjustment such as the ones performed by Gwinner et al. Gwinner et al. (2016). Nevertheless, even given these limitations, the bias between overlapping strips for different MYs and L_s is very small (see 6 and 8), peaks at -1m, as shown in 9

This planimetric correlation can also be seen by comparing the side-by-side appearances of orthorectified images around their edges. In the example, we can see that improved pointing from the exterior orientation worked well, shown by the smooth changes over the edges between different strips as pictured in Figure 10. Although the strips differ in appearance because of the differences in solar longitude value, the features are well aligned visually. If the difference in solar

Figure 9: Differences between all overlapping strips in meters

longitude between strips is not much (adjacent strips are in the same season based on solar longitude), the strips can be seamlessly mosaicked to produce larger ORI products.

5.3. Production of a Mosaic from Orthorectified Orbital strip Products

Martian atmospheric variability makes it difficult to construct a seamless image mosaic. The presence of dust or aerosols in the camera's line of sight degrades the image quality, the fraction of light arriving directly from the surface diminishing with respect to that scattered by atmospheric dust particles. The consequence of a decrease in image contrast together with an increase in average brightness, leads to a 'patchwork' appearance when many images are compiled into a mosaic. It has proven difficult to make a systematic atmospheric correction, so we take an alternative approach: equalising the images to an external brightness reference (Michael et al., 2016). This enables retention of high resolution detail in the images while bringing the local absolute brightness of the images into mutual consistency. For the polar mosaic, we used a high altitude HRSC observation as the brightness reference: image HE150_0000 (25-02-2015, MY33, L_s 297.4), covering the whole of the cap with a swath width, in its vicinity, of around 2200 km and a surface resolution of about 440 m/pixel.

The changing ice cover at the polar cap introduces an additional complication to the mosaicking process. Ideally, we would choose a set of images taken over a short period, or from different years at similar L_s . Our selected images, chosen for their quality, however, cover a range of 120° of L_s , equivalent to a third of a year. Consequently, we see some image boundaries where the ice coverage has shifted. Likewise, there are areas where the image is not entirely consistent with the brightness reference image (taken about 1/12 Martian year after southern midsummer), causing mild brightness artefacts at the edge of the cap.

The images from the 33 selected observations were initially sorted in order of ground sampling distance, compiling the lowest surface resolution image into the

Figure 10: Examples of good co-registration between strip edges by comparing H2163.0000, 20-09-2005, MY27, L_s 291.64 with H2189.0000, 27-09-2005, MY27, L_s 296.05

Figure 11: Mosaic of HRSC Orthorectified Images over the South Pole

Figure 12: A mosaic of 2 CTX images and an HRSC ORI. The CTX images were co-registered to the HRSC ORI using the algorithm of (?). The image in the top-left part of the figure is CTX image D14_032511.0959_XI.84S078W_ORI (03-07-2013, MY31, L_s 345.80) while the image in the centre is the CTX image B11_013813.0955_XN.84S078W (07-07-2009, MY29, L_s 299.19). The background image is the level-4 HRSC ORI H2288.0000 (25-10-2005, MY27, L_s 312.46). All images are demonstrated using polar stereographic projection

494 mosaic first, and the highest resolution last. This leaves the best resolved images
 495 at the top of the mosaic stack, and thus most visible in the final product. After
 496 inspection of the completed mosaic in 12.5m/pixel, in order to not sacrifice the
 497 higher-resolution data, some alterations to the mosaicking sequence were made
 498 to move images with more strongly visible atmospheric artefacts lower in the
 499 sequence and optimise the quality of the final product (Figure 11).

500 5.4. Automated co-registration and orthorectification (ACRO) of NASA High- 501 Resolution South Pole Imagery

502 The HRSC level-4 products that were generated using the pipeline presented
 503 in Section 4 are high-resolution 3D surface models with an inherent potential to
 504 facilitate the examination and analysis of South Polar dynamic surface phenom-
 505 ena. Their value is further increased by the use of the automated co-registration
 506 and orthorectification (ACRO) of NASA high-resolution South Pole imagery
 507 using the produced HRSC DTMs and ORIs as a baseline. The goal of this addi-
 508 tional pipeline is to geometrically align all high-resolution South Pole imagery,
 509 but the final objective is to automatically detect South Pole surface changes
 510 through pixel-scale pairwise comparisons as well as multi-source data fusion.
 511 Preliminary results 12 indicate that there is no significant difference in the ac-
 512 curacy and reliability of the ACRO pipeline when the products derived from
 513 this work are used instead of those released by DLR (Gwinner et al., 2009),
 514 which provides further evidence for the quality and geometric accuracy of our
 515 new data products. More information about the ACRO algorithm can be found
 516 in Sidiropoulos and Muller Sidiropoulos et al. (2018).

517 6. Conclusions and Future Work

518 In this paper we have described the production of 33 HRSC orbital strip
519 DTMs covering the SPRC and the South Polar region of Mars (82°S–90°S) by
520 using a method based on DLR-VICAR with modifications by Kim and Muller
521 (2009). The DTMs produced show elevation differences of -2.20 m (up to 0.04
522 m) mean with MOLA PEDR points with a root mean square error of -9.48m
523 and alternatively a mean difference of 1.08m and 7.29m root mean square error
524 with MOLA MEGDR rasters. By comparing different strips taken in different
525 seasons and different years, we find that there are no vertical changes larger
526 than the errors in the DTMs. Different DTM strips can be merged into a
527 single DTM mosaic based on an assessment of the height differences between
528 overlapping strips. The produced ORIs are currently being used as base images
529 for coregistering higher resolution images from CTX and the produced DTMs
530 are currently being used as base DTM to produce higher resolution DTMs.

531 7. Acknowledgements

532 The first author acknowledges support for her studies from the Indonesian
533 Endowment Fund of Education. This work forms part of the European Unions
534 Seventh Framework Programme under iMars grant No. 607379 and by the
535 German Space Agency (DLR Bonn), grant 50QM1702 (HRSC on Mars Ex-
536 press). Partial funding was obtained from the STFC MSSL Consolidated Grant
537 ST/K000977/1. Green Open Access Funding is provided by University College
538 London. The authors acknowledge the Principal Investigator, Ralf Jaumann, of
539 the HRSC instrument onboard the Mars Express mission for providing datasets
540 in the archive. Level-2 Input Datasets of the HRSC instrument have been down-
541 loaded from the ESA Planetary Science Archive (<http://archives.esac.esa.int/psa>).
542 We also express gratitude to the HRSC team and the MOLA team for the us-
543 age of HRSC and MOLA data. In addition, the authors would like to thank
544 Marita Wählisch for kind assistance with the areoid conversion and last but
545 not least, Alexander Dumke for the exterior orientation processing results used
546 within this work. The HRSC orbital strip and mosaiced products of the DTMs
547 and ORIs which are described in this paper are available from the ESA Guest
548 Storage Facility which can be found using the DOI of the HRSC data collection
549 as follows: They can also be browsed, downloaded and visualised through the
550 iMars web GIS at <http://www.i-mars.eu/web-gis>

551 8. References

- 552 Becker, K. J., Archinal, B. A., Hare, T. H., Kirk, R. L., Howington-Kraus, E.,
553 Robinson, M. S., Rosiek, M. R., 2015. Criteria for Automated Identification
554 of Stereo Image Pairs. In: Lunar and Planetary Science Conference. Vol. 46
555 of Lunar and Planetary Inst. Technical Report. p. 2703.

- 556 Blasius, K. R., Vetrone, A. V., Martin, M. D., 1980. Viking orbiter stereo imag-
557 ing catalog. Tech. rep.
- 558 Bostelmann, J., Heipke, C., 2016. Global Bundle Adjustment with Variable
559 Orientation Point Distance for Precise Mars Express Orbit Reconstruction.
560 ISPRS - International Archives of the Photogrammetry, Remote Sensing and
561 Spatial Information Sciences XLI-B4, 361–368.
- 562 Buhler, P. B., Ingersoll, A. P., Ehlmann, B. L., Fassett, C. I., Head, J. W.,
563 2017. How the Martian Residual South Polar Cap Develops Quasi-Circular
564 and Heart-Shaped Pits, Troughs, and Moats. *Icarus* 286, 69–93.
- 565 Byrne, S., Ingersoll, A. P., 2003. A Sublimation Model for Martian South Polar
566 Ice Features. *Science* 299 (5609), 1051–1053.
567 URL <http://science.sciencemag.org/content/299/5609/1051>
- 568 Calvin, W., Cantor, B., James, P., 2017. Interannual and Seasonal Changes in
569 The South Seasonal Polar Cap of Mars: Observations from MY 28-31 using
570 MARCI. *Icarus* 292, 144–153.
- 571 Cantor, B. A., Wolff, M. J., James, P. B., Higgs, E., 1998. Regression of Martian
572 North Polar Cap: 1990-1997 Hubble Space Telescope Observations. *Icarus*
573 136 (2), 175–191.
- 574 Christensen, P. R., Jakosky, B. M., Kieffer, H. H., Malin, M. C., McSween Jr,
575 H. Y., Neelson, K., Mehall, G. L., Silverman, S. H., Ferry, S., Caplinger, M.,
576 2004. The Thermal Emission Imaging System (THEMIS) for the Mars 2001
577 Odyssey Mission. *Space Science Reviews* 110 (1-2), 85–130.
- 578 Duxbury, T. C., Kirk, R. L., Archinal, B. A., Neumann, G. A., 2002. Mars
579 Geodesy/Cartography Working Group Recommendations on Mars Carto-
580 graphic Constants and Coordinate Systems. *International Archives of Pho-
581 togrammetry Remote Sensing and Spatial Information Sciences* 34 (4), 743–
582 748.
- 583 Geissler, P. E., 2005. Three Decades of Martian Surface Changes. *Journal of*
584 *Geophysical Research* 110 (E2).
- 585 Gruen, A., 1985. Adaptive Least Squares Correlation: A Powerful Image Match-
586 ing Technique. *South African Journal of Photogrammetry, Remote Sensing*
587 *and Cartography* 14 (3), 175–187.
- 588 Gwinner, K., Jaumann, R., Hauber, E., Hoffmann, H., Heipke, C., Oberst, J.,
589 Neukum, G., Ansan, V., Bostelmann, J., Dumke, A., Elgner, S., Erkeling, G.,
590 Fueten, F., Hiesinger, H., Hoekzema, N., Kersten, E., Loizeau, D., Matz, K.-
591 D., McGuire, P., Mertens, V., Michael, G., Pasewaldt, A., Pinet, P., Preusker,
592 F., Reiss, D., Roatsch, T., Schmidt, R., Scholten, F., Spiegel, M., Stesky, R.,
593 Tirsch, D., van Gasselt, S., Walter, S., Whlisch, M., Willner, K., 2016. The
594 High Resolution Stereo Camera (HRSC) of Mars Express and Its Approach

595 to Science Analysis and Mapping for Mars and Its Satellites. *Planetary and*
596 *Space Science* 126, 93–138.

597 Gwinner, K., Scholten, F., Preusker, F., Elgner, S., Roatsch, T., Spiegel, M.,
598 Schmidt, R., Oberst, J., Jaumann, R., Heipke, C., 2010. Topography of Mars
599 from Global Mapping by HRSC High-Resolution Digital Terrain Models and
600 Orthoimages: Characteristics and Performance. *Earth and Planetary Science*
601 *Letters* 294 (3), 506–519.

602 Gwinner, K., Scholten, F., Spiegel, M., Schmidt, R., Giese, B., Oberst, J.,
603 Heipke, C., Jaumann, R., Neukum, G., 2009. Derivation and Validation of
604 High-Resolution Digital Terrain Models from Mars Express HRSC Data. *Pho-*
605 *togrammetric Engineering & Remote Sensing* 75 (9), 1127–1142.

606 Heipke, C., Oberst, J., Albertz, J., Attwenger, M., Dorninger, P., Dorrer, E.,
607 Ewe, M., Gehrke, S., Gwinner, K., Hirschmiller, H., others, 2007. Evaluating
608 Planetary Digital Terrain ModelsThe HRSC DTM Test. *Planetary and Space*
609 *Science* 55 (14), 2173–2191.

610 Herschel, W., 1784. XIX. On The Remarkable Appearances at The Polar Re-
611 gions of The Planet Mars, and Its Spheroidical Figure; with A Few Hints
612 Relating to Its Real Diameter and Atmosphere. *Philosophical Transactions of*
613 *the Royal Society of London* 74, 233–273.

614 James, P. B., 1979. Recession of Martian North Polar Cap: 19771978 Viking
615 Observations. *Journal of Geophysical Research: Solid Earth* 84 (B14), 8332–
616 8334.

617 James, P. B., Briggs, G., Barnes, J., Spruck, A., 1979. Seasonal Recession of
618 Mars’ South Polar Cap as Seen by Viking. *Journal of Geophysical Research:*
619 *Solid Earth* 84 (B6), 2889–2922.

620 John Louis Emil, D., 2013. *The Scientific Papers of Sir William Herschel. Vol. 1.*
621 Cambridge University Press.

622 Kieffer, H. H., 2007. Cold Jets in The Martian Polar Caps. *Journal of Geophys-*
623 *ical Research: Planets* 112 (E8).

624 Kim, J., Lin, S.-Y., Choi, Y.-S., Kim, Y.-H., 2013. Toward Generalized Plane-
625 tary Stereo Analysis SchemePrototype Implementation with Multi-Resolution
626 Martian Stereo Imagery. *Earth, Planets and Space* 65 (7), 799–809.

627 Kim, J., Muller, J.-P., 2009. Multi-Resolution Topographic Data Extraction
628 from Martian Stereo Imagery. *Planetary and Space Science* 57 (14-15), 2095–
629 2112.

630 Kirk, R., Howington-Kraus, E., Rosiek, M., Anderson, J., Archinal, B., Becker,
631 K., Cook, D., Galuszka, D., Geissler, P., Hare, T., et al., 2008. Ultrahigh
632 Resolution Topographic Mapping of Mars with MRO HiRISE Stereo Images:
633 Meter-Scale Slopes of Candidate Phoenix Landing Sites. *Journal of Geophys-*
634 *ical Research: Planets* 113 (E3).

635 Kirk, R., Soderblom, L., Howington-Kraus, E., Archinal, B., Team, A., 2002.
636 USGS High Resolution Topo-Mapping of Mars with Mars Orbiter Camera
637 Narrow-Angle Images. *International Archives of Photogrammetry Remote*
638 *Sensing and Spatial Information Sciences* 34 (4), 713–722.

639 Lemoine, F. G., Smith, D. E., Rowlands, D. D., Zuber, M. T., Neumann, G.,
640 Chinn, D., Pavlis, D., 2001. An Improved Solution of the Gravity Field of
641 Mars(GMM-2 B) from Mars Global Surveyor. *Journal of Geophysical Re-*
642 *search* 106 (E10), 23–359.

643 Malin, M. C., Edgett, K. S., Cantor, B. A., Caplinger, M. A., Danielson, G. E.,
644 Jensen, E. H., Ravine, M. A., Sandoval, J. L., Supulver, K. D., 2010. An
645 Overview of the 1985-2006 Mars Orbiter Camera Science Investigation. *Inter-*
646 *national Journal of Mars Science and Exploration* 5, 1–60.

647 Mattson, S., Kirk, R. L., Heyd, R., McEwen, A. S., Eliason, E., Hare, T., Beyer,
648 R., Howington-Kraus, E., Okubo, C., Herkenhoff, K., 2011. Release of HiRISE
649 Digital Terrain Models to the Planetary Data System. Vol. 42. p. 1558.

650 Michael, G. G., Walter, S. H. G., Kneissl, T., Zuschneid, W., Gross, C.,
651 McGuire, P. C., Dumke, A., Schreiner, B., van Gasselt, S., Gwinner, K.,
652 et al., 2016. Systematic Processing of Mars Express HRSC Panchromatic and
653 Colour Image Mosaics: Image Equalisation using an External Brightness Ref-
654 erence. *Planetary and Space Science* 121, 18–26.

655 Neukum, G., Jaumann, R., 2004. HRSC: The High Resolution Stereo Camera
656 of Mars Express. In: *Mars Express: The Scientific Payload*. Vol. 1240. pp.
657 17–35.

658 Otto, G. P., Chau, T. K. W., 1989. Region-Growing Algorithm for Matching of
659 Terrain Images. *Image and vision computing* 7 (2), 83–94.

660 Phillips, T., 2006. Mars is Melting. *Science @ NASA*.
661 URL [https://science.nasa.gov/science-news/science-at-nasa/2003/](https://science.nasa.gov/science-news/science-at-nasa/2003/07aug_southpole)
662 [07aug_southpole](https://science.nasa.gov/science-news/science-at-nasa/2003/07aug_southpole)

663 Piqueux, S., Byrne, S., Richardson, M. I., 2003. Southern Seasonal CO Ice
664 Cap and the Formation of Spiders. *Journal of Geophysical Research: Planets*
665 108 (E8).

666 Piqueux, S., Edwards, C. S., Christensen, P. R., 2008. Distribution of the ices
667 exposed near the south pole of mars using thermal emission imaging sys-
668 tem (themis) temperature measurements. *Journal of Geophysical Research:*
669 *Planets* 113 (E8).

670 Piqueux, S., Kleinböhl, A., Hayne, P. O., Kass, D. M., Schofield, J. T., Mc-
671 Cleese, D. J., 2015. Variability of The Martian Seasonal CO₂ Cap Extent
672 over Eight Mars Years. *Icarus* 251, 164–180.

673 Poole, W., Muller, J.-P., Gupta, S., Grindrod, P. M., 2014. Calibrating Mars
674 Orbiter Laser Altimeter Pulse Widths at Mars Science Laboratory Candidate
675 Landing Sites. *Planetary and Space Science* 99, 118–127.

676 Scholten, F., Gwinner, K., Roatsch, T., Matz, K.-D., Whlisch, M., Giese, B.,
677 Oberst, J., Jaumann, R., Neukum, G., 2005. Mars Express HRSC Data Pro-
678 cessing Methods and Operational Aspects. *Photogrammetric Engineering &*
679 *Remote Sensing* 71 (10), 1143–1152.

680 Seidelmann, P. K., Abalakin, V. K., Bursa, M., Davies, M. E., De Bergh, C.,
681 Lieske, J. H., Oberst, J., Simon, J. L., Standish, E. M., Stooke, P., 2002.
682 Report of the IAU/IAG Working Group on Cartographic Coordinates and
683 Rotational Elements of The Planets and Satellites: 2000. *Celestial Mechanics*
684 *and Dynamical Astronomy* 82 (1), 83–111.

685 Sheehan, W., 1996. *The Planet Mars: A History of Observation & Discovery*.
686 University of Arizona Press.

687 Shin, D., Muller, J.-P., 2012. Progressively Weighted Affine Adaptive Corre-
688 lation Matching for Quasi-Dense 3D Reconstruction. *Pattern Recognition*
689 45 (10), 3795–3809.

690 Sidiropoulos, P., Muller, J.-P., 2018. A Systematic Solution to Multi-Instrument
691 Co-Registration to High-Resolution Planetary Images to an Orthorectified
692 Baseline. *IEEE Transactions on Geoscience and Remote Sensing* 56 (1), 78–
693 92.

694 Sidiropoulos, P., Muller, J.-P., Watson, G., Michael, G., Walter, S., 2018. Au-
695 tomatic Coregistration and Orthorectification (ACRO) and Subsequent Mo-
696 saicing of NASA High-Resolution Imagery over The Mars MC11 Quadrangle,
697 using HRSC as A Baseline. *Planetary and Space Science* 151, 33 – 42.

698 Smith, D., Neumann, G., Ford, P., Arvidson, R. E., Guinness, E. A., Slavney,
699 S., 1999. Mars Global Surveyor Laser Altimeter Mission Experiment Grid-
700 ded Data Record, MGS-M-MOLA-3-PEDR-L1A-V1.0. NASA Planetary Data
701 System.

702 Smith, D. E., Zuber, M. T., Frey, H. V., Garvin, J. B., Head, J. W., Muhle-
703 man, D. O., Pettengill, G. H., Phillips, R. J., Solomon, S. C., Zwally, H. J.,
704 et al., 2001a. Mars orbiter laser altimeter: Experiment summary after the
705 first year of global mapping of mars. *Journal of Geophysical Research: Plan-*
706 *ets* 106 (E10), 23689–23722.

707 Smith, D. E., Zuber, M. T., Neumann, G. A., 2001b. Seasonal Variations of
708 Snow Depth on Mars. *Science* 294 (5549), 2141–2146.
709 URL <http://science.sciencemag.org/content/294/5549/2141>

710 Soffen, G. A., Snyder, C. W., 1976. The First Viking Mission to Mars. *Science*
711 193, 759–766.

712 Tao, Y., Muller, J.-P., 2017. Automated Planet-Wide DTM Generation from
713 NASA MRO Data A Status Report. In: Lunar and Planetary Science Con-
714 ference. Vol. 48 of Lunar and Planetary Institute Technical Report. p. 2965.

715 Tao, Y., Muller, J.-P., Sidiropoulos, P., Xiong, S.-T., Putri, A., Walter, S.,
716 Veitch-Michaelis, J., Yershov, V., 2018. Massive Stereo-Based DTM Produc-
717 tion for Mars on Cloud Computers. Planetary and Space Science.

718 Thomas, N., Cremonese, G., Banaszkiewicz, M., Bridges, J., Byrne, S.,
719 da Deppo, V., Debei, S., El-Maarry, M. R., Hauber, E., Hansen, C. J., 2014.
720 The Colour and Stereo Surface Imaging System (CaSSIS) for ESA’s Trace
721 Gas Orbiter. In: 8th International Conference on Mars.

722 Thomas, P., Calvin, W., Cantor, B., Haberle, R., James, P., Lee, S., 2016. Mass
723 Balance of Mars Residual South Polar Cap from CTX Images and Other
724 Data. *Icarus* 268, 118–130.

725 Thomas, P., James, P., Calvin, W., Haberle, R., Malin, M., 2009. Residual
726 South Polar Cap of Mars: Stratigraphy, History, and Implications of Recent
727 Changes. *Icarus* 203 (2), 352–375.

728 Thomas, P., Malin, M., James, P., Cantor, B., Williams, R., Gierasch, P., 2005.
729 South Polar Residual Cap of Mars: Features, Stratigraphy, and Changes.
730 *Icarus* 174 (2), 535–559.

731 Thomas, P. C., Malin, M. C., Edgett, K. S., Carr, M. H., Hartmann, W. K.,
732 Ingersoll, A. P., James, P. B., Soderblom, L. A., Veverka, J., Sullivan, R.,
733 2000. NorthSouth Geological Differences Between the Residual Polar Caps
734 on Mars. *Nature* 404 (6774), 161–164.

735 Thornhill, G. D., Rothery, D. A., Murray, J. B., Cook, A. C., Day, T., Muller,
736 J.-P., Iliffe, J., 1993. Topography of Apollinaris Patera and Ma’adim Vallis:
737 Automated Extraction of Digital Elevation Models. *Journal of Geophysical*
738 *Research: Planets* 98 (E12), 23581–23587.