

Influence of channel shape on wave generated parameters by a pressure source in shallow water

Mohammadreza Javanmardi¹

PhD, Australian Maritime College, University of Tasmania, Australia

AMC, Launceston, Tasmania, 7250, Australia

Mj00@utas.edu.au

Jonathan Binns

Associate Dean of Research, Australian Maritime College

AMC, Launceston, Tasmania, 7250, Australia

jrbins@amc.edu.au

Martin Renilson

Dean, Maritime Programs, Higher Colleges of Technology

martin.renilson@hct.ac.ae

Giles Thomas

BMT Chair of Maritime Engineering, University College London

giles.thomas@ucl.ac.uk

Abstract

The present work is a numerical investigation into the waves generated by a pressure source moving in straight channels with a non-rectangular cross channel depth profile. Wave fields generated by the moving pressure source are described, and the effects of channel bathymetry on the generated wave

¹ Corresponding author
Email: mj00@utas.edu.au

characteristics; wave height, wave breaking location, wave breaking type and intensity, and peel angle are presented. Four different channel cross-section shapes were investigated and the results were analysed.

It was concluded that maximum wave height depends on pressure source parameters and the channel shape does not have significant effect on the maximum wave height. All four investigated channels were able to generate plunging shaped breaking waves. In addition, it was found that wave breaking intensity and barrel shape can be controlled by beach slope shape, however, beach slope does not have considerable effect on the wave breaking location. The width of deep-section of channel has significant effect on the breaking location. Widening the deep-section of the channel moves the breaking point further from the pressure source. According to the simulation results, it is possible to generate waves for intermediate to expert levels only by changing the pressure source speed. According to the results, by changing the pressure source speed, the peel angle changes and is the best way to change the required skill level for surfing and also, changing the channel shape does not have significant effect on required skill level for surfing.

Keywords: Shallow water wave, Wave breaking type, Wave breaking intensity, Peel angle

Introduction

Vessel generated waves

Usually the wave generated by high-speed vessels moving in shallow water is considered in terms of environmental and safety hazard in confined waters. Creating vessel generated waves, disturbing other vessels in ports and harbours, shoreline erosion and its impact on marine life are some of the most important issues in this field (Macfarlane 2012). Field studies have been conducted on several locations where problems of this nature have occurred (Nanson, Krusenstierna et al. 1994, Macfarlane and Cox 2004, Macfarlane, Cox et al. 2008).

The wash waves generated by vessels can be characterized in terms of the hull shape (Renilson and Lenz 1989) and operating condition (Robbins, Thomas et al. 2011). Due to the great interest in wake-wash effects, a considerable amount of research effort has been conducted in the last years. In model experimental studies the focus has been on designing low-wash ships and acquiring reliable data for validation (Zibell and Grollius 1999, Koushan, Werenskiold et al. 2001, Macfarlane and Bose 2012).

Effect of waterway bathymetry

Waterway bathymetry has influence on the wash wave generated characteristics. Natural and man-made water channels often have non-rectangular cross sections. It is important to understand how channel geometry affects the evolution of waves in water channels of arbitrary shape. Several researchers have studied waves propagating in channels with arbitrary cross-section profiles (Peregrine 1966, Peters 1966) and the wave patterns, in two horizontal dimensions generated by a disturbance moving at speeds close to the critical Froude number in channels with a rectangular cross-section profile (Ertekin, Webster et al. 1986, Katsis and Akylas 1987, Pedersen 1988). Mathew and Akylas (Mathew and Akylas 1990) studied waves propagating in channels with a trapezoidal cross-section profile. Teng and Wu (Teng and Y. Wu 1997), Jiang et al. (Jiang, Henn et al. 2002). and Liu and Wu (Liu and Wu 2004) have made contributions to this field of research. According to their results, the wavelength and time period of wave generation were affected by both the submerged channel cross-sectional geometry and the channel sidewall slope at the waterline. Most of these studies deal with channels with trapezoidal cross-section profiles, but Jiang et al. (Jiang, Henn et al. 2002) include results for a channel with a deep trench along the centre line. They used a method based on Boussinesq-type equations for the far-field flow and on slender-body theory for the near-ship flow and they showed this method is able to predict 2D wave propagation and waves far from the vessel in a rectangular channel.

69 *Waves for surfing*

70 In addition to these reasons for conducting wake wave studies, such waves can be considered with respect
71 to the wave surfing. A new surf pool concept was developed by Greg Webber and his idea to produce
72 continuous breaking waves was patented (Webber 2004, Webber 2006) by Liquid Time Pty Ltd. This
73 invention is based on a circular pool in which the surfing waves are created continuously along the banks
74 of the pool (Schmied, Binns et al. 2011). The idea was born from Webber's experiences surfing in the
75 Clarence River on waves generated behind a fishing boat. Webber's idea is based on one or more pressure
76 sources being rotated within an annular wave pool to generate waves. A pressure source is any object that
77 disrupts the water's surface and creates a wave. The circular channel has sloping bathymetry with the
78 outer side being deeper; the waves are generated in the deep water and break in the shallow water on the
79 inner island (Fig. 1).

80 *Prediction of vessel generated waves*

81 Tools for predicting the near-field vessel generated waves and their propagation to far field with accuracy
82 are needed. Most research has been conducted using theoretical (Chandrababha and Molland 2004) or
83 experimental (Fontaine and Tulin 1998, Henn, Sharma et al. 2001) approaches. In numerical simulations,
84 the focus has been on developing efficient methods. For a ship moving in water of uniform depth, linear
85 and nonlinear theories can be applied usefully in the subcritical and the supercritical speed range (Raven
86 2000, Yang, Faltinsen et al. 2001). Thin ship theory can be used for the wave generated by a ship moving
87 in a channel. This theory provides an alternative to higher order panel methods for estimating wave
88 resistance when applied solely to slender hulls (Chandrababha and Molland 2004), but it is not valid for
89 unsteady cases and transom stern flow separation (Yang, Faltinsen et al. 2001). More general shallow
90 water approximations are obtained from Boussinesq type equations, which are valid for most arbitrarily
91 unsteady cases. Boussinesq's equations based on a suitable reference level were used for computing ship
92 waves in shallow water. However this method is not able to predict the 3D flow pattern around the vessel
93 (Kofoed-Hansen, Jensen et al. 2000). An alternative is to combine the thin ship theory and the Boussinesq

method. This hybrid approach combines a steady nonlinear panel method for the near-ship flow with a Boussinesq solver for the far-field wave propagation (Yang, Faltinsen et al. 2001). However, this method is only useful for steady problems. It should be noted that due to the nonlinear and unsteady nature, as well as the large domain feature of the wash problems, they cannot be solved well by the linear wave theory nor approximated efficiently by nonlinear singularity methods. Typically, the finite volume method has been used to predict the wave generated and its propagation (Kofoed-Hansen, Jensen et al. 2000, Kim 2003).

Wave parameters for surfing

The wave breaking location, breaking type and intensity, and peel angle are most important characteristics which should be considered for generated waves for surfing purposes. It is well known that a wave will break in different shapes depending on the beach slope, wave height and the wavelength perpendicular to the beach slope. The types of breaker shapes were defined by Galvin (Galvin 1968). There are some existing methods that can be used to describe wave breaking characteristics such as Iribarren number (Black and Mead 2001). The Iribarren number is defined as:

$$\xi = \frac{\tan(s)}{\sqrt{H_{breaking}/\lambda_s}} \quad (1)$$

where s is the beach slope, $H_{breaking}$ is wave height at the breaking point and λ_s is the offshore wavelength perpendicular to the direction of wave propagation. The wave breaker type can be predicted based on value for ξ :

$$\begin{cases} \xi < 0.4 & \text{Spilling} \\ 0.4 \leq \xi \leq 2.0 & \text{Plunging} \\ \xi > 2.0 & \text{Surging / collapsing} \end{cases}$$

However, while these methods give an indication of breaker type, studies of surfing wave shape have found that they do not accurately differentiate the transition between breaker categories (Mead 2003).

The cubic curve method is a method for predicting the shape of a plunging wave and wave breaking intensity (Sayce, Black et al. 1999). In this method a cubic curve is fitted to the crest parallel images of breaking waves and vortex length (l), vortex width (w), vortex breaking angle (θ) and wave height are calculated (Fig. 2). The ‘vortex ratio’ (tube length to width: Fig. 2) is a measure of the ‘roundness’ of the tube. As the ratio of vortex length to width approaches 1, the tube shape becomes more circular and the breaking is more intense (Black and Mead 2001).

Peel angle is a term used to describe the speed that a surfer needs to travel successfully across the face of a wave (Mead 2003). The peel angle is defined as the angle between the trail of the broken white water and the crest of the unbroken part of the wave as it propagates shoreward (Fig. 3). Peel angles range between 0° and 90° , with small peel angles resulting in fast surfing waves and large angles in slow surfing waves. It is possible to classify the surfing skill for all channels by considering the wave height and the peel angle (Mead 2003) (Hutt, Black et al. 2001).

Methodology

In this study, a Computational Fluid Dynamics approach was utilized to predict the motion of the fluid, and hence the free-surface. The CFD software ANSYS-Fluent was used as the flow solver. Previous work by the authors demonstrated that ANSYS-Fluent software is capable of predicting the wave parameters (Javanmardi, Binns et al. 2013, Javanmardi 2015). In this investigation, the effect of channel bathymetry on the key parameters (wave breaking location, breaking type and intensity, and peel angle) was investigated and the results are presented here.

Numerical method

Simulation setups

In this study, a Computational Fluid Dynamics approach was utilized. The CFD software ANSYS-Fluent version 14.0 was used as the flow solver (2011). The governing equations are three-dimensional Reynolds Averaged Navier-Stokes equations for incompressible flows, along with the $k - \varepsilon$ turbulence model. These were solved using the FVM approach. Since the flow is incompressible, a pressure based solver was used.

The volume of fluid approach was used with a time dependent and first order explicit time discretisation scheme. The SIMPLE algorithm was used for pressure-velocity coupling. The PRESTO scheme was used to interpolate the pressure on the cell faces, as this is recommended for VOF simulations (Andersson, Andersson et al. 2012). The Least Squares Cell Based scheme was used for gradient discretisation and momentum was discretized with second order upwind approach. The standard wall function was utilised for $k - \varepsilon$ turbulence modelling.

In this work, to discretize the convective term in the equation for transport of the volume fraction, the High Resolution Interface Capturing scheme (HRIC) was used (Muzaferija, peric et al. 1998).

A variable time step method with Global Courant Number of 5 and 20000 time steps was chosen, with five iterations per time step. The First Order Implicit method was used for transient formulation.

In general, the number of cells in the domain was about 17 millions. Simulation models were executed on 48 nodes at AMC Linux cluster that consisted of quad core, 64 bit system. Typically, each simulation took three weeks to complete.

To predict the wave height accurately, the cell aspect ratio is a significantly important parameter. An average aspect ratio of no greater than about 7 is required to predict wave height. Additionally, 10 cells

per wave height are sufficient to predict wave height (Javanmardi, Binns et al. 2013). These outcomes were utilised to generate cells in the domains.

Mostly hexahedral meshes were used to discretize the domains. The velocity inlet and outflow conditions were used to specify the inlet and outlet boundary conditions and the remaining boundary surfaces along the exterior of the domain were set to no-slip wall conditions.

The simulations were accomplished using moving reference frames (MRF) with Fluent ANSYS providing these for both translating and rotating systems.

Validation

The experimental results, obtained from tests conducted at the AMC towing tank, were compared with the numerical predictions in earlier work (Javanmardi, Binns et al. 2012, Javanmardi, Binns et al. 2013). The wavedozer **wich used as a pressure source** was a wedge shape body with constant beam (Driscoll and Renilson 1980). Towing tank tests were conducted in a water depth of 1.5 m with a wavedozer of 0.3 m beam and 0.1 m **draft. Fig. 4 to Fig. 6 present the wave time history for $Fr_h = 0.7$ at three different lateral distances. Since the first wave behind the pressure source was important for this study, the simulations' convergence checked by monitoring the continuity residuals and characteristic of the first generated wave behind the pressure source and the simulations were ceased as soon as the first generated wave height reached to a steady level.** Fig. 7 shows the comparison of maximum wave height of numerical and experimental results at varying lateral distances for different depth Froude numbers, where depth Froude number is based on the (Javanmardi, Binns et al. 2012)depth under the wavedozer and is defined by equation (7):

$$Fr_h = \frac{V}{\sqrt{gh}} \quad (7)$$

where V is wavedozer speed (m/s), g is gravitational acceleration (m/s^2) and h (m) is depth of calm water in the deep-section of the channel.

As can be seen from Fig. 4 to Fig. 6, and from (Javanmardi, Binns et al. 2012, Javanmardi, Binns et al. 2013) the numerical simulations were able to adequately predict the experimental results, thus giving confidence in the use of this approach to investigate the effect of bathymetry on the generated waves.

Test geometries

The validated numerical approach discussed above was used to investigate the influence of channel shape on the wave pattern generated by a pressure source. For all the cases a wanedozer was used as the pressure source. The concept of the wanedozer is explained in (Driscoll and Renilson 1980). A schematic of the wanedozer used for this study is given in Fig. 8.

Four channels with the cross-sections as shown in **Error! Reference source not found.** were used. In each case the wanedozer was located adjacent to the wall on the left hand side.

For the simulation, 144.5m of channel length with a downstream domain of 84m was modelled. The depth of water at the deep-section of channel was 3.75 m in each of the cases. Approximately 17 million cells were used, based on mesh density studies conducted earlier (Javanmardi, Binns et al. 2013).

The depth Froude number was altered by changing the velocity. The focus of the work was on depth Froude numbers close to one, as this had already been shown to be the value which gives the best quality for surfing (Javanmardi 2015).

Results and discussion

Wave height and breaking location

Error! Reference source not found. presents free surface elevation for Channel 1 at depth Froude number of 0.95. Fig. 11 presents the predicted wave height at different lateral distances for various depth Froude numbers. It can be seen that it is possible to generate larger wave by increasing wanedozer's speed. To find the breaking point location, the numerical results were post-processed by generating a

plane at different lateral distances and observe the shape of free-surface. The open markers in the figures show the start of wave breaking at different depth Froude numbers. It can be seen that for all Fr_h , the wave starts to break around 14 m lateral distance except for $Fr_h = 0.8$. At $Fr_h = 0.8$, the breaking point is close to the pressure source. In addition, the wave at $Fr_h = 0.9$ has two breaking points. Depth-limited breaking occurs when orbital velocities, increasing towards the beach exceed the wave phase speed which decreases in the landward direction. Generally, the depth-limited breaking happens where $0.35 < \frac{H_b}{h_b} < 0.5$, where H_b is related to the breaking wave height and h_b is water depth at breaking. According to Nelson (Nelson 1997) the depth-to-wave height ratio cannot exceed 0.55. To investigate whether the breaks are depth-limited breaking, wave heights and water depth at breaking points were summarized in Table 1. According to Table 1, the depth-to-wave height ratio (H/h) for all breaks is less than 0.55. Only the first breaks at $Fr_h = 0.8$ and $Fr_h = 0.9$ (close to wadedozer) are out of the depth-limited breaking condition, while other breaking points are in the interval.

Since nearly all of the waves break at around 14 m lateral distance, it was thought to be possible to move the breaking point further from the pressure source by changing the bathymetry for y greater than 13.5m (0.5m before the breaking point) and making the cross-section plateau as shown in **Error! Reference source not found.**. This configuration was simulated at two Fr_h values of 0.8 and 0.99. The results for the two different channel configurations are compared in Fig. 12 for $Fr_h = 0.8$, and 0.99. The break point for Channel 2 configuration occurred at the same position as in Channel 1 for both the simulated values of Fr_h . It was concluded that changing the bathymetry beyond $y=13.5$ m does not have any significant effect on the location of break point.

Since changing the bathymetry for y greater than 13.5 did not change the location of breaking point, it was assumed that the wave is completely developed before $y=13.5$ m such that changing the bathymetry only half a meter before the break point (14m) does not have any influence. Thus, the effect of the lateral position of the toe of the beach was investigated using a third channel geometry, channel 3 (see **Error!**

Reference source not found.) For this geometry the flat bathymetry starts at $y = 12$ m from the wall. This configuration was simulated at $Fr_h = 0.99$. According to the results (Fig. 13), it is clear that changing the bathymetry did not have any effect on the breaking point nor on the wave height before breaking.

In the next configuration (Channel 4), the slope of the bathymetry was kept identical to Channel 1, but the width of the deep-section of the channel was increased to 12m (Fig. 9). The wave heights were almost the same for all four channels at the same pressure source speed ($Fr_h = 0.99$). Comparing the results of Channel 4 with previous results showed that increasing the width of the deep-section of the channel causes the wave breaking point to move further from the pressure source (closer to the beach), Fig. 13. Widening the channel by three meters causes the breaking point to move 4 m. Since generated wave does not breaking the deep-section of channel 1 at $Fr_h=0.99$, widening the deep-section moves breaking point further from the wanedozer. Additionally, there is decrease in the wave height in the deep-section in Channel 4 compared to Channel 1 (see Fig. 13) which causes the height-to-water depth ratio on the beach for Channel 4 becomes less than Channel 1. Therefore, to compensate the decrease, the breaking point moves more than 3 meters added to deep-section.

Wave breaking type and intensity

Several factors affect the category that waves fall into when breaking (spilling, plunging, collapsing or surging), such as wave height and wave length, wind strength and direction. However, the bathymetry has most influence on the shape of breaking waves. The transition of breaker shape, from spilling through to surging, is mainly a result of increasing the seabed gradient. On low gradient seabeds, waves break with a spilling form. As seabed gradients increase, breaker form tends towards plunging, and finally to collapsing or surging waves on very steep gradients.

As explained previously, Iribarren number can be used to describe wave breaking characteristics. **Error! Reference source not found.** shows that the generated wave plunges for channel 3 at $Fr_h=0.99$. Due to

the following reasons, the Iribarren number cannot be used to predict wave breaking type in this case. Simulation results for Channel 2 and Channel 3 indicate that it is possible to have the plunging breaking type (see **Error! Reference source not found.**) where the beach slope is zero, while according to the Iribarren, waves spill over low gradient bathymetry. In addition, the Iribarren number was defined for waves with crests perpendicular to the beach, while the waves generated by moving pressure sources have an angle relative to the beach. Therefore, it is proposed that it is inappropriate to use the Iribarren number to quantify the wave breaking intensity in this study.

The cubic curve method is a method for predicting the shape of a plunging wave and wave breaking intensity. Fig. 15 compares the experimental and numerical wave breaking shape and proves that numerical approach is able to predict shape of plunging waves. To identify the vortex ratio for different channel shapes, the numerical results were post-processed by generating a plane at the distance where the wave plunged. The vortex ratio is manually measured at the moment wave lip just touches the water. The maximum length of vortex was chosen as vortex length and the maximum width perpendicular to the vortex length was selected as vortex width. Table 2 shows the measured vortex ratio for different channels. It is clear that the breaking shapes for the different channels are different. As a general conclusion, the channel slope shape has an effect on the breaking intensity. In addition, Channel 1 has the highest vortex ratio and Channel 4 has the lowest. The water depths at breaking point for Channel 1 and 4 are 1.25 and 1.08 m and the wave heights are 0.9 and 0.91 m respectively. Therefore, the wave height-to-water depth ratio for Channel 4 is bigger than Channel 1 that has effect on wave breaking intensity. From this conclusion it can be further concluded that Channel 1 has lowest intensity and Channel 4 has highest.

Peel Angle

By finding the position of wave peak at different lateral distances, the average peel angle was calculated. Table 3 and Table 4 show the average peel angles and surfing skills for different Fr_h and different channel shapes. According to the results, the best way to change the required skill level for surfing is to change

the pressure source speed and changing the channel shape does not have significant effect on required skill level for surfing.

Concluding remarks

In this study, the influences of channel parameters on wave characteristics were investigated. Four full scale channels with different cross-sections were modelled, with the effect of beach slope and channel shape on the wave breaking location, wave breaking type and intensity, and peel angles investigated. It is possible to generate larger wave by increasing wanedozer's speed. The wave heights were almost the same for all four channels at the same pressure source speed ($Fr_h = 0.99$). It was concluded that channel shape does not have significant effect on the maximum wave height and the maximum wave height is function of pressure source parameters. In terms of wave breaking intensity, all four channels were able to generate plunging shaped breaking waves. Beach slope shape has an effect on wave breaking intensity, while it does not have considerable effect on the wave breaking location. The width of deep-section of channel has significant effect on the breaking location. Widening the deep-section of the channel moves the breaking point further from the pressure source. It was concluded that Iribarren number could not be used to determine the wave breaking type in these cases. The cubic curve method was used to specify the wave breaking intensity. The vortex ratio for each breaking wave was measured. It was found that changing the beach slope had an effect on the barrel shape. The peel angles were extracted from simulation results for different Fr_h and different channels. Based on Hutt's chart, the surfing skill level for different channels and different speeds were considered. According to the simulation results, it is possible to generate waves for intermediate to expert levels by changing the speed. By comparing the results for all channel configurations, two important conclusions can be made. Firstly, in terms of construction costs and commercial considerations, Channel 1 is the most successful, because it is possible to generate a wave with the same height as the other channels while this channel is the narrowest, thus needing the least materials and would have the lowest construction cost. Secondly, in terms of surfing, since the breaking

point in Channel 4 occurs further from pressure source than other channels, the surfable wave width is larger than other waves which gives more space to surfers for manoeuvring.

Acknowledgement

The Authors wish to thank the Australian Research Council (ARC), University of Tasmania and Liquid time Pty Ltd that funded this research. This research was supported under Australian Research Council's Linkage Projects funding scheme (project number LP0990307).

References

- (2011). ANSYS FLUENT User's Guide, ANSYS, Inc.
- Andersson, B., et al. (2012). Computational Fluid Dynamics for Engineers, Cambridge University Press.
- Black, K. and S. Mead (2001). "Field Studies Leading to the Bathymetric Classification of World-Class Surfing Breaks." Journal of Coastal Research: 5-20.
- Black, K. and S. Mead (2001). "Predicting the Breaking Intensity of Surfing Waves." Special issue of the Journal Coastal Research on Surfing.
- Chandraprabha, S. and A. F. Molland (2004). A Numerical Prediction of Wash Wave and Wave Resistance of High Speed Displacement Ships in Deep and Shallow Water. Conference of Mechanical Engineering Network of Thailand. Khon Kaen, Thailand.
- Driscoll, A. and M. R. Renilson (1980). "The Wavedozer. a System of Generating Stationary Waves in a Circulating Water Channel." AMTE(H) TM80013.
- Ertekin, R. C., et al. (1986). "Waves Caused by a Moving Disturbance in a Shallow Channel of Finite Width." Fluid Mechanics: 18.
- Fontaine, E. and M. P. Tulin (1998). On the Prediction of Nonlinear Free-Surface Flows Past Slender Hulls Using 2D+T Theory: The Evolution of an Idea. Fluid Dynamics of Vehicles Operating Near or in the Air-Sea Interface Amsterdam, Netherland.
- Galvin, C. J. J. (1968). "Breaker Type Classification on Three Laboratory Beaches." J. Geoph. Res.(73): 3651-3659.

- Henn, R., et al. (2001). Influence of Canal Topography on Ship Waves in Shallow Water. 16th International Workshop on Water Waves and Floating Bodies. Hiroshima, Japan.
- Hutt, J. A., et al. (2001). "Classification of surf breaks in Relation to Surfing Skill." Journal of Coastal Research(29): 16.
- Javanmardi, M. (2015). The Investigation of High Quality Surfing Waves Generated by a Moving Pressure Source. Australian Maritime College, University of Tasmania. **PhD**.
- Javanmardi, M., et al. (2012). The Formation of Surfable Waves in a Circular Wave Pool- Comparison of Numerical and Experimental Approaches. 31th International Conference on Ocean, Offshore and Arctic Engineering. Rio de Janeiro, Brazil.
- Javanmardi, M., et al. (2013). Prediction of Water Wave Propagation Using Computational Fluid Dynamics. 32nd International Conference on Ocean, Offshore and Arctic Engineering OMAE2013, Nantes, France.
- Jiang, T., et al. (2002). Wash Waves Generated by Ships Moving on Fairways of Varying Topography. The 24th Symposium on Naval Hydrodynamics, Fukuoka, Japan.
- Katsis, C. and T. R. Akylas (1987). "On the Excitation of Long Nonlinear Water Waves by a Moving Pressure Distribution. Part 2. Three-Dimensional Effects." Fluid Mechanics: 18.
- Kim, Y. (2003). "Artificial Damping in Water Wave Problems II: Application to Wave Absorption." International Journal of Offshore and Polar Engineering **13**: 5.
- Kofoed-Hansen, H., et al. (2000). Wake Wash Risk Assessment of High-Speed Ferry Routes – A Case Study and Suggestions for Model Improvements. International Conference on Hydrodynamics of High-Speed Craft - Wake Wash and Motion Control. London, UK, The Royal Institution of Naval Architects.
- Koushan, K., et al. (2001). Experimental and Theoretical Investigation of Wake Wash. FAST. Southampton, UK, The Royal Institution Of Naval Architects. **I**: 165-179.
- Liu, P. L.-F. and T.-R. Wu (2004). "Waves Generated by Moving Pressure Disturbances in Rectangular and Trapezoidal Channels." Journal of Hydraulic Research: 9.
- Macfarlane, G. (2012). Marine Vessel Wave Wake: Focus on Vessel Operations Within Sheltered Waterways. Australian Maritime College, University of Tasmania. **Doctor of Philosophy**.
- Macfarlane, G. and G. Cox (2004). The Development of Vessel Wave Wake Criteria for the Noosa and Brisbane Rivers in Southeast Queensland. 5th International Conference on Coastal Environment, Alicante, Spain.
- Macfarlane, G., et al. (2008). "Bank Erosion From Small Craft Wave Wake in Sheltered Waterways." RINA Transactions, International Journal of Small Craft Technology **Part B**.

Macfarlane, G. J. and N. Bose (2012). "Wave Wake: Focus on Vessel Operations Within Sheltered Aterways." SNAME **006**.

Mathew, J. and T. R. Akylas (1990). "On Three-Dimensional Long Water Waves in a Channel With Sloping Sidewalls." Fluid Mechanics: 19.

Mead, S. (2003). Surfing Science. 3rd International Surfing Reef Symposium, Raglan, New Zealand.

Muzaferija, S., et al. (1998). A Two-Fluid Navier-Stokes Solver to Simulate Water Entry. International Proceeding 22nd Symposium on Naval Hydrodynamics, Washington, DC.

Nanson, G., et al. (1994). "Experimental Measurements of River Bank Erosion Caused by Boat-Generated Waves on the Gordon River, Tasmania." Regulated Rivers, Research and Management **9**: 14.

Nelson, R. (1997). "Height Limits in Top Down and Bottom Up Wave Environments." Coastal Engineering **32**: 9.

Pedersen, G. (1988). "Three-Dimensional Wave Patterns Generated by Moving Disturbances at Transcritical Speeds." Fluid Mechanics: 25.

Peregrine, D. H. (1966). "Long Waves in a Uniform Channel of Arbitrary Cross Section." Fluid Mechanics: 23.

Peters, A. S. (1966). "Rotational and Irrotational Solitary Waves in a Channel with Arbitrary Cross-Section." 26.

Raven, H. C. (2000). Numerical Wash Prediction Using a Free-Surface Panel Code. International Conference on Hydrodynamics of High-Speed Craft - Wake Wash and Motion Control. London, UK, The Royal Institution of Naval Architects.

Renilson, M. R. and S. Lenz (1989). An Investigation into the Effect of Hull Form on the Wake Wave Generated by Low Speed Vessels. 22nd American Towing Tank Conference.

Robbins, A., et al. (2011). "Subcritical Wave Wake Unsteadiness." RINA Transactions, International Journal of Maritime Engineering **153, Part A3**.

Sayce, A., et al. (1999). Breaking Wave Shape on Surfing Reefs. 14th Australian Conference on Coastal Engineering.

Schmied, S., et al. (2011). A Novel Method for Generating Continuously Surfable Waves- Comparison of Predictions with Experimental Results. 30th International Conference on Ocean, Offshore and Arctic Engineering, Rotterdam, Netherlands.

419 Teng, M. H. and T. Y.Wu (1997). "Effects of Channel Cross-Sectional Geometry on Long Wave
420 Generation and Propagation." Physics and Fluids: 20.

421

422 Webber, G. (2004). Wave Generation Apparatus. I. P. Australia. Australia. **20049070401**.

423

424 Webber, G. (2006). W. I. P. Organization. Switzerland.

425

426 Yang, Q., et al. (2001). Wash of Ships in Finite Water Depth. FAST. Southhampton, UK, The Royal
427 Institution of Naval Architects: 181-196.

428

429 Zibell, H. G. and W. Grollius (1999). Fast Vessels on Inland Waterways. The RINA International
430 Conference on Coastal Ships and Inland Waterways, London, England.

431

432

433




Fig. 1 : Wave pool concept (reproduced with perission of Liquid time Pty Ltd)




Fig. 2: Curve fitting method (contain data from (Sayce, Black et al. 1999))




Fig. 3: Schematic diagram of wave peel angle, α . (contain data from (Mead 2003))




Fig. 4: Wave height time history for $Fr_h=0.7$ at 0.75m lateral distance from centre-line (WP1)




Fig. 5: Wave height time history for $Fr_h=0.7$ at 1.0m lateral distance from centre-line (WP2)





Fig. 6: Wave height time history for $Fr_h=0.7$ at 1.25m lateral distance (WP3)


441



442


443 Fig. 7: Comparison of maximum wave height of numerical and experimental results at varying lateral distances for
 444 different depth Froude numbers, the horizontal axes presents the distance from from centre-line

445




446

447 Fig. 8: Wavedozer of beam=4.0 m, draught=0.75 m, angle of attack= 7 degrees




Channel 1



Channel 2



Channel 3



Channel 4

Fig. 9: Investigated channels' parameters




Fig. 10: Free surface elevation for Channel 1 at $Fr_h=0.95$ at the same time instant but different views




Fig. 11: Wave height at different lateral distances for various Depth Froude numbers for Channel 1

Table 1: Wave height and water depth at wave breaking points for different Froude depth numbers for Channel 1

Fr_h	Wave height at breaking point H [m]	Water depth at breaking point h [m]	H/h
0.8	0.84	3.75	0.224
0.9	0.94	3.75	0.25
	0.77	1.7	0.45
0.95	0.87	1.7	0.51
0.99	0.9	1.7	0.53




Fig. 12: Comparison of the results for two different channel configuration; channel 1 and channel 2, at $Fr_h = 0.8$




Fig. 13: Simulation results of wave height for different lateral distances for four channel configurations at $Fr_h = 0.99$.




Fig. 14: Plunging shape of the wave for channel 3 at $Fr_h=0.99$ at different lateral distances

Table 2: Vortex ratio for different channel at $Fr_h=0.99$

	Vortex ratio
Channel 1	3.8
Channel 2	5
Channel 3	4.2
Channel 4	5.5




Fig. 15: Comparison of experimental and numerical wave breaking shape

Table 3: Average Peel Angle for Channel 1 for Different Fr_h

Fr_h	Average peel angle (degrees)	Average wave height (mm)	Surfing skill level
0.8	63	395	9
0.9	66	870	4
0.95	63	923	4
0.99	52	913	6

Table 4: Average Peel Angle for Different Channels at $Fr_h=0.99$

	Average peel angle (degrees)	Average wave height (mm)	Surfing skill level
Channel 1	52	913	6
Channel 2	52	903	6
Channel 3	52	903	6
Channel 4	54	898	7