Experimental investigation of wave-in-deck impact events on a TLP model

Nagi Abdussamie¹, Yuriy Drobyshevski¹, Roberto Ojeda¹, Giles Thomas², Walid Amin¹

¹National Centre for Maritime Engineering and Hydrodynamics, Australian Maritime College

University of Tasmania, TAS 7250, Australia

²Department of Mechanical Engineering

University College London, UK

Abstract

Model tests were conducted to investigate the global response of a conventional tension leg platform (TLP) due to wave-in-deck loads associated with extreme wave events in irregular long-crested waves of a cyclonic sea state. The experimental setup was designed to allow for the simultaneous measurement of wave surface elevations, rigid body motions, tendon tensions, as well as the pressure distribution at the model's deck underside. The obtained results demonstrated the variability of all the measurements and provided insights into the effect of wave-in-deck loads on the platform behaviour, tendon tensions and slamming pressures and showed qualitative correlations between these parameters. Based on the repeated tests in several events with different wave parameters, general observations and conclusions were made with respect to the platform dynamics during the deck impact, tendon tensions, slack tendon situations, tendon ringing and local impact pressures. The results of this study could be used for calibrating computational fluid dynamics (CFD) tools.

Keywords: Extreme waves; cyclonic conditions, tension leg platforms; wave-in-deck loads; dynamic response.

1. Introduction

In recent years, much effort has been made to investigate wave-in-deck impact problems in offshore platforms through experimental and numerical methods or a combination of both. Nevertheless, the current engineering knowledge required to accurately predict the magnitude and distribution of wave-in-deck loads and the resulting global response of a floating structure remains limited (Scharnke and Hennig, 2015, Lee et al., 2014, Hirdaris et al., 2014, Rudman and Cleary, 2013).

In the 2004 – 2005 year period, hurricanes *Ivan*, *Katrina* and *Rita* in the Gulf of Mexico destroyed 126 offshore structures and severely damaged 183 other structures (Kaiser et al., 2009). The reported damage suggests that during tropical storms or hurricanes the wave height exceeds the design height for many existing offshore structures. Most recently, in December 2015, the living quarters of 50 workers of an offshore drilling rig in the North Sea were damaged when an extreme wave hit the accommodation block leaving one person dead and two more injured (REUTERS, 2016). It has been found that these deck impact events occur more frequently than have been predicted using theoretical methods (Naess and Gaidai, 2011).

The majority of cited research conducted on wave impact on offshore decks has focused on investigating simplified deck boxes or flat plates. However, under deck structures, such as columns and pontoons, can affect the force magnitude and its distribution on the upper deck structure. Owing to the hydrodynamic interaction between the columns and pontoons of a multi-column platform such as tension leg platform (conventional TLP), the diffraction and radiation effects can cause the wave elevation to increase and locally impact the lower deck (Niedzwecki and Huston, 1992, Scharnke and Hennig, 2015, Abdussamie et al., 2016a). Niedzwecki and

Huston (1992) found that column spacing plays a major role in the wave upwelling underneath the deck and thereby it may affect the vertical wave-in-deck force. Abdussamie et al found that the deck-column intersection areas of a fixed TLP model under the action of long-crested irregular waves experienced larger wave-in-deck slamming pressures than the middle areas of the deck underside. Scharnke and Hennig (2015) investigated the effect of substructures on the wave-in-deck load magnitude by attaching a box-type deck structure to a square column. It was found that the column presence had a significant effect on the magnitude of global vertical forces and local pressures; the load magnitudes were significantly increased. With the column present, the upward peak of the vertical wave-in-deck force increased to more than double the maximum load measured without the column.

Wave-in-deck slam events may produce major global and local loads on floating offshore structures. Global loads can generate large forces in the tendons and risers and adversely affect the floating structure's motions, whilst local loads can cause structural damage to the deck and equipment impairing the safety of operation and life on-board (DNV, 2009). A significant part of the tendon tension experienced by a TLP during storm conditions can be associated with the ringing response, which is a narrow band process due to low damping in heave motion (Johannessen et al., 2006, Hennig et al., 2011). Thus, there is a need to investigate the dynamic behaviour of a TLP installation due to wave-in-deck slam events.

Among the known theoretical approaches, the momentum method developed by Kaplan (1992, Kaplan et al., 1995), has been used extensively to estimate the wave impact and slamming loads on fixed offshore platforms. For instance, the method has been applied for the analysis of wave impact on decks of Gravity Based Structures (GBS) (Baarholm and Stansberg, 2005) as well as other fixed offshore

platforms (Baarholm, 2009, Baarholm and Faltinsen, 2004). The use of the momentum method is also recommended by classification societies for analysing wave impact forces on decks of floating platforms. Baarholm et al. (2001) investigated theoretically an extreme wave impact on the deck of a semisubmersible platform due to regular waves. The authors used a Wagner based approach to account for the platform motions and Stokes second order wave theory to describe the incident waves. The panel code WAMIT was used to obtain the transfer functions for the linear induced motions. The authors concluded that the deck impact caused a significant suction force which led to a large downward heave motion. With application to fixed structures, attempts have been made to predict the slam pressure and its distribution through the deck area using the linear wave theory. Wang (1970) developed a theoretical formula for the impact pressure on a flat plate of negligible thickness, which demonstrated good qualitative agreement with the pressure measured in model tests. The limitations of the momentum and similar methods are related to its use of wave kinematics of a non-disturbed wave field or otherwise relying on the potential flow theory for an incompressible fluid; this implies that no consideration is given to the effect of trapped air or viscous effects.

Methods based on the computational fluid dynamics (CFD) have therefore received an increasing amount of attention in recent years. Commonly used commercial codes such as STAR-CCM+ and ANSYS FLUENT are available for modelling and solving wave-in-deck impact problems using the volume of fluid (VOF) method to capture free-surface hydrodynamic flows (CD-Adapco, 2012, Fluent, 2009). Nevertheless, CFD-based techniques have still limited acceptance for practical use for modelling a moored floating body subjected to extreme waves in an irregular sea state.

Model tests have previously been carried out to estimate wave-in-deck forces on different types of offshore structures. Model tests remain arguably the best approach for estimating wave-in-deck loads (Scharnke et al., 2014). The vast majority of published work has been focused on measuring global wave-in-deck impact forces on simplified deck boxes or flat plates fixed in space and subjected to regular waves (Bhat, 1994) and random waves (Sun et al., 2011). On the other hand, investigations of typical multi-column floaters are scarce. Furthermore, most investigations conducted on such structures are subjected to project confidentiality requirements and are therefore not available in the public domain. Experimental examination of wave-in-deck impacts on floating offshore structures seems to have started in the mid-2000's. Among few studies, Johannessen et al. (2006) and Hennig et al. (2011) investigated the dynamic air gap, wave loads and response of TLP models under extreme wave conditions. Both investigations reported that a wave-in-deck event can lead to an additional extreme response mechanism, and a step change in the extreme loading was noticeable due to such events. At the same time, the distribution of the wave-in-deck slam pressure around the forward and aft columns of a multi-column floating platform and its correlation with the global loads, including the tendon tensions, has not been systematically studied. Reports of accurate measurements and prediction of global loads and dynamic response of floating offshore structures due to wave-in-deck impact events are extremely limited. As the CFD-based techniques for the prediction the dynamic response of a moored floating body continue to be developed (for instance, an overset mesh technique (Chen et al., 2008)), experimental wave-in-deck data are necessary to validate the CFD simulations and to provide information that can be used in the design of such platforms.

The objective of the present study is to investigate the global response of a conventional TLP due to wave-in-deck impacts by performing model tests under several different extreme wave events and their repeated realisations. The study is focused on providing both qualitative and detailed quantitative insights into the wave-in-deck impacts, rigid body motions, tendon tensions and deck slam pressures and their correlation. The response of a TLP model was examined in several irregular wave events with different wave kinematics, which were taken from a typical 10,000-year return period cyclonic sea state at the Australian North West Shelf. By conducting tests for several wave events with repeated realisations, the study aims at estimating the variability of the measured platform responses and providing conclusions which may be broadly applicable to many floating structures of this type. The present study also aims at providing detailed results which can be used for calibrating global performance analysis software and CFD simulations. To enable the model test results to be used for the comparison with future numerical simulations, detailed information is presented on the model and the results, including the wave elevations measured at different wave probes. More detailed information, such as the time series of the measured wave elevations, is also available. One approach that can be used to numerically simulate the results of this experimental investigation is the focused wave technique, also known as the NewWave theory, developed by Tromans et al. (1991). Although most reported investigations have used the focused wave technique to investigate the response of fixed structures, e.g., Westphalen (2011) and Deng et al (2016), Ransley (2015) has demonstrated that a similar approach can be applied to investigate the dynamic response of a floating moored structure. Such technique requires the time history of wave elevation at a point which is provided in this paper and in the Research Gate page of the first author

(Abdussamie, 2017). CFD users should note while the measured wave time history can be reconstructed by using a superposition of linear wave components through direct Fourier transform, the linear wave components obtained will not produce the correct wave at the model location due to nonlinear wave interactions. An iterative technique is therefore required to adjust the amplitude and phase of each wave component to reconstruct the target wave time history at the desired location. For more details about this technique, please refer to Wu et al. (2014).

The material is set out as follows. Section 2 describes the TLP model, instrumentations and model testing procedure. Section 3 describes the wave conditions selected for this study, which are representative of the 10,000-year return period cyclonic sea state in the Australian North West Shelf. Section 4 presents the experimental setup and the results of free decay tests in different degrees of freedom. Section 5 introduces uncertainty analyses of experimental data of wave, forces and slam pressures. Section 6 discusses the obtained results of the model's dynamic response, tendon tensions and the slam pressure distribution. Supplementary time histories of different wave realisations and the corresponding surge motions and loads are given in the Appendix.

2. Model and Instrumentation

2.1 Model Testing Facility

The model tests were conducted at the Australian Maritime College towing tank, which is 100 m long and 3.55 m wide and can be operated at a maximum water depth of 1.5 m. The towing tank is equipped with a wavemaker for generating regular and irregular waves of different spectral properties, within the range of wave heights of 0.05 – 0.3 m and wave periods 0.6 – 3.5 s. To examine the platform response and

its dependency on the wave properties, neither wind nor current conditions are modelled.

2.2 TLP model

The 1:125 scaled model based on the SNORRE-A tension leg platform (Almeland et al., 1991) has been tested, with the platform deck modelled as a box-shaped structure. The main particulars of the platform at full scale and model scale are given in Table 1 and Figure 1. Due to the limitation of the maximum water depth in the towing tank (1.5 m), the scaled water depth does not represent the actual water depth at SNORRE-A location. Whilst the axial stiffness of the TLP tendons was modelled to represent their actual full-scale length (307.0 m) the modelled water depth corresponded to a full-scale water depth of 187.5 m. This approach is considered acceptable since this study aims at investigating the hydrodynamic deck loads of a generic TLP platform rather than the response of a specific TLP installed at a specific water depth.

As the objective of this investigation is to get an insight in typical wave-in-deck events, the height of the deck of the scaled TLP model had to be defined carefully. In order to achieve a sufficiently large number of impact events in an irregular sea state waves (DNV, 2010), the static deck clearance of the platform is set to 15.0 m (120 mm in model scale), which is reduced by 12.0 m (92 mm in model scale) compared with the prototype. This modification is a compromise adopted to ensure a sufficient number of wave impact events could be observed and analysed during the model tests, even though the frequency of such events will be higher than that for the actual full-scale platform in the same sea state. The differences in deck clearance between the SNORRE-A platform and the model used in this investigation

are illustrated in Figure 2. The frequency of expected wave impacts is further discussed in Section 3.

Table 1: Key particulars for the SNORRE-A TLP at full and model scales.

Parameter	Full scale	Model scale (1:125)	Tested model scale
Column diameter, D	25.00 m	200 mm	200 mm
Pontoon size, $h \times w$	11.50 $\times$ 11.50 m	92 $\times$ 92 mm	92 $\times$ 92 mm
Column spacing, s	76.00 m	608 mm	608 mm
Column height	63.00 m	504 mm	505 mm
Deck size, $L \times B \times h_d$	124.50 $\times$ 92.00 $\times$ 15.00 m	996 $\times$ 736 $\times$ 120 mm	608 $\times$ 608 $\times$ 210 mm
Deck clearance, a_0	27.00 m	216 mm	120 mm
Platform's draft, d	38.125 m	305 mm	305 mm
Displacement, Δ	101840 t	52.15 kg	52.15 kg
Total mass, M	77640 t	39.75 kg	39.75 kg
Initial pretension per leg, T_0	6055 t	3.10 kg	3.10 kg
Number of tendon per leg, n	4	4	1
Total tendon length at zero offset,	307.00 m	2456 mm	1195 mm
Axial stiffness per leg, nEA/L_0	2.42×10^8 N/m	15.49 N/mm	15.80 N/mm
Riser tension	3320 t	1.70 kg	1.70 kg
Centre of gravity, $C_g (x, y, z)$	n/a	n/a	(0.0, 0.0, 5.0) mm
Mass moment of inertia (I_{xx}, I_{yy}, I_{zz})	n/a	n/a	(5.23, 5.23, 5.63) kg.m ²
Water depth	310.00 m	2480 mm	1500 mm

The model was divided into two modules, namely a hull module (columns and pontoons) and a topside deck module. Having these separate modules allowed testing of the deck individually and the deck and hull as a combined structure (Abdussamie et al., 2016a, Abdussamie et al., 2016b). The model was designed to be as stiff and as watertight as possible. As overtopping on columns was expected, the column tops were tightly closed. A 100 mm tall acrylic bulkhead was mounted on top of the aluminium sides to prevent green water ingress onto the deck space, as can be appreciated in the overall view of the TLP model presented in Figure 3.

Inclining experiments and bifilar tests were conducted to determine the vertical centre of gravity and mass moment of inertia, as given in Table 1. The riser tension was modelled by a 1.70 kg lumped mass located 515 mm above the keel at the platform centre (see Figure 6b). The location of this concentrated mass was selected to represent the riser tension at the deck underside of SNORRE A.

Figure 1: TLP model particulars: (a) top view; (b) profile view [not to scale].

Figure 2: One-quarter of SNORRE TLP Deck and Hull showing a cross-section of the original and modified deck clearance given at model scale: (a) Original deck; (b) Modified deck.

Figure 3: Photograph showing the TLP model (waves propagating from right to left).

2.3 Tendon system

In order to represent the mooring system of the SNORRE-A TLP, i.e., four tendons at each corner, one single tendon per corner was used at model scale with equivalent stiffness. The tendon rotation points at the TLP model end were located at the column base by installing a 3 axis hinge in each column as shown in Figure 4. The anchor point of each tendon was fixed on the tank floor. The actual axial compliance of the four SNORRE-A TLP tendons was modelled using custom stainless steel springs representing the appropriately scaled stiffness. The light-mass

spring with the axial stiffness of 15.80 N/mm was installed between a 3.20 mm stainless steel wire rope and an anchor base (Figure 4). For Leg#1 and Leg#4, the spring was connected to the wire rope and a waterproof load cell. A plastic anchor block provided a strong fixture for the tendon to the tank floor. In order to adjust the initial pretension, each tendon was connected to a 1.20 mm wire run through the anchor base block to an adjustable turnbuckle attached to the tank side; hence providing a mechanism to remotely control tendon pretensions. The tendon pretension is $T_0 = 30.4$ N.

Figure 4: Profile view of the TLP model setup.

2.4 Instrumentation

The location of the five wave probes (WP) is presented in Table 2 (coordinate system is shown Figure 5). Wave probes WP1 – WP3 measure the wave height of the incident incoming waves travelling in the positive x-direction. During wave impact tests, wave probes WP4 and WP5 were attached to the leading and trailing edges of the topside deck.

Table 2: Location of wave probes used in the model tests with respect to the model's centroid.

Wave probe (WP)	Location (x, y) without the model (m)	Location (x, y) with the model (m)
1	(-10.000, 1.280)	(-10.0, 1.280)
2	(-5.000, 1.280)	(-5.0, 1.280)
3	(-1.000, 0.000)	(-1.0, 0.000)
4	(-0.404, 1.200)	(-0.304, 0.000) moving with the model
5	(0.000, 1.2000)	(0.304, 0.000) moving with the model

Figure 5: Plan view of the AMC towing tank showing the distribution of wave probes (WP) with the TLP model in-place [not to scale].

The model's surge motion was measured by a MagneRule magnetostrictive linear displacement transducer (MLDT), as illustrated in Figure 6 (b). In addition, an MTi-30 Xsens, six degrees of freedom motion measurement system was installed on the TLP model to measure the translational acceleration components as well as the model's pitch motion. The objective of this particular measurement system was to determine the peak pitch motion, which is associated with a wave impact event. This system was switched on simultaneously with the DAQ system, but its data set was not synchronised with the wave elevations, loads and surge data. In order to obtain the peak pitch motion caused by a wave-in-deck impact event, an approximate synchronisation was performed by comparing the time history of pitch response with the wave elevation and surge motion time histories, and with the video recording.

This way, although it was not possible to ensure the temporal precision of the peak pitch event, the magnitude of extreme pitch angle within the cycle of a wave-in-deck impact event was identified.

Figure 6: Instrumentation layout: (a) distribution of pressure transducers (PT) on the bottom plate; (b) profile view showing the instrumented deck structure by Xsens accelerometer and the MLDT.

Only two tendons were instrumented by two FUTEK submersible S-beam junior load cells, see Figure 4, one up-wave tendon and one down-wave tendon (denoted by Leg#1 and Leg#4). The underside of the topside deck structure was instrumented by sixteen piezoresistive pressure transducers (PT). The tip of each transducer (approximately 4.0 mm in diameter) was mounted flush with the underside of the deck. The pressure transducers were distributed over two main regions: forward (FWD) and aft (AFT) (Figure 6). The area around the forward column (C2) was instrumented by PT#1 – PT#4, whilst PT#13 – PT#16 measured wave impact pressures near the aft column, C3. The remaining pressure transducers, PT#5 – PT#12, were installed in the mid-span area. By referring to Figure 6 four zones along and across the deck underside were instrumented by four pressure transducers each. Table 3 shows the definition of each zone. This arrangement of local pressure transducers will enable the detailed pressure distribution to be established.

Table 3: Definition of pressure zones at the deck underside.

Zone	Definition	Pressure Transducers (PT)
I	Around forward columns	1, 2, 3, 4
II	Forward middle section	5, 6, 7, 8
III	Aft middle section	9, 10, 11, 12
IV	Around aft columns	13, 14, 15, 16

High-speed cameras were used to capture both photographs and videos in various instants of several wave-in-deck impact events.

3. Wave Conditions

3.1 Sea State

The sea state used for the model testing was representative of the 10,000-year return period cyclonic storm in Australia's North West Shelf. The sea state was modelled by the JONSWAL spectrum with the significant wave height $H_s = 22.13$ m, peak period $T_p = 17.0$ s ($T_p / \sqrt{H_s} = 3.61$), and the peak shape parameter $\gamma = 1.0$, which yields the Pierson-Moskowitz spectrum. The corresponding parameters at model scale 1:125 are $H_s = 177$ mm, $T_p = 1.52$ s. The Long-crested sea state is assumed, with no effects of wind or current.

It should be noted that be the full-scale TLP studied in these model tests does not necessarily represent the best design solution in particular with respect to its static deck clearance and its exposure to a harsh sea state. In fact, the model dimensions (refer to Section 2.2) and the sea states have been selected to ensure that wave-in-deck events do occur more than once in the 10,000-year storm. Although this would be opposite to what a designer would like to achieve, such

selection enables the wave-in-deck events to be investigated within wave trains of a reasonably short duration, less than the 3-hour design storm and featuring different wave properties.

3.2 Wave Trains and Calibration

Such short-time irregular wave trains were synthesised by the wavemaker using an iterative wave calibration process, which was conducted without the model in the tank. The process involved running a single random wave realisation initially for approximately 22 minutes (120 s in model scale) using a sampling frequency of 200 Hz for wave probes. The wave realisation would be selected for the subsequent tests if it had at least one wave crest height exceeding the static air-gap $a_0 = 120$ mm (15.0 m full scale) at wave probes WP3 – WP5, which coincided with the deck edges. Nine (9) wave realisations, each approximately 450 s long (40 s in model scale), have been selected which contained eight (8) wave exceedance events.

Although this study does not aim at investigating a multitude of possible wave-in-deck events, the selected wave trains can be considered as a sample with meaningful probabilistic interpretation. Based on the Forristall short-term distribution of wave crests (DNV, 2010), it is expected that on average 46 wave crests will exceed the static air gap $a_0 = 15.0$ m in this sea state over a 3-hour storm duration. Therefore, nine randomly selected realisations correspond to 17.4% of all wave crests exceeding the static deck level at a given location. This selection is considered to be sufficient for making generalisations with respect to the TLP responses induced by the wave-in-deck impacts. Although broadening the range of wave events would provide more confidence in the findings, this would require model tests with longer wave trains (with the potential effect of the reflected waves) or reduce the static deck clearance (with the TLP model being less representative of a

practical design solution). The selected combination of the model dimensions, the sea state and the wave trains represent a reasonable compromise for the purpose of this study.

4. Experimental setup

4.1 Model setup

The TLP model was set up on the tank centreline with its centroid ($x = y = 0.0$) located 15.0 m away from the wavemaker (Figure 5). The remaining 85.0 m of towing tank allowed for sufficiently long run times without interference from reflected waves (Abdussamie et al., 2014). A sampling frequency of 20 kHz was adopted for all channels in order to capture the short-duration slamming pressures. Twenty-four channels (1 for linear displacement transducer, 2 for load cells, 16 for pressure transducers and 5 for wave probes) sampled at 20 kHz produced a data file of approximately 220 MB for 40 s of acquisition time.

4.2 Natural periods and damping

Decay tests were conducted for the TLP-tendon system; the logarithmic decrement method was used to determine the damping ratios. The natural periods of the TLP model were compared with the full-scale values obtained from (Johannessen et al., 2006), see Table 4. A large difference in the surge natural period was found, as expected, due to the water depth (and tendon length) not being modelled to scale. Heave and pitch natural periods agree with the full-scale data within 10% and 3.7%, respectively.

Table 4: Natural periods and damping ratios of the TLP.

Motion	Full scale [s]	Model: target [s]	Model: tested [s]	Model : Damping [-]
Surge	84.0	7.513	5.660	0.106
Heave	2.3	0.205	0.225	0.023
Pitch	2.4	0.214	0.222	0.123

4.3 Test matrix

With the TLP model being in the tank the wave parameters for each wave event (WE#) were derived from the time history of WP3 (Figure 5). The crossing analysis was employed to estimate zero crossing period, T_z , crest height, η_c , and crest to trough height, H , see Figure 4. Table 5 summarises these parameters where λ is the wavelength estimated from the dispersion relationship. The generated wave events are non-breaking at WP3 as indicated by the wave steepness ($S = H/\lambda$). The phase celerity, C , was estimated by λ/T_z for each wave event. Also indicated in the table is the horizontal velocity, u , at the crest calculated using the Stokes second order wave theory at $z = \eta_c$. Although the Stokes theory may not be accurate in predicting the kinematics of extreme waves (Scharnke et al., 2014), yet, this horizontal velocity is employed as an approximate measure for comparison between the wave events.

Table 5: Wave event parameters extracted from WP3 with the TLP model in-place.

Wave event (WE#)	H (mm)	η_c (mm)	T_z (s)	λ (m)	C (m/s)	u (m/s)	S (-)
1	231	145	1.48	3.39	2.29	0.65	0.068
2	260	163	1.37	2.92	2.13	0.85	0.089
3	238	171	1.65	4.16	2.52	0.60	0.057
4	227	137	1.35	2.84	2.10	0.72	0.080
5	186	156	1.76	4.67	2.65	0.42	0.040
6	168	126	1.73	4.53	2.62	0.37	0.037
7	191	144	1.44	3.22	2.24	0.55	0.059
8	261	160	1.46	3.31	2.27	0.77	0.079

5. Uncertainty analyses

The uncertainty of the measured TLP responses in both time and magnitude was estimated by running several (up to five) repeats for each of 9 wave realisations and assessing the variability of the results for the waves and the responses. As an example, four runs of the wave realisation that contained two wave events WE#2 and WE#3, are shown in Figure 7, is described below in detail. Two deck impacts caused by wave events WE#2 and WE#3 can be observed at time = 5.0 s – 7.0 s

(WE#2) and at time = 23.0 s – 25.0 s (WE#3). Three more wave crests in this time history exceeded the static deck clearance without severely impacting the deck.

The four measured time histories of the surge motion are presented in Figure 8 and the corresponding tendon tensions are presented in Figure 9 for the up-wave (Leg#1) and the down-wave (Leg#4) tendons of the model. Qualitatively, all global responses show limited variability between the repeated runs. In contrast, the localised pressures measured at discrete points of the deck are found to have much higher variability in space, time, magnitude and duration. This can be seen in Figure 10, where the time series of pressure transducers PT#8 (mid-span region) and PT#16 (aft region of the deck) are shown for WE#2. Although the time histories of both pressure transducers show a typical trend of the impact pressure signal, i.e., a rapid increase in magnitude followed by a slow reduction, the differences are obvious.

Figure 7: A short-time history of wave elevation measured by WP3 at 1.0 m from the model's centroid using four repeated runs.

Figure 8: Time series showing surge motion measured using four repeated runs.

Figure 9: Time series showing tension in the platform's tendons measured using four repeated runs: up-wave tendon (top); down-wave tendon (bottom).

Figure 10: Time history of wave-in-deck pressures due to wave event WE#2 [$H = 260$ mm, $T_z = 1.37$ s] measured in four repeated runs: at PT#8 (top); at PT#16 (bottom).

The peak values of the measured wave elevations at WP3, the maximum and minimum tendon tensions (denoted by $T_{\max}$ and $T_{\min}$), and the slamming pressures (P_i) at PT#8 and PT#16 are summarised in Table 6 – Table 8, respectively, for the four test runs. The mean values, standard deviations and coefficients of variation (CV) are presented. The CV values for the peak wave elevations are of the order of 2.5% for the positive and 1.5% for the minimum wave elevations. The maximum CV value was found to be less than 3.0% for all wave events reported in this paper which demonstrates a good repeatability of the wavemaker. The dynamic components of the maximum and minimum tendon tensions (the initial pretension was removed: dynamic tension = total tension – pretension) show similar variability for WE#2 (within 2.8%) and larger variability for WE#3, with the negative tensions varying significantly more than the positive ones.

Table 6: Uncertainty analysis of wave crests and troughs (mm) at WP3 using four repeated runs for wave events WE#2 and WE#3.

Run id	WE#2		WE#3	
	WP3(+)	WP3(-)	WP3(+)	WP3(-)
1	158	-100	163	-68
2	162	-97	169	-67
3	163	-98	171	-69
4	168	-100	170	-67
Mean (mm)	162.75	-98.75	168.25	-67.75
σ (mm)	4.11	1.50	3.59	0.96
CV (%)	2.53	1.52	2.14	1.41

Table 7: Peak values of the dynamic tension (N) measured in the up-wave tendon (Leg#1) and down-wave tendon (Leg#4) using four repeated runs for wave events WE#2 and WE#3.

WE#2 [$H = 260$ mm, $T_z = 1.37$ s]									
Leg#	Tension	Run 1	Run 2	Run 3	Run 4	Mean	σ	CV (%)	α (-)
1	$T_{\max}$	47.5	49.8	49.2	50.8	49.3	1.38	2.81	1.11
	$T_{\min}$	-23.8	-23.3	-24.6	-23.3	-23.8	0.61	2.58	1.70
4	$T_{\max}$	31.0	29.9	30.2	31.7	30.7	0.81	2.65	1.05
	$T_{\min}$	-28.3	-28.5	-28.5	-29.1	-28.6	0.35	1.21	0.80
WE#3 [$H = 238$ mm, $T_z = 1.65$ s]									
1	$T_{\max}$	29.7	30.2	27.8	31.2	29.7	1.43	4.80	2.2
	$T_{\min}$	-9.6	-11.7	-7.8	-12.8	-10.5	2.22	21.22	15.1
4	$T_{\max}$	18.1	18.4	21.2	18.7	19.1	1.42	7.44	3.5
	$T_{\min}$	-13.0	-14.8	-13.5	-17.3	-14.7	1.92	13.12	9.3

The magnitude of the impact pressure was found to vary among runs with a standard deviation of approximately 1.0 kPa for PT#8 and 0.122 kPa for PT#16 (Table 8), which corresponds to the CV of up to 9%, or about 3 times higher than that for the maximum wave elevation in the same event.

Table 8: Impact pressures, P_i , [kPa] measured in four repeated runs at PT#8 and PT#16 due to wave event WE#2 [$H = 260$ mm, $T_z = 1.37$ s].

PT#	Run 1	Run 2	Run 3	Run 4	Mean	σ	CV (%)	α (-)
8	12.08	11.96	12.32	10.05	11.6	1.05	9.00	3.56
16	1.34	1.62	1.57	1.51	1.51	0.12	8.00	3.16

The differences in the variability of the measured responses are expected and they can be related to the response physical non-linearity. The highly non-linear

responses are bound to have higher uncertainty and are therefore more difficult to reproduce accurately. In fact, any TLP response X may be considered as a probabilistic variable which depends on the wave elevation Z in the generic form:

$$X = K(a, b, c, \dots)Z^\alpha \quad (1)$$

Here $K(a, b, c, \dots)$ is the coefficient, which depends on all physical parameters of the model and a particular wave event, excluding the wave elevation Z . By linearizing the above function in the vicinity of its expected value and taking its variance, the following relation can be shown:

$$CV(X) \approx \alpha CV(Z) \quad (2)$$

Therefore, although the exact functional form of the response is unknown, the extent of its nonlinear dependence on the wave elevation (or other wave properties proportional to wave elevation) can be inferred from the measured CV values. The power values, α , are also shown in the respective tables. It can be seen that the maximum tendon tensions behave approximately linear with the wave elevation in WE#2 whilst higher non-linearity is inferred for WE #3, especially for the minimum tensions. Similarly, the CV for the impact pressures (Table 8), behave non-linearly and are consistent with the power α between 3 and 4. The variability of the impact pressure measured by all transducers in different test runs can be seen from the boxplot produced in Figure 11 for wave event WE#2. A particularly high variability (CV up to $\approx 70\%$ or α up to 30) was obtained for the forward part of the deck, and pressure locations PT#1 and PT#6. This indicates an extremely high non-linearity and that a larger number of test runs are required to produce more consistent values of the impact pressure for such locations. It is worth mentioning that the presence of

small scale hydrodynamic flow instability and turbulence might have a role in the observed variability in the measurements of wave-in-deck slamming pressure at a discrete point. Based on the platform column diameter Reynolds number was estimated to be 1.7×10^5 and 1.2×10^5 for WE#2 and WE#3, respectively. Boxplots corresponding to all wave events analysed in this study are given in Appendix.

Figure 11: Boxplots showing variation in impact pressure at different pressure transducers due to wave event WE#2 [$H = 260$ mm, $T_z = 1.37$ s].

6. Results and discussion

A complete set of results for all wave events, including time histories of wave elevations at deck leading edge (LE) and trailing edge (TE), surge motion of the platform and tendon tensions are presented in Appendix. In this section, only selected results are discussed to support the interpretation the observed TLP behaviour.

6.1 Model's dynamics due to wave-in-deck impact

Time histories of the wave elevations at the deck leading and trailing edge, LE and TE, platform surge motion and tendon tensions are shown in Figure 12 for wave

event WE # 1, as an example. For the interpretation of the platform dynamics, it is convenient to introduce several parameters, which are schematically illustrated in Figure 13. In this figure, the position of the deck is defined in the local coordinate system (x, z) with its origin at the deck LE in the static condition. The following parameters are defined:

- t_o is the initial time of contact when the wave comes in contact with the LE.
- t_i is the time when the up-wave tendon experiences maximum tension in which the wave crest comes in contact with the LE.
- t_m is the end time of contact with the LE when the wave leaves the LE and propagates along the deck.
- t_f is the end time of contact with TE when the wave leaves the deck.
- $x(t)$ is the horizontal coordinate of the deck LE relative to the static condition at the corresponding time instances.
- Time of the up-wave tendon tension build up $dt = t_i - t_o$.
- Time of interaction with LE: $dt_{LE} = t_m - t_o$.
- Platform horizontal (surge) velocity at the initial contact U_o .
- Platform surge velocity at time of maximum tension in the up-wave tendon $U = dx/dt$;
- The relative horizontal velocity of the wave crest and the platform $u_r = u - U$. The horizontal velocity of the wave crest used in this parameter is calculated approximately (Section 4.3), which is sufficient for the purpose of comparing it with the surge velocity of the platform.

With reference to Figure 12 and Figure 13, the behaviour of the platform due to the wave-in-deck event can be described in terms of the four stages:

- At time $t_o = 31.74$ s (Figure 12), the wave contacted the deck LE at $z = a_o = 120$ mm. The deck was at $x_o = -61.28$ mm as the model was offset towards the wave and moving in the positive x -direction (along with the wave) with $U_o = 0.09$ m/s. The up-wave tendon (Leg#1) came under increased tension $T' = T_o + \Delta T \approx 37.40$ N.
- At time $t_i = 31.90$ s (Figure 12), the up-wave tendon came under maximum tension ($T_{max} = 48.00$ N) when the wave crest was still in contact with the deck LE at $x_i = -19.95$ mm. The model was now moving with a higher velocity $U = dx/dt \approx 0.30$ m/s and the relative horizontal velocity ($u_r = u - U$) between the wave crest and the model was 0.39 m/s. At time $t_m = 32.03$ s, the wave crest was leaving the deck LE, which was at $x_m = 21.40$ mm. During the time interval $[t_m - t_i] \approx 0.13$ s, the tension in the up-wave tendon decreased rapidly to approximately the same value T' that was experienced at the initial contact. As such, the impulse-like loading in the up-wave tendon lasted for 0.28 s at model scale (3.13 s at full scale).
- At time $t_f = 32.03$ s (Figure 12), the wave was tangentially leaving the deck TE, which was at $x_f = 93.40$ mm. Hence the platform travelled 154.68 mm (or 19.33 m at full scale) in wave direction over the duration of wave impact; this surge motion represents only 4.5% of the wave length. The down-wave tendon (Leg#4) was under very low tension (3.60 N) while the tension in the up-wave tendon also reduced (24.93 N) and the model experienced large pitch motion of approximately 0.80° .

It can be seen in Figure 12 that the minimum tensions in both tendons occurred after time t_f when the down-wave tendon became slack. This was followed by a rapid increase in tension and a number of ringing oscillations in the down-wave tendon. The up-wave tendon also showed ringing response with smaller amplitudes.

Figure 12: Simultaneous measurements corresponding to wave event WE#1 [$H = 231 \text{ mm}$, $T_z = 1.48 \text{ s}$]: wave elevations at WP4 and WP5 and surge motion (top); tension in the up-wave and down-wave tendons (bottom).

Table 9 summarises all the key parameters of the wave and model response for all wave events averaged over multiple repeated runs. The following observations were made:

- In all wave impact events, at the time of the initial contact of the wave with the deck, the model was always moving in the positive x -direction; the model velocity U_o was the range of $0.09 - 0.32 \text{ m/s}$. Even if the platform was offset towards the waves, it was still moving with the waves. This behaviour was likely to be caused by the wave-induced hydrodynamic forces on the columns and pontoons immediately prior to the deck impact.

Figure 13: Sketch definition showing the interaction between wave event WE#1 and the topside deck structure both moving in the positive x-direction. The time sequence is given from top to bottom [not to scale].

Table 9: Parameters of wave and model response during wave-in-deck impact.

Wave event (WE#)	T_z (s)	u (m/s)	x_o (mm)	x_i (mm)	dt (s)	U_o (m/s)	U (m/s)	u_r (m/s)	dt_{LE}/T_z (%)
1	1.48	0.65	-61.28	-19.95	0.16	0.09	0.26	0.39	19
2	1.37	0.85	-3.44	20.64	0.06	0.32	0.37	0.48	9
3	1.65	0.60	27.17	62.59	0.09	0.30	0.39	0.21	9
4	1.35	0.72	10.88	34.38	0.09	0.24	0.27	0.45	11
5	1.76	0.42	-33.46	-15.27	0.12	0.09	0.15	0.27	16
6	1.73	0.37	-55.83	-36.55	0.08	0.14	0.24	0.13	10
8	1.46	0.77	-47.43	-5.86	0.14	0.16	0.30	0.47	20

- In all wave events, the model's surge velocity increased to a higher value of $U = 0.15 - 0.39$ m/s during the active phase of the wave-in-deck event (dt). As a result, the relative horizontal velocity, u_r , between the wave crest and the deck was always smaller compared with the initial moment, and with a similar situation for a fixed structure. This reduction in the relative velocity was of the order of 50% on average, compared with the wave particle velocity u in the undisturbed wave crest.
- On average, the wave remained in contact with the deck LE over the time of approximately 13% T_z , and during this time, the up-wave tendon experienced its peak loading.
- Similar wave events (WE#2 and WE#8) were found to cause similar model's dynamics in terms of the relative velocity. However, differences in dt_{LE}/T_z were obtained, which could be attributed to the difference in T_z and the initial position x_o between various wave events.
- In all wave events tested, the wave crest exceedance measured at the deck leading edge was always higher than that at the trailing edge. This indicates the presence of diffraction (distortion of the impacting wave profile) caused by the deck itself.

Figure 14 shows the interaction between WE#1 and the model during the water-entry and the water-exit phases.

Figure 14: Photograph showing wave impact at the TLP model due to wave event WE#1: (1) water entry at time $\approx t_0$; (2) water exit at time $\approx t_r$ (wave propagating from right to left).

6.2 Slack tendon situations

The slack tendon situations were observed in the down-wave tendon due to wave events WE#1, WE#2 and WE#8. The time period during which the down-wave tendon remained slack (t_{slack}) was found to be between 0.25 s and 0.34 s at model scale or 3 – 4 s in full scale (refer Figure 12, Fig.A 3, and Fig.A 15); these times are summarised in Table 10. Consistent with the slack tendon measurements, a relatively large pitch response was measured with the maximum pitch angles in the down-wave direction between 0.65° and 0.80° . Johannessen et al. (2006) have also observed a large pitch angle (approximately 0.3°) during model testing of SNORRE A TLP when the model was subjected to a large deck exceedance. Furthermore, Johannessen et al. conducted CFD simulations for SNORRE A TLP at full scale using two extreme regular wave conditions including $H = 27.9$ m and 36.4 m. At $H =$

36.4 m (approximately 3 m deck exceedance when wave diffraction and upwelling effects are considered), the platform pitch motion was found to be approximately 0.3°. Since the equivalent full scale deck exceedance of WE#1, WE#2 and WE#8 reported in the present investigation are larger than 3 m at full scale, which was approximately twice as large as that tested by Johannessen et al., the larger maximum pitch response are justified.

The measurements of tendon tensions, wave elevation at LE and TE suggest that these wave events must have caused significant downward forces on the model, which originated from the deck impact. Findings from other recent studies (Abdussamie et al, 2016; Scharnke et al, 2014; Scharnke and Henning, 2015) into the wave-in-deck impact problems of fixed decks identified the downward force on the deck alone, the magnitude of which can be as large as the upward force component. Scharnke et al (2014) and Abdussamie et al. (2016) attributed the large magnitude of the downward force to the added mass surrounding the deck structure, in both x and z directions, which is accelerated downwards at this time. This can be interpreted as a “suction force” due to substantial amount of water flowing downwards from the deck underside, when the wave leaves the deck after the impact. The instantaneous reduction in buoyancy of the aft columns subsequent to the deck impact could also be a contributing factor.

Table 10: Slack tendon situations in the down-wave tendon.

Waver event (WE#)	Minimum tension, $T_{\min}$ [N]	Slackness duration, t_{slack} [s]	t_{slack}/T_z [%]	Max pitch angle (°)
1	0.46	0.30	20	0.80
2	1.78	0.34	25	0.67
8	1.41	0.25	17	0.65

6.3 Tendon ringing response

In all wave events, the TLP model was found to experience high-frequency vertical motions with the period close to its natural heave period (0.225 s), known as “ringing”. The short-term transient ringing response was observed in both up-wave and down-wave tendons. The energy spectra of both tendon tensions for wave event WE#1 are presented in Figure 15, for the time window of 31.9 s – 40 s (starting from t_i in Figure 12). The figure shows significant energy around the heave natural frequency, whereas the spectrum of the wave elevation (measured by WP 4) has almost no content at this frequency. This indicates that the tendon ringing was caused mostly by the wave-in-deck impact.

Figure 15: Power density spectra of wave elevations (top) and tendon tensions (bottom) during and subsequent to the deck impact due to WE#1 [$H = 231$ mm, $T_z = 1.48$ s].

The extended set of results, presented in the Appendix, indicates that ringing response was presented in almost all wave events. In the cases when the TLP was subjected to a single wave-in-deck impact, the ringing was noticeable in the tendon time history only after the point of minimum tendon tension. In the rare cases where the TLP was subjected to two consecutive wave-in-deck impacts, the ringing

1 response caused by the preceding wave was found to be noticeable along the entire
2 time history of the second impact after the point of minimum tendon tension. In some
3 cases, the high-frequency content in the tendon tensions was detected before or
4 even without the wave-in-deck impact event. In these situations, it is rather difficult to
5 separate the ringing response caused by the wave-in-deck events from “springing”
6 response caused by the sum-frequency second order wave loading. Because such
7 analysis is outside the scope of this study, the high-frequency motions and dynamic
8 tensions of the platform will be generally referred to as “ringing” and more specific
9 explanations provided where possible.

10 In order to quantify the ringing response associated with each wave event the
11 following approach was used:

- 12 • The ringing duration was defined by the number of oscillations
13 observed in the time history of the tendon tension until the oscillatory
14 tension response approximately vanished;
- 15 • The maximum and minimum magnitude of each observed oscillation
16 were extracted and the tension range (T_r) calculated (T_r = maximum
17 tension – minimum tension); and
- 18 • The tension ranges were then normalised by the tendon pretension
19 (normalised ringing tendon tension $T_r^* = T_r / T_o$) and grouped according
20 to the number of occurrences.

21 Examples of the ringing response identified in wave events WE#1 – WE#8 for
22 the up-wave and down-wave tendons are presented in Figure 16.

Figure 16: Normalised ringing tension in the up-wave and down-wave tendons caused by the examined wave events versus the number of occurrences.

In most cases, as expected, the number of occurrences (N) was inversely proportional to the tendon tension range for both tendons. Wave events WE#3 and WE#1 caused the largest number of ringing tension occurrences, in particular in the up-wave tendons, with ringing tension range exceeding the 15% of the tendon pretension. A particular feature of wave event WE #3, as seen in Figure 7, was the second successive steep wave, which was the likely cause of a longer oscillatory heave of the platform. This observation revealed that whilst the platform may have

missed the second deck impact by the successive large wave, this wave may have largely contributed to the extended high-frequency tension response.

On average, the magnitude of ringing range in Leg#1 and Leg#4 was found to be almost the same over all wave events. On the other hand, the ringing response observed in the up-wave tendon (Leg#1) was seen to be more intense than that in the down-wave tendon (Leg#4). This observation correlates well with the higher values of slams pressure measured over the front section of the deck underside in most cases.

6.4 Maximum and minimum tension

The magnitudes of maximum and minimum tendon tension measured in repeated runs were averaged and summarised in Table 11 for all wave events. The maximum tensions in the up-wave and down-wave tendons corresponding to each wave event are of approximately the same level, except for wave events WE#1 – 3, without a clear trend of higher tension being experienced by the up-wave or down-wave tendon. The minimum tension in Leg#4 is significantly lower than that in Leg#1, particularly in wave events WE#1, WE#2 and WE#8, when the down-wave tendon became slack. In order to compare the extreme tensions, they were normalised using the tendon pretension, $T_o = 30.4$ N. The normalised maximum tension ($T^*_{\max} = T_{\max}/T_o$) and minimum tension ($T^*_{\min} = T_{\min}/T_o$) are shown in Figure 17 against the wave steepness. In most conditions, $T^*_{\max}$ appears to increase with the wave steepness, although the trend is not very noticeable. Notably, two extreme events WE#2 and WE#3 produced the maximum tendon tension of approximately 2.5 times the pretension. It is important to note that, out of all wave events studied, the maximum tendon tension occurred in the up-wave tendon in wave event WE#2,

which is characterised by the highest wave steepness rather than the highest wave crest.

With respect to the minimum tension, there is a slight trend for the down-wave tendon to experience less tension as the wave steepness increases. The minimum tension in the up-wave tendon does not show a noticeable change. As already mentioned, wave events WE#1, 2 and 8 caused lower minimum tension among other wave events which could be attributed to the large pitch angle observed during such wave events (see Table 10). Another observation is that out of all events studied, that minimum tendon tension occurred in wave event WE#1, which is characterised by moderate crest height and also moderate wave steepness. This indicates that the selection of a particular wave event which may produce the highest or the lowest tension (including the slack tendon situation), as may be required for the TLP design, is not a straightforward task, and a range of wave events or other special criteria may need to be considered.

Table 11: Average maximum and minimum tensions measured in the up-wave tendon (Leg#1) and down-wave tendon (Leg#4) for different wave events.

WE#	H [mm]	T_z (s)	S (-)	Tension in Leg#1		Tension in Leg#4	
				(N)		(N)	
				T_{max}	T_{min}	T_{max}	T_{min}
1	231	1.48	0.068	47.08	18.83	54.33	0.46
2	260	1.37	0.089	79.69	6.66	61.11	1.78
3	238	1.65	0.057	60.13	19.92	49.51	15.75
4	227	1.35	0.080	39.90	28.70	43.73	14.90
5	186	1.76	0.040	50.48	13.04	45.30	13.43
6	168	1.73	0.037	38.30	21.67	45.82	15.27
7	191	1.44	0.059	53.78	22.00	49.64	8.00
8	261	1.46	0.079	67.63	17.99	67.34	1.41

Figure 17: Average normalised tension ($T^*_{max} = T_{max}/T_o$, $T^*_{min} = T_{min}/T_o$, $T_o = 30.4$ N) versus wave steepness: up-wave tendon, Leg#1 (top); down-wave tendon, Leg#4 (bottom).

6.5 Wave-in-deck slamming pressures

The measured pressure values P_i were normalised by the hydrostatic wave pressure:

$$P_i^* = \frac{P_i}{\rho g \eta_c} \quad (3)$$

where ρ is the density of water, g is the acceleration due to gravity, η_c is the crest height for each wave events measured by WP3 in front of the model. The normalised maximum pressures averaged over the repeated runs are presented for all wave impact events in Figure 18 through Figure 21 for the deck zones I – IV, respectively (for the definition of the zones, refer to Table 3). When the pressure is considered as a function of the relative deck exceedance $\epsilon = 1 - a_0/\eta_c$, the increasing trend is evident as the relative exceedance increases, which corresponds to increasing wave crest height compared with the still water deck clearance a_0 . The same figures compare the model test results with the theoretical result obtained by

Wang (1970) for the maximum wave-induced uplift pressure on a horizontal flat plate. Wang's result for the maximum wave impact pressure reduces to a simple equation:

$$P_i^* = \frac{P_i}{\rho g \eta_c} = \pi \tanh(kd) \sqrt{1 - \left(\frac{a_0}{\eta_c}\right)^2} \quad (4)$$

where d is the water depth, k is the wave number ($= 2\pi/\lambda$) and λ is the wave length. For the individual wave events, these quantities are given in Table 5. Because Wang's treatment was limited to a fixed flat plate, its applicability to floating structures is in question. However, the comparison in Figure 18 through Figure 21 shows that the overall trend of the measured pressures is generally similar to that given by Wang's equation, even though a large spread of measured results is evident. A possible explanation for this observation may be in the fact that the vertical (heave) response of a TLP is always small and its horizontal (surge) excursion over the duration of the impact is also small compared with the wave length (Section 6.1). Therefore, although the wave-induced TLP responses do affect the impact pressure and Wang's equation is not be strictly applicable for each particular event, when several impact events with different wave properties and phases are considered the trend for the average deck impact pressure tends to become close to that for a fixed structure, but with a broader variability. Further work is required to confirm or dismiss this suggestion.

The experimental results indicate that the impact pressure in the forward part of the deck is higher than in the aft part except PT #1, 16 and #2, 15 (near the columns and ends of the deck) where this trend is reversed. By comparing pressure between the areas of forward and aft columns (PT #1, 16 and #2, 15), in most cases,

pressure near the aft end is higher than that near the front end (i.e., pressure at PT#16 is larger than that at PT#1; and similarly for PT#15 and PT#2). This could be caused by the wave upwelling being larger around the aft columns and/or the effect of platform set-down as the platform offsets.

Figure 18: Normalised slam pressure distribution in the zone I (around the forward columns).

Figure 19: Normalised slam pressure distribution in the zone II (forward middle section).

Figure 20: Normalised slam pressure distribution in the zone III (aft middle section).

Figure 21: Normalised slam pressure distribution in the zone IV (around the aft columns).

6.6 Correlation between tendon tensions and impact pressure

Maxima of tendon tensions and localised pressures in the forward and aft regions are presented in Figure 22. The figure suggests that correlation exists between the maximum tendon tension and the localised pressure measured around the columns of the deck underside in the respective part of the structure. In addition to the motion-induced forces, the magnitude of wave-in-deck slamming pressure may significantly contribute in the maximum tendon tensions, as evident from a number of wave events examined in this study. To confirm this finding, more investigations are still required.

Figure 22: Maximum tension measured in the up-wave tendon (Leg#1) and down-wave tendon (Leg#4) versus maximum pressure measured in the forward and aft sections of the deck underside.

7. Conclusions

This experimental investigation has provided detailed information on the global behaviour of a TLP due to wave-in-deck events in abnormal waves, which can be used for calibrating analytical tools and CFD models. The model test study is

1 focused on the wave-structure interaction irregular waves, without the presence of
2 the wind and current. Analysis of the measurements and observations of the model
3 response also enabled several general conclusions to be drawn. Presented below is
4 only a high-level summary of the findings.
5
6
7
8
9

10 **7.1 Variability of measurements in model test**

11 Based on the repeated test runs with identical wave trains, the wave
12 elevations, tendon tension and surge motion of the platform are found to have limited
13 variability (CV within 2.8 %). For the impact pressures, the variability is at least a
14 factor of 3 higher, with CV sometimes reaching 70%. This confirms a higher degree
15 of non-linearity of the impact pressure responses even though five repeated runs
16 were done for each sea state condition. It is therefore recommended that a sufficient
17 number of runs should be performed to allow for this variability of the measured
18 pressure.
19
20
21
22
23
24
25
26
27
28
29
30
31

32 **7.2 Platform dynamics and tendon tensions due to extreme wave impact**

33 In all extreme wave events, compliance of the floating platform in the
34 horizontal direction is seen as having a positive effect by reducing the relative
35 horizontal velocity and alleviating the horizontal wave-in-deck impact, compared with
36 a fixed structure. The maximum tension in the up-wave tendons usually occurred
37 when the wave crest reached the deck leading edge and the forward columns. The
38 maximum tension in the down-wave tendons occurred at about the same time and
39 exceeded tension in the up-wave tendons in some cases.
40
41
42
43
44
45
46
47
48
49
50
51
52

53 On average, the wave remained in contact with the deck LE over about 13%
54 of wave period, which is about 2.2 s at full scale; during this time the up-wave tendon
55 experienced its peak loading. In many cases, the down-wave tendons experienced a
56
57
58
59
60
61
62
63
64
65

1 rapid reduction in tension up to almost zero, which coincided with a relatively large
2 pitch angle in the down-wave direction, pointing to the effect of the hydrodynamic
3 suction force acting under the deck after the initial impact. This finding is supported
4 by the results of experimental studies (Abdussamie et al, 2016; Scharnke et al,
5 2014; Scharnke and Henning, 2015) on the wave-in-deck impact problems of fixed
6 decks, which determined that that the magnitude of the downward force caused by
7 the inertia of water flowing down can be as large as the upward impact force. The
8 instantaneous reduction in buoyancy of the aft columns subsequent to the deck
9 impact could also be a contributing factor to cause the tendon to become slack. The
10 slack tendon situations lasted for about 3 – 4 s at full scale. Such situations, if
11 encountered at full scale, may result in tendon disconnection and failure of the
12 platform.

13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
Maximum and minimum tensions experienced by the up-wave and down-wave tendons appeared to correlate with the steepness of the extreme wave: the maximum tensions increased and the minimum tension in the down-wave tendon reduced as the wave steepness increased. The wave events that produced the maximum and minimum tendon tension generally did not correspond to the largest wave crest or the largest wave steepness; this indicates that selection of the design wave event or wave train, in the same sea state, may require special attention.

66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184

7.3 Impact pressure on the deck underside

The overall trend in the maximum impact pressure, as a function of the deck exceedance, is generally consistent with that predicted by Wang (1970) for a fixed horizontal plate, but with a much broader variability. The forward part of the deck is found to experience higher pressures than the aft part, with the exception of the areas near the ends and around the columns, where this trend is reversed. This could be caused by the wave upwelling being larger around the aft columns and/or the effect of platform set-down as the platform offsets. Over all the wave events tested, the maximum impact pressures around the forward and aft columns show a positive correlation with the maximum tensions in the up-wave and down-wave tendons. This may suggest that the magnitude of wave-in-deck slamming pressure was large enough to rapidly increase the tendon tensions.

Acknowledgments

The authors would like to acknowledge the assistance from Mr Tim Lilienthal, Mr Kirk Meyer and Mr Liam Honeychurch at the AMC towing tank.

Reference

- Abdussamie, N. (2017). Data Set in MATLAB .fig file of "Experimental investigation of wave-in-deck impact events on a TLP model: Wave Event #1 (WE#1)".
https://www.researchgate.net/publication/317163075_Data_Set_in_MATLAB_fig_file_of_Experimental_investigation_of_wave-in-deck_impact_events_on_a_TLP_model.
- Abdussamie, N., Amin, W., Ojeda, R., Thomas, G. & Drobyshevski, Y. (2014). Irregular Wave Generation and Assessment of Static Air Gap of Offshore Structures. Proceedings of the 19th Australasian Fluid Mechanics Conference, Melbourne, Australia. AFMS.

- 1 Abdussamie, N., Ojeda, R., Drobyshevski, Y., Thomas, G. & Amin, W. (2016a).
2 Experimental Investigation of Extreme Wave Impacts on a Rigid TLP Model in
3 Cyclonic Conditions. *Ships and Offshore Structures*, 1-18.
- 4
5
6
7 Abdussamie, N., Ojeda, R., Thomas, G. & Amin, W. (2016b). Measurements of
8 Global and Local Effects of Wave Impact on a Fixed Platform Deck. *the*
9 *Proceedings of the Institution of Mechanical Engineers, Part M: Journal of*
10 *Engineers for the Maritime Environment*.
- 11
12
13
14
15
16
17 Almeland, I., Gaul, T., Pettersen, D. & Vogel, H. (1991). SNORRE TLP Configuration
18 and Analysis Technology. Proceedings of Offshore Technology Conference,
19 Houston, USA. Offshore Technology Conference.
- 20
21
22
23
24 Baarholm, R. (2009). Experimental and Theoretical Study of Three-Dimensional
25 Effects on Vertical Wave-in-Deck Forces. Proceedings of the ASME 28th Int.
26 Conf. on Ocean, Offshore and Arctic Eng., Honolulu, Hawaii, USA. ASME.
- 27
28
29
30
31 Baarholm, R., Faltinsen, O. & Herfjord, K. (2001). Wave Impact on Decks of Floating
32 Platforms. Practical Design of Ships and Other Floating Structures.
33 Proceedings of the Eighth International Symposium on Practical Design of
34 Ships and Other Floating Structures,.
- 35
36
37
38
39
40
41 Baarholm, R. & Faltinsen, O. M. (2004). Wave Impact Underneath Horizontal Decks.
42 *Journal of Marine Science and Technology*, 9, 1-13.
- 43
44
45
46 Baarholm, R. & Stansberg, C. T. (2005). Extreme Vertical Wave Impact on the Deck
47 of a Gravity-Based Structure (GBS) Platform. *Proc., Rogue Waves 2004*.
- 48
49
50
51 Bhat, S. S. (1994). *Wave Slamming on a Horizontal Plate*. MSc thesis, University of
52 British Columbia.
- 53
54
55
56 CD-Adapco (2012). User Guide - Star-Ccm+ Version 7.04. CD-Adapco.
- 57
58
59
60
61
62
63
64
65

- Chen, H.-C., Lee, S.-K. & Seah, A. K. (2008). Overset Grid CFD Applications for Challenging Offshore Hydrodynamic Problems. *ABS Technical Paper*.
- Deng, Y., Yang, J., Zhao, W., Li, X. & Xiao, L. (2016). Freak wave forces on a vertical cylinder. *Coastal Engineering*, 114, 9-18.
- DNV (2009). Offshore Standard Det Norske Veritas: Structural Design of TLPs (LRFD Method). Høvik, Norway: Det Norske Veritas, DNV.
- DNV (2010). Recommended Practice DNV-RP-C205: Environmental Conditions and Environmental Loads. Høvik, Norway: Det Norske Veritas, DNV.
- Fluent, A. (2009). Ansys Fluent 12.0 User Guide. *ANSYS Inc.*
- Hennig, J., Scharnke, J., Buchner, B. & van den Berg, J. (2011). Extreme Load-Response Mechanisms of a Tension Leg Platform Due to Larger Wave Crests: Some Results of the 'Crest'JIP. Proceedings of the ASME 30th Int. Conf. on Ocean, Offshore and Arctic Eng., Rotterdam, the Netherlands.
- Hirdaris, S. E., Bai, W., Dessi, D., Ergin, A., Gu, X., Hermundstad, O. A., Huijsmans, R., Iijima, K., Nielsen, U. D., Parunov, J., Fonseca, N., Papanikolaou, A., Argyriadis, K. & Incecik, A. (2014). Loads for Use in the Design of Ships and Offshore Structures. *Ocean engineering*, 78, 131-174.
- Johannessen, T., Haver, S., Bunnik, T. & Buchner, B. (2006). Extreme Wave Effects on Deep Water Tlps Lessons Learned from the Snorre a Model Tests. *Proc. Deep Offshore Technology*, 28-30.
- Kaiser, M. J., Yu, Y. & Jablonowski, C. J. (2009). Modeling Lost Production from Destroyed Platforms in the 2004–2005 Gulf of Mexico Hurricane Seasons. *Energy*, 34, 1156-1171.

- 1 Kaplan, P. (1992). Wave Impact Forces on Offshore Structures: Re-Examination and
2 New Interpretations. *Offshore Technology Conference, OTC 6814*, Houston,
3 TX.
4
5
6
7 Kaplan, P., Murray, J. & Yu, W. (1995). Theoretical Analysis of Wave Impact Forces
8 on Platform Deck Structures. Proceedings of the ASME 14th Int. Conf. on
9 Ocean, Offshore and Arctic Eng., Copenhagen, Denmark, 18–22 June. New
10 York: ASME.
11
12
13
14
15
16
17 Lee, S.-K., Yu, K. & Huang, S. C. (2014). CFD Study of Air-Gap and Wave Impact
18 Load on Semisubmersible under Hurricane Conditions. Proceedings of the
19 ASME 33rd Int. Conf. on Ocean, Offshore and Arctic Eng., 2014 San
20 Francisco, CA, USA. ASME.
21
22
23
24
25
26
27 Naess, A. & Gaidai, O. (2011). Extreme Value Statistics of Non-Gaussian Random
28 Wave Fields and the Airgap Problem for Offshore Platforms. Proceedings of
29 the 8th International Conference on Structural Dynamics, Leuven, Belgium.
30
31
32
33
34 Niedzwecki, J. & Huston, J. (1992). Wave Interaction with Tension Leg Platforms.
35 *Ocean engineering*, 19, 21-37.
36
37
38
39 Ransley, E. (2015). Survivability of Wave Energy Converter and Mooring Coupled
40 System using CFD. PhD thesis, University of Plymouth.
41
42
43
44 REUTERS. (2016). North Sea Storm Forces Oil Platform Evacuations, Output
45 Shutdown [Online]. Available: [http://www.reuters.com/article/us-weather-](http://www.reuters.com/article/us-weather-northsea-idUSKBN0UE0OR20151231)
46 [northsea-idUSKBN0UE0OR20151231](http://www.reuters.com/article/us-weather-northsea-idUSKBN0UE0OR20151231).
47
48
49
50
51 Rudman, M. & Cleary, P. W. (2013). Rogue Wave Impact on a Tension Leg
52 Platform: The Effect of Wave Incidence Angle and Mooring Line Tension.
53 *Ocean Engineering*, 61, 123-138.
54
55
56
57
58
59
60
61
62
63
64
65

- Scharnke, J. & Hennig, J. (2015). Vertical Wave Impact Loading on a Fixed Platform Deck. Proceedings of the ASME 34th Int. Conf. on Ocean, Offshore and Arctic Eng., St. John's, Newfoundland, Canada. American Society of Mechanical Engineers.
- Scharnke, J., Vestbostad, T., Wilde, J. d. & Haver, S. K. (2014). Wave-in-Deck Impact Load Measurements on a Fixed Platform Deck. Proceedings of the ASME 33rd Int. Conf. on Ocean, Offshore and Arctic Eng., San Francisco, CA, USA. American Society of Mechanical Engineers.
- Sun, J.-W., Sun, Z.-C., Liang, S.-X. & Zheng, K. (2011). Spectral Analysis of Random Wave Uplift Force on a Horizontal Deck. *Journal of Hydrodynamics, Ser. B*, 23, 81-88.
- Tromans, P. S., Anaturk, A. R. & Hagemeyer, P. (1991). A new model for the kinematics of large ocean waves-application as a design wave. Proceedings of the 1st International Offshore and Polar Engineering Conference, Edinburgh, The United Kingdom, International Society of Offshore and Polar Engineers.
- Wang, H. 1970. Water Wave Pressure on Horizontal Plate. *Journal of the Hydraulics Division*, 96, 1997-2017.
- Westphalen, J. (2011). Extreme Wave Loading on Offshore Wave Energy Devices using CFD. PhD thesis, University of Plymouth.
- Wu, G., Jang, H., Kim, J. W., Ma, W., Wu, M-C., O'Sullivan, J. (2014). Benchmark of CFD modeling of TLP free motion in extreme wave event. Proceedings of the ASME 33rd Int. Conf. on Ocean, Offshore and Arctic Eng., San Francisco, CA, USA. American Society of Mechanical Engineers.

Appendix

Wave event WE#1

Model scale (1:125): $H = 231$ mm, $\eta_c = 145$ mm, $T_z = 1.48$ s, $\lambda = 3.39$ m, $S = 0.068$

Fig.A 1: Simultaneous measurements: wave elevations (top); surge motion (middle); tendon tension (bottom).

Fig.A 2: Boxplots showing variation in impact pressure at different pressure transducers.

Wave event WE#2

Model scale (1:125): $H = 260$ mm, $\eta_c = 163$ mm, $T_z = 1.37$ s, $\lambda = 2.92$ m, $S = 0.089$

Fig.A 3: Simultaneous measurements: wave elevations (top); surge motion (middle); tendon tension (bottom).

Fig.A 4: Boxplots showing variation in impact pressure at different pressure transducers.

Wave event WE#3

Model scale (1:125): $H = 238$ mm, $\eta_c = 171$ mm, $T_z = 1.65$ s, $\lambda = 4.16$ m, $S = 0.057$

Fig.A 5: Simultaneous measurements: wave elevations (top); surge motion (middle); tendon tension (bottom).

Fig.A 6: Boxplots showing variation in impact pressure at different pressure transducers.

Wave event WE#4

Model scale (1:125): $H = 227$ mm, $\eta_c = 137$ mm, $T_z = 1.35$ s, $\lambda = 2.84$ m, $S = 0.08$

Fig.A 7: Simultaneous measurements: wave elevations (top); surge motion (middle); tendon tension (bottom).

Fig.A 8: Boxplots showing variation in impact pressure at different pressure transducers.

Wave event WE#5

Model scale (1:125): $H = 186$ mm, $\eta_c = 156$ mm, $T_z = 1.76$ s, $\lambda = 4.67$ m, $S = 0.04$

Fig.A 9: Simultaneous measurements: wave elevations (top); surge motion (middle); tendon tension (bottom).

Fig.A 10: Boxplots showing variation in impact pressure at different pressure transducers.

Wave event WE#6

Model scale (1:125): $H = 168$ mm, $\eta_c = 126$ mm, $T_z = 1.73$ s, $\lambda = 4.53$ m, $S = 0.037$

Fig.A 11: Simultaneous measurements: wave elevations (top); surge motion (middle); tendon tension (bottom).

Fig.A 12: Boxplots showing variation in impact pressure at different pressure transducers.

Wave event WE#7

Model scale (1:125): $H = 191$ mm, $\eta_c = 144$ mm, $T_z = 1.44$ s, $\lambda = 3.22$ m, $S = 0.059$

Fig.A 13: Simultaneous measurements: wave elevations (top); surge motion (middle); tendon tension (bottom).

Fig.A 14: Boxplots showing variation in impact pressure at different pressure transducers.

Wave event WE#8

Model scale (1:125): $H = 261$ mm, $\eta_c = 160$ mm, $T_z = 1.46$ s, $\lambda = 3.31$ m, $S = 0.079$

Fig.A 15: Simultaneous measurements: wave elevations (top); surge motion (middle); tendon tension (bottom).

Fig.A 16: Boxplots showing variation in impact pressure at different pressure transducers.